

Package ‘MiscMetabar’

March 8, 2024

Type Package

Title Miscellaneous Functions for Metabarcoding Analysis

Version 0.7.10

Description Facilitate the description, transformation, exploration, and reproducibility of metabarcoding analyses. ‘MiscMetabar’ is mainly built on top of the ‘phyloseq’, ‘dada2’ and ‘targets’ R packages. It helps to build reproducible and robust bioinformatics pipelines in R. ‘MiscMetabar’ makes ecological analysis of alpha and beta-diversity easier, more reproducible and more powerful by integrating a large number of tools. Important features are described in Taudière A. (2023) <[doi:10.21105/joss.06038](https://doi.org/10.21105/joss.06038)>.

License AGPL-3

Encoding UTF-8

LazyData true

Depends R (>= 3.5.0), phyloseq, ggplot2 (>= 3.5.0), dada2, dplyr

Suggests adespatial, ANCOMBC, BiocManager, Biostrings, circlize, ComplexUpset, DECIPHER, DESeq2, devtools, DT, edgeR, gghalves, ggh4x, ggstatsplot, ggridges, ggVennDiagram, gtsummary, grDevices, grid, gridExtra, here, httr, iNEXT, indicspecies, jsonlite, knitr, magrittr, metacoder, methods, mia, mixtools, multcompView, networkD3, pak, patchwork, permute, phangorn, phyloseqGraphTest, pbapply, plotly, plyr, purrr, reshape2, rmarkdown, rotl, Rtsne, scales, seqinr, SRS, stringr, SummarizedExperiment, testthat (>= 3.0.0), tibble, tidyverse, treemapify, vegan, vennuler, vctrs, viridis, withr

RoxygenNote 7.3.1

URL <https://github.com/adrientaudiere/MiscMetabar>,
<https://adrientaudiere.github.io/MiscMetabar/>

biocViews Sequencing, Microbiome, Metagenomics, Clustering, Classification, Visualization

BugReports <https://github.com/adrientaudiere/MiscMetabar/issues>

Imports ape, lifecycle, rlang, stats

Config/testthat/edition 3

Config/testthat/parallel true
VignetteBuilder knitr
Language en-US
NeedsCompilation no
Author Adrien Taudière [aut, cre, cph]
 (<<https://orcid.org/0000-0003-1088-1182>>)
Maintainer Adrien Taudière <adrien.taudiere@zaclys.net>
Repository CRAN
Date/Publication 2024-03-08 10:00:03 UTC

R topics documented:

| | |
|-----------------------------------|----|
| MiscMetabar-package | 4 |
| accu_plot | 5 |
| accu_samp_threshold | 6 |
| add_blast_info | 7 |
| add_dna_to_phyloseq | 8 |
| add_funguild_info | 9 |
| add_info_to_sam_data | 10 |
| add_new_taxonomy_pq | 11 |
| adonis_pq | 12 |
| all_object_size | 13 |
| ancombc_pq | 14 |
| are_modality_even_depth | 15 |
| asv2otu | 16 |
| as_binary_otu_table | 18 |
| biplot_pq | 19 |
| blast_pq | 21 |
| blast_to_derep | 22 |
| blast_to_phyloseq | 24 |
| build_phytree_pq | 26 |
| chimera_detection_vs | 28 |
| chimera_removal_vs | 29 |
| circle_pq | 30 |
| clean_pq | 32 |
| compare_pairs_pq | 33 |
| count_seq | 34 |
| cutadapt_remove_primers | 35 |
| data_fungi | 37 |
| data_fungi_mini | 38 |
| data_fungi_sp_known | 39 |
| diff_fct_diff_class | 39 |
| dist_bycol | 41 |
| dist_pos_control | 42 |
| filter_asv_blast | 43 |

| | |
|------------------------------------|----|
| filter_trim | 44 |
| funguild_assign | 45 |
| funky_color | 46 |
| get_file_extension | 47 |
| get_funguild_db | 47 |
| ggbetween_pq | 48 |
| ggvenn_pq | 49 |
| graph_test_pq | 51 |
| heat_tree_pq | 52 |
| hill_pq | 53 |
| hill_tuckey_pq | 55 |
| iNEXT_pq | 56 |
| is_cutadapt_installed | 57 |
| is_falco_installed | 58 |
| is_krona_installed | 59 |
| is_mumu_installed | 59 |
| is_swarm_installed | 60 |
| is_vsearch_installed | 61 |
| krona | 61 |
| LCBD_pq | 63 |
| list_fastq_files | 64 |
| lulu | 65 |
| lulu_pq | 67 |
| merge_krona | 68 |
| merge_samples2 | 69 |
| merge_taxa_vec | 71 |
| MiscMetabar-deprecated | 72 |
| multipatt_pq | 73 |
| multiplot | 74 |
| multitax_bar_pq | 75 |
| multi_biplot_pq | 76 |
| mumu_pq | 77 |
| perc | 78 |
| phyloseq_to_edgeR | 79 |
| physeq_or_string_to_dna | 80 |
| plot_deseq2_pq | 81 |
| plot_edgeR_pq | 83 |
| plot_guild_pq | 84 |
| plot_LCBD_pq | 85 |
| plot_mt | 87 |
| plot_SCBD_pq | 88 |
| plot_tax_pq | 89 |
| plot_tsne_pq | 91 |
| read_pq | 92 |
| rename_samples | 93 |
| rename_samples_otu_table | 94 |
| reorder_taxa_pq | 95 |
| ridges_pq | 96 |

| | |
|--------------------------------------|-----|
| rotl_pq | 97 |
| sample_data_with_new_names | 98 |
| sankey_pq | 99 |
| save_pq | 100 |
| search_exact_seq_pq | 101 |
| select_one_sample | 102 |
| select_taxa | 102 |
| simplify_taxo | 103 |
| SRS_curve_pq | 104 |
| subsample_fastq | 105 |
| subset_samples_pq | 106 |
| subset_taxa_pq | 106 |
| subset_taxa_tax_control | 108 |
| summary_plot_pq | 109 |
| swarm_clustering | 110 |
| tax_bar_pq | 112 |
| tax_datatable | 113 |
| tbl_sum_samdata | 114 |
| Tengeler2020_pq | 115 |
| track_wkflow | 116 |
| track_wkflow_samples | 117 |
| treemap_pq | 118 |
| tsne_pq | 119 |
| unique_or_na | 120 |
| upset_pq | 121 |
| upset_test_pq | 124 |
| venn_pq | 125 |
| verify_pq | 126 |
| vsearch_clustering | 127 |
| vs_search_global | 129 |
| write_pq | 130 |

| | |
|--------------|------------|
| Index | 133 |
|--------------|------------|

MiscMetabar-package *MiscMetabar package*

Description

Functions to help analyze and visualize metabarcoding data. Mainly based on the phyloseq and dada2 packages.

`accu_plot`

Plot accumulation curves for phyloseq-class object

Description

[Maturing]

Usage

```
accu_plot(  
  physeq,  
  fact = NULL,  
  add_nb_seq = TRUE,  
  step = NULL,  
  by.fact = FALSE,  
  ci_col = NULL,  
  col = NULL,  
  lwd = 3,  
  leg = TRUE,  
  print_sam_names = FALSE,  
  ci = 2,  
  ...  
)
```

Arguments

| | |
|-----------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| fact | (required) Name of the factor in physeq@sam_data used to plot different lines |
| add_nb_seq | (default: TRUE, logical) Either plot accumulation curves using sequences or using samples |
| step | (Integer) distance among points calculated to plot lines. A low value give better plot but is more time consuming. Only used if add_nb_seq = TRUE. |
| by.fact | (default: FALSE, logical) First merge the OTU table by factor to plot only one line by factor |
| ci_col | Color vector for confidence interval. Only use if add_nb_seq = FALSE. If add_nb_seq = TRUE, you can use ggplot to modify the plot. |
| col | Color vector for lines. Only use if add_nb_seq = FALSE. If add_nb_seq = TRUE, you can use ggplot to modify the plot. |
| lwd | (default: 3) thickness for lines. Only use if add_nb_seq = FALSE. |
| leg | (default: TRUE, logical) Plot legend or not. Only use if add_nb_seq = FALSE. |
| print_sam_names | (default: FALSE, logical) Print samples names or not? Only use if add_nb_seq = TRUE. |

- `ci` (default: 2, integer) Confidence interval value used to multiply the standard error to plot confidence interval
`...` Additional arguments passed on to `ggplot` if `add_nb_seq = TRUE` or to `plot` if `add_nb_seq = FALSE`

Value

A `ggplot2` plot representing the richness accumulation plot if `add_nb_seq = TRUE`, else, if `add_nb_seq = FALSE` return a base plot.

Author(s)

Adrien Taudière

See Also

`specaccum accu_samp_threshold()`

Examples

```
data("GlobalPatterns", package = "phyloseq")
GP <- subset_taxa(GlobalPatterns, GlobalPatterns@tax_table[, 1] == "Archaea")
GP <- rarefy_even_depth(subset_samples_pq(GP, sample_sums(GP) > 3000))
p <- accu_plot(GP, "SampleType", add_nb_seq = TRUE, by.fact = TRUE, step = 10)
p <- accu_plot(GP, "SampleType", add_nb_seq = TRUE, step = 10)

p + theme(legend.position = "none")

p + xlim(c(0, 400))
```

`accu_samp_threshold` *Compute the number of sequence to obtain a given proportion of ASV in accumulation curves*

Description

[Experimental]

Usage

`accu_samp_threshold(res_accumplot, threshold = 0.95)`

Arguments

- `res_accumplot` the result of the function `accu_plot()`
`threshold` the proportion of ASV to obtain in each samples

Value

a value for each samples of the number of sequences needed to obtain threshold proportion of the ASV

Author(s)

Adrien Taudière

See Also

[accu_plot\(\)](#)

Examples

```
data("GlobalPatterns", package = "phyloseq")
GP <- subset_taxa(GlobalPatterns, GlobalPatterns@tax_table[, 1] == "Archaea")
GP <- rarefy_even_depth(subset_samples_pq(GP, sample_sums(GP) > 3000))
p <- accu_plot(GP, "SampleType", add_nb_seq = TRUE, by.fact = TRUE, step = 10)

val_threshold <- accu_samp_threshold(p)

summary(val_threshold)

# Plot the number of sequences needed to accumulate 0.95% of ASV in 50%, 75%
# and 100% of samples
p + geom_vline(xintercept = quantile(val_threshold, probs = c(0.50, 0.75, 1)))
```

add_blast_info

Add information from [blast_pq\(\)](#) to the tax_table slot of a phyloseq object

Description**[Experimental]**

Basically a wrapper of [blast_pq\(\)](#) with option unique_per_seq = TRUE and score_filter = FALSE.

Add the information to the taxtable

Usage

```
add_blast_info(physeq, fasta_for_db, silent = FALSE, ...)
```

Arguments

| | |
|---------------------------|--|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>fasta_for_db</code> | path to a fasta file to make the blast database |
| <code>silent</code> | (logical) If true, no message are printing. |
| ... | Other arguments passed on to blast_pq() function. |

Value

a physeq object with more information in tax_table based on a blast on a given database

Author(s)

Adrien Taudière

`add_dna_to_phyloseq` *Add dna in refseq slot of a physeq object using taxa names and re-names taxa using ASV_1, ASV_2, ...*

Description

[Stable]

Usage

```
add_dna_to_phyloseq(physeq)
```

Arguments

| | |
|---------------------|--|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
|---------------------|--|

Value

A new [phyloseq-class](#) object with refseq slot and new taxa names

add_funguild_info *Add information about Guild for FUNGI the FUNGuild database*

Description

[Experimental]

Please cite Nguyen et al. 2016 ([doi:10.1016/j.funeco.2015.06.006](https://doi.org/10.1016/j.funeco.2015.06.006))

Usage

```
add_funguild_info(  
  physeq,  
  taxLevels = c("Kingdom", "Phylum", "Class", "Order", "Family", "Genus", "Species")  
)
```

Arguments

| | |
|-----------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| taxLevels | Name of the 7 columns in tax_table required by funguild |

Details

This function is mainly a wrapper of the work of others. Please make a reference to FUNGuildR package and the associate [publication](#) if you use this function.

Value

A new object of class physeq with Guild information added to tax_table slot

Author(s)

Adrien Taudière

See Also

[plot_guild_pq\(\)](#)

Examples

```
d_fung_mini <- add_funguild_info(data_fungi_mini,  
  taxLevels = c(  
    "Domain",  
    "Phylum",  
    "Class",  
    "Order",  
    "Family",  
    "Genus",
```

```

    "Species"
  )
)
sort(table(d_fung_mini@tax_table[, "guild"]), decreasing = TRUE)

```

add_info_to_sam_data *Add information to sample_data slot of a phyloseq-class object*

Description

[Experimental]

Warning: The value nb_seq and nb_otu may be outdated if you transform your phyloseq object, e.g. using the [subset_taxa_pq\(\)](#) function

Usage

```

add_info_to_sam_data(
  physeq,
  df_info = NULL,
  add_nb_seq = TRUE,
  add_nb_otu = TRUE
)

```

Arguments

| | |
|-------------------------|--|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>df_info</code> | : A dataframe with rownames matching for sample names of the phyloseq object |
| <code>add_nb_seq</code> | (Logical, default TRUE) Does we add a column nb_seq collecting the number of sequences per sample? |
| <code>add_nb_otu</code> | (Logical, default TRUE) Does we add a column nb_otu collecting the number of OTUs per sample? |

Value

A phyloseq object with an updated sam_data slot

Author(s)

Adrien Taudière

Examples

```
data_fungi <- add_info_to_sam_data(data_fungi)
boxplot(data_fungi@sam_data$nb_otu ~ data_fungi@sam_data$Time)

new_df <- data.frame(
  variable_1 = runif(n = nsamples(data_fungi), min = 1, max = 20),
  variable_2 = runif(n = nsamples(data_fungi), min = 1, max = 2)
)
rownames(new_df) <- sample_names(data_fungi)
data_fungi <- add_info_to_sam_data(data_fungi, new_df)
plot(data_fungi@sam_data$nb_otu ~ data_fungi@sam_data$variable_1)
```

`add_new_taxonomy_pq` *Add new taxonomic rank to a phyloseq object.*

Description

[Experimental]

One of main use of this function is to add taxonomic assignment from a new database.

Usage

```
add_new_taxonomy_pq(physeq, ref_fasta, suffix = NULL, ...)
```

Arguments

| | |
|------------------------|---|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>ref_fasta</code> | (required) A link to a database. Pass on to dada2::assignTaxonomy. |
| <code>suffix</code> | (character) The suffix to name the new columns. If set to NULL (the default), the basename of the file reFasta is used. |
| <code>...</code> | Others arguments pass on to dada2::assignTaxonomy. |

Value

a physeq object with a larger slot tax_table

Author(s)

Adrien Taudière

adonis_pq

Permanova on a phyloseq object

Description

[Experimental]

A wrapper for the [vegan::adonis2\(\)](#) function in the case of physeq object.

Usage

```
adonis_pq(
  physeq,
  formula,
  dist_method = "bray",
  merge_sample_by = NULL,
  na_remove = FALSE,
  correction_for_sample_size = FALSE,
  rarefy_nb_seqs = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

| | |
|----------------------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| formula | (required) the right part of a formula for vegan::adonis2() . Variables must be present in the physeq@sam_data slot. |
| dist_method | (default "bray") the distance used. See phyloseq::distance() for all available distances or run phyloseq::distanceMethodList() . For aitchison and robust.aitchison distance, vegan::vegdist() function is directly used. |
| merge_sample_by | a vector to determine which samples to merge using the merge_samples2() function. Need to be in physeq@sam_data |
| na_remove | (logical, default FALSE) If set to TRUE, remove samples with NA in the variables set in formula. |
| correction_for_sample_size | (logical, default FALSE) If set to TRUE, the sample size (number of sequences by samples) is add to formula in the form y~Library_Size + Biological_Effect following recommendation of Weiss et al. 2017 . correction_for_sample_size overcome rarefy_nb_seqs if both are TRUE. |
| rarefy_nb_seqs | (logical, default FALSE) Rarefy each sample (before merging if merge_sample_by is set) using phyloseq::rarefy_even_depth() . if correction_for_sample_size is TRUE, rarefy_nb_seqs will have no effect. |
| verbose | (logical, default TRUE) If TRUE, prompt some messages. |
| ... | Other arguments passed on to vegan::adonis2() function. |

Details

This function is mainly a wrapper of the work of others. Please make a reference to `vegan::adonis2()` if you use this function.

Value

The function returns an `anova.cca` result object with a new column for partial R^2. See help of `vegan::adonis2()` for more information.

Author(s)

Adrien Taudière

Examples

```
data(enterotype)
adonis_pq(enterotype, "SeqTech*Enterotype", na_remove = TRUE)
adonis_pq(enterotype, "SeqTech", dist_method = "jaccard")
adonis_pq(enterotype, "SeqTech", dist_method = "robust.aitchison")
```

all_object_size *List the size of all objects of the GlobalEnv.*

Description**[Stable]**

Code from <https://tolstoy.newcastle.edu.au/R/e6/help/09/01/1121.html>

Usage

```
all_object_size()
```

Value

a list of size

ancombc_pq*Run ANCOMBC2 on phyloseq object*

Description

[Experimental]

A wrapper for the [ANCOMBC::ancombc2\(\)](#) function

Usage

```
ancombc_pq(physeq, fact, levels_fact = NULL, tax_level = "Class", ...)
```

Arguments

| | |
|-------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| fact | (required) Name of the factor in physeq@sam_data used to plot different lines |
| levels_fact | (default NULL) The order of the level in the factor. Used for reorder levels and select levels (filter out levels not present en levels_fact) |
| tax_level | The taxonomic level passed on to ANCOMBC::ancombc2() |
| ... | Other arguments passed on to ANCOMBC::ancombc2() function. |

Details

This function is mainly a wrapper of the work of others. Please make a reference to [ANCOMBC::ancombc2\(\)](#) if you use this function.

Value

The result of [ANCOMBC::ancombc2\(\)](#) function

Author(s)

Adrien Taudière

Examples

```
res_height <- ancombc_pq(
  data_fungi_mini,
  fact = "Height",
  levels_fact = c("Low", "High"),
  verbose = TRUE
)

ggplot(
  res_height$res,
  aes(
```

```

    y = reorder(taxon, lfc_HeightHigh),
    x = lfc_HeightHigh,
    color = diff_HeightHigh
  )
) +
  geom_vline(xintercept = 0) +
  geom_segment(aes(
    xend = 0, y = reorder(taxon, lfc_HeightHigh),
    yend = reorder(taxon, lfc_HeightHigh)
  ), color = "darkgrey") +
  geom_point()

res_time <- ancombc_pq(
  data_fungi_mini,
  fact = "Time",
  levels_fact = c("0", "15"),
  tax_level = "Family",
  verbose = TRUE
)

```

are_modality_even_depth

Test if the mean number of sequences by samples is link to the modality of a factor

Description**[Experimental]**

The aim of this function is to provide a warnings if samples depth significantly vary among the modalities of a factor present in the `sam_data` slot.

This function apply a Kruskal-Wallis rank sum test to the number of sequences per samples in function of the factor `fact`.

Usage

```
are_modality_even_depth(physeq, fact, boxplot = FALSE)
```

Arguments

| | |
|----------------------|---|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the <code>phyloseq</code> package. |
| <code>fact</code> | (required): Name of the factor to cluster samples by modalities. Need to be in <code>physeq@sam_data</code> . |
| <code>boxplot</code> | (logical) Do you want to plot boxplot? |

Value

The result of a Kruskal-Wallis rank sum test

Author(s)

Adrien Taudière

Examples

```
are_modality_even_depth(data_fungi_mini, "Time")$p.value
are_modality_even_depth(rarefy_even_depth(data_fungi_mini), "Time")$p.value
are_modality_even_depth(data_fungi_mini, "Height", boxplot = TRUE)
```

asv2otu

Recluster sequences of an object of class physeq or a list of DNA sequences

Description

[Maturing]

Usage

```
asv2otu(
  physeq = NULL,
  dna_seq = NULL,
  nproc = 1,
  method = "clusterize",
  id = 0.97,
  vsearchpath = "vsearch",
  tax_adjust = 0,
  vsearch_cluster_method = "--cluster_size",
  vsearch_args = "--strand both",
  keep_temporary_files = FALSE,
  swarmpath = "swarm",
  d = 1,
  swarm_args = "--fastidious",
  method_clusterize = "overlap",
  ...
)
```

Arguments

| | |
|---------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| dna_seq | You may directly use a character vector of DNA sequences in place of physeq args. When physeq is set, dna sequences take the value of physeq@refseq |
| nproc | (default: 1) Set to number of cpus/processors to use for the clustering |
| method | (default: clusterize) Set the clustering method. <ul style="list-style-type: none"> • clusterize use the DECIPHER::Clusterize() fonction, |

- vsearch use the vsearch software (<https://github.com/torognes/vsearch>) with arguments --cluster_size by default (see args vsearch_cluster_method) and -strand both (see args vsearch_args)
 - swarm use the swarm
- `id` (default: 0.97) level of identity to cluster
- `vsearchpath` (default: vsearch) path to vsearch
- `tax_adjust` (Default 0) See the man page of [merge_taxa_vec\(\)](#) for more details. To conserved the taxonomic rank of the most abundant ASV, set tax_adjust to 0 (default). For the moment only tax_adjust = 0 is robust
- `vsearch_cluster_method` (default: "--cluster_size") See other possible methods in the [vsearch manual](#) (e.g. --cluster_size or --cluster_smallmem)
 - --cluster_fast : Clusterize the fasta sequences in filename, automatically sort by decreasing sequence length beforehand.
 - --cluster_size : Clusterize the fasta sequences in filename, automatically sort by decreasing sequence abundance beforehand.
 - --cluster_smallmem : Clusterize the fasta sequences in filename without automatically modifying their order beforehand. Sequence are expected to be sorted by decreasing sequence length, unless `-usersort` is used. In that case you may set vsearch_args to vsearch_args = "--strand both -usersort"
- `vsearch_args` (default : "-strand both") a one length character element defining other parameters to passed on to vsearch.
- `keep_temporary_files` (logical, default: FALSE) Do we keep temporary files
 - temp.fasta (refseq in fasta or dna_seq sequences)
 - cluster.fasta (centroid if method = "vsearch")
 - temp.uc (clusters if method = "vsearch")
- `swarmpath` (default: swarm) path to swarm
- `d` (default: 1) maximum number of differences allowed between two amplicons, meaning that two amplicons will be grouped if they have d (or less) differences
- `swarm_args` (default : "-fastidious") a one length character element defining other parameters to passed on to swarm See other possible methods in the [SWARM pdf manual](#)
- `method_clusterize` (default "overlap") the method for the [DECIPHER::Clusterize\(\)](#) method
- `...` Others arguments passed on to [DECIPHER::Clusterize\(\)](#)

Details

This function use the `merge_taxa_vec` function to merge taxa into clusters. By default `tax_adjust` = 0. See the man page of [merge_taxa_vec\(\)](#).

Value

A new object of class physeq or a list of cluster if dna_seq args was used.

Author(s)

Adrien Taudière

References

VSEARCH can be downloaded from <https://github.com/torognes/vsearch>. More information in the associated publication <https://pubmed.ncbi.nlm.nih.gov/27781170>.

See Also

[vsearch_clustering\(\)](#) and [swarm_clustering\(\)](#)

Examples

```
asv2otu(data_fungi_mini)

asv2otu(data_fungi_mini, method_clusterize = "longest")

if (MiscMetabar::is_swarm_installed()) {
  d_swarm <- asv2otu(data_fungi_mini, method = "swarm")
}
if (MiscMetabar::is_vsearch_installed()) {
  d_vs <- asv2otu(data_fungi_mini, method = "vsearch")
}
```

as_binary_otu_table *Transform the otu_table of a phyloseq-class object into a phyloseq-class object with a binary otu_table.*

Description

[Maturing]

Usage

```
as_binary_otu_table(physeq, min_number = 1)
```

Arguments

| | |
|------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| min_number | (int) the minimum number of sequences to put a 1 in the otu table. |

Value

A physeq object with only 0/1 in the OTU table

Note

Useful to test if the results are not biased by sequences bias that appended during PCR or NGS pipeline.

Author(s)

Adrien Taudière

Examples

```
data(enterotype)
enterotype_bin <- as_binary_otu_table(enterotype)
```

biplot_pq

Visualization of two samples for comparison

Description

[Maturing]

Usage

```
biplot_pq(
  physeq,
  fact = NULL,
  merge_sample_by = NULL,
  rarefy_after_merging = FALSE,
  inverse_side = FALSE,
  left_name = NULL,
  left_name_col = "#4B3E1E",
  left_fill = "#4B3E1E",
  left_col = "#f3f2d9",
  right_name = NULL,
  right_name_col = "#1d2949",
  right_fill = "#1d2949",
  right_col = "#1d2949",
  log10trans = TRUE,
  nudge_y = c(0.3, 0.3),
  geom_label = FALSE,
  text_size = 3,
  size_names = 5,
  y_names = NA,
  ylim_modif = c(1, 1),
  nb_samples_info = TRUE,
  plotly_version = FALSE,
  ...
)
```

Arguments

| | |
|-----------------------------------|---|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>fact</code> | (default: NULL) Name of the factor in physeq@sam_data. If left to NULL use the <code>left_name</code> and <code>right_name</code> parameter as modality. |
| <code>merge_sample_by</code> | (default: NULL) if not NULL samples of physeq are merged using the vector set by <code>merge_sample_by</code> . This merging used the merge_samples2() . In the case of biplot_pq() this must be a factor with two levels only. |
| <code>rarefy_after_merging</code> | Rarefy each sample after merging by the modalities <code>merge_sample_by</code> |
| <code>inverse_side</code> | Inverse the side (put the right modality in the left side). |
| <code>left_name</code> | Name fo the left sample. |
| <code>left_name_col</code> | Color for the left name |
| <code>left_fill</code> | Fill fo the left sample. |
| <code>left_col</code> | Color fo the left sample. |
| <code>right_name</code> | Name fo the right sample. |
| <code>right_name_col</code> | Color for the right name |
| <code>right_fill</code> | Fill fo the right sample. |
| <code>right_col</code> | Color fo the right sample. |
| <code>log10trans</code> | (logical) Does abundance is log10 transformed ? |
| <code>nudge_y</code> | A parameter to control the y position of abundance values. If a vector of two values are set. The first value is for the left side. and the second value for the right one. If one value is set, this value is used for both side. |
| <code>geom_label</code> | (default: FALSE, logical) if TRUE use the ggplot2::geom_label() function instead of ggplot2::geom_text() to indicate the numbers of sequences. |
| <code>text_size</code> | size for the number of sequences |
| <code>size_names</code> | size for the names of the 2 samples |
| <code>y_names</code> | y position for the names of the 2 samples. If NA (default), computed using the maximum abundances values. |
| <code>ylim_modif</code> | vector of two values. Modificator (by a multiplication) of ylim. If one value is set, this value is used for both limits. |
| <code>nb_samples_info</code> | (default: TRUE, logical) if TRUE and <code>merge_sample_by</code> is set, add the number of samples merged for both levels. |
| <code>plotly_version</code> | If TRUE, use plotly::ggplotly() to return a interactive ggplot. |
| ... | other arguments for the ggplot function |

Value

A plot

Author(s)

Adrien Taudière

Examples

```
data_fungi_2Height <- subset_samples(data_fungi_mini, Height %in% c("Low", "High"))
biplot_pq(data_fungi_2Height, "Height", merge_sample_by = "Height")
```

blast_pq

Blast all sequence of refseq slot of a phyloseq-class object against a custom database.

Description**[Experimental]****Usage**

```
blast_pq(
  physeq,
  fasta_for_db = NULL,
  database = NULL,
  blastpath = NULL,
  id_cut = 90,
  bit_score_cut = 50,
  min_cover_cut = 50,
  e_value_cut = 1e-30,
  unique_per_seq = FALSE,
  score_filter = TRUE,
  nproc = 1,
  args_makedb = NULL,
  args_blastn = NULL,
  keep_temporary_files = FALSE
)
```

Arguments

| | |
|----------------------------|--|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>fasta_for_db</code> | path to a fasta file to make the blast database |
| <code>database</code> | path to a blast database |
| <code>blastpath</code> | path to blast program |
| <code>id_cut</code> | (default: 90) cut off in identity percent to keep result |
| <code>bit_score_cut</code> | (default: 50) cut off in bit score to keep result The higher the bit-score, the better the sequence similarity. The bit-score is the negative log ₂ of a sequence database in which the current match could be found just by chance. The bit-score is a log ₂ scaled and normalized raw-score. Each increase by one doubles the required database size (2bit-score). |

| | |
|-----------------------------------|--|
| <code>min_cover_cut</code> | (default: 50) cut off in query cover (%) to keep result |
| <code>e_value_cut</code> | (default: 1e-30) cut off in e-value (%) to keep result The BLAST E-value is the number of expected hits of similar quality (score) that could be found just by chance. |
| <code>unique_per_seq</code> | (logical, default FALSE) if TRUE only return the better match (higher bit score) for each sequence |
| <code>score_filter</code> | (logical, default TRUE) does results are filtered by score? If FALSE, <code>id_cut</code> , <code>bit_score_cut</code> , <code>e_value_cut</code> and <code>min_cover_cut</code> are ignored |
| <code>nproc</code> | (default: 1) Set to number of cpus/processors to use for blast (args -num_threads for blastn command) |
| <code>args_makedb</code> | Additional parameters parse to makeblastdb command |
| <code>args_blastn</code> | Additional parameters parse to blastn command |
| <code>keep_temporary_files</code> | (logical, default: FALSE) Do we keep temporary files <ul style="list-style-type: none">• db.fasta (refseq transformed into a database)• dbase list of files (output of blastn)• blast_result.txt the summary result of blastn using -outfmt "6 qseqid qlen sseqid slen length p" |

Value

a blast table

See Also

[blast_to_phyloseq\(\)](#) to use refseq slot as a database

`blast_to_derep`

Blast some sequence against sequences from of a derep-class object.

Description

[Experimental]

Usage

```
blast_to_derep(
  derep,
  seq2search,
  blastpath = NULL,
  id_cut = 90,
  bit_score_cut = 50,
  min_cover_cut = 50,
  e_value_cut = 1e-30,
  unique_per_seq = FALSE,
  score_filter = FALSE,
```

```

    list_no_output_query = FALSE,
    min_length_seq = 200,
    args_makedb = NULL,
    args_blastn = NULL,
    nproc = 1,
    keep_temporary_files = FALSE
)

```

Arguments

| | |
|----------------------|--|
| derep | The result of dada2::derepFastq(). A list of derep-class object. |
| seq2search | (required) path to a fasta file defining the sequences you want to blast against the ASV sequences from the physeq object. |
| blastpath | path to blast program |
| id_cut | (default: 90) cut off in identity percent to keep result |
| bit_score_cut | (default: 50) cut off in bit score to keep result The higher the bit-score, the better the sequence similarity. The bit-score is the required size of a sequence database in which the current match could be found just by chance. The bit-score is a log2 scaled and normalized raw-score. Each increase by one doubles the required database size (2bit-score). |
| min_cover_cut | (default: 50) cut off in query cover (%) to keep result |
| e_value_cut | (default: 1e-30) cut off in e-value (%) to keep result The BLAST E-value is the number of expected hits of similar quality (score) that could be found just by chance. |
| unique_per_seq | (logical, default FALSE) if TRUE only return the better match (higher bit score) for each sequence |
| score_filter | (logical, default TRUE) does results are filtered by score? If FALSE, id_cut, bit_score_cut, e_value_cut and min_cover_cut are ignored |
| list_no_output_query | (logical) does the result table include query sequences for which blastn does not find any correspondence? |
| min_length_seq | (default: 200) Removed sequences with less than min_length_seq from derep before blast. Set to 0 to discard filtering sequences by length. |
| args_makedb | Additional parameters parse to makeblastdb command |
| args_blastn | Additional parameters parse to blastn command |
| nproc | (default: 1) Set to number of cpus/processors to use for blast (args -num_threads for blastn command) |
| keep_temporary_files | (logical, default: FALSE) Do we keep temporary files : <ul style="list-style-type: none"> • db.fasta (refseq transformed into a database) • dbase list of files (output of blastn) • blast_result.txt the summary result of blastn using -outfmt "6 qseqid qlen sseqid slen length p" |

Value

A blast table

Author(s)

Adrien Taudière

See Also

[blast_pq\(\)](#) to use refseq slot as query sequences against un custom database and [blast_to_phyloseq\(\)](#) to use refseq slot as a database

| | |
|--------------------------|--|
| blast_to_phyloseq | <i>Blast some sequence against refseq slot of a phyloseq-class object.</i> |
|--------------------------|--|

Description

[Maturing]

Usage

```
blast_to_phyloseq(
  physeq,
  seq2search,
  blastpath = NULL,
  id_cut = 90,
  bit_score_cut = 50,
  min_cover_cut = 50,
  e_value_cut = 1e-30,
  unique_per_seq = FALSE,
  score_filter = TRUE,
  list_no_output_query = FALSE,
  args_makedb = NULL,
  args_blastn = NULL,
  nproc = 1,
  keep_temporary_files = FALSE
)
```

Arguments

| | |
|-------------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| seq2search | (required) path to a fasta file defining the sequences you want to blast against the ASV sequences from the physeq object. |
| blastpath | path to blast program |
| id_cut | (default: 90) cut off in identity percent to keep result |

| | |
|-----------------------------------|--|
| <code>bit_score_cut</code> | (default: 50) cut off in bit score to keep result The higher the bit-score, the better the sequence similarity. The bit-score is the requires size of a sequence database in which the current match could be found just by chance. The bit-score is a log2 scaled and normalized raw-score. Each increase by one doubles the required database size (2bit-score). |
| <code>min_cover_cut</code> | (default: 50) cut off in query cover (%) to keep result |
| <code>e_value_cut</code> | (default: 1e-30) cut off in e-value (%) to keep result The BLAST E-value is the number of expected hits of similar quality (score) that could be found just by chance. |
| <code>unique_per_seq</code> | (logical, default FALSE) if TRUE only return the better match (higher bit score) for each sequence |
| <code>score_filter</code> | (logical, default TRUE) does results are filter by score? If FALSE, <code>id_cut</code> , <code>bit_score_cut</code> , <code>e_value_cut</code> and <code>min_cover_cut</code> are ignored |
| <code>list_no_output_query</code> | (logical) does the result table include query sequences for which blastn does not find any correspondence? |
| <code>args_makedb</code> | Additional parameters parse to makeblastdb command |
| <code>args_blastn</code> | Additional parameters parse to blastn command |
| <code>nproc</code> | (default: 1) Set to number of cpus/processors to use for blast (args -num_threads for blastn command) |
| <code>keep_temporary_files</code> | (logical, default: FALSE) Do we keep temporary files <ul style="list-style-type: none">• db.fasta (refseq transformed into a database)• dbase list of files (output of blastn)• blast_result.txt the summary result of blastn using -outfmt "6 qseqid qlen sseqid slen length p" |

Value

the blast table

See Also

[blast_pq\(\)](#) to use refseq slot as query sequences against un custom database.

Examples

```
## Not run:

blastpath <- "...YOUR_PATH_TO_BLAST..."
blast_to_phyloseq(data_fungi,
  seq2search = system.file("extdata", "ex.fasta",
    package = "MiscMetabat", mustWork = TRUE
  ),
  blastpath = blastpath
)
## End(Not run)
```

`build_phytree_pq`*Build phylogenetic trees from refseq slot of a phyloseq object*

Description

[Experimental]

This function build tree phylogenetic tree and if nb_bootstrap is set, it build also the 3 corresponding bootstrapped tree.

Default parameters are based on [doi:10.12688/f1000research.8986.2](https://doi.org/10.12688/f1000research.8986.2) and phangorn vignette [Estimating phylogenetic trees with phangorn](#). You should understand your data, especially the markers, before using this function.

Note that phylogenetic reconstruction with markers used for metabarcoding are not robust. You must verify the robustness of your phylogenetic tree using taxonomic classification (see vignette [Tree visualization](#)) and bootstrap or multi-tree visualization

Usage

```
build_phytree_pq(
  physeq,
  nb_bootstrap = 0,
  model = "GTR",
  optInv = TRUE,
  optGamma = TRUE,
  rearrangement = "NNI",
  control = phangorn::pml.control(trace = 0),
  optNni = TRUE,
  multicore = FALSE,
  ...
)
```

Arguments

| | |
|----------------------------|---|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>nb_bootstrap</code> | (default 0): If a positive number is set, the function also build 3 bootstrapped trees using <code>nb_bootstrap</code> bootstrap samples |
| <code>model</code> | allows to choose an amino acid models or nucleotide model, see phangorn::optim.pml() for more details |
| <code>optInv</code> | Logical value indicating whether topology gets optimized (NNI). See phangorn::optim.pml() for more details |
| <code>optGamma</code> | Logical value indicating whether gamma rate parameter gets optimized. See phangorn::optim.pml() for more details |
| <code>rearrangement</code> | type of tree tree rearrangements to perform, one of "NNI", "stochastic" or "ratchet" see phangorn::optim.pml() for more details |

| | |
|-----------|--|
| control | A list of parameters for controlling the fitting process. see phangorn::optim.pml() for more details |
| optNni | Logical value indicating whether topology gets optimized (NNI). see phangorn::optim.pml() for more details |
| multicore | (logical) whether models should estimated in parallel. see phangorn::bootstrap.pml() for more details |
| ... | other params for be passed on to phangorn::optim.pml() function |

Details

This function is mainly a wrapper of the work of others. Please make a reference to phangorn package if you use this function.

Value

A list of phylogenetic tree

Author(s)

Adrien Taudière

Examples

```
if (!requireNamespace("phangorn")) {
  df <- subset_taxa_pq(data_fungi_mini, taxa_sums(data_fungi_mini) > 9000)
  df_tree <- build_phytree_pq(df, nb_bootstrap = 2)
  plot(df_tree$UPGMA)
  phangorn::plotBS(df_tree$UPGMA, df_tree$UPGMA_bs, main = "UPGMA")
  plot(df_tree$NJ, "unrooted")
  plot(df_tree$ML)

  phangorn::plotBS(df_tree$ML$tree, df_tree$ML_bs, p = 20, frame = "circle")
  phangorn::plotBS(
    df_tree$ML$tree,
    df_tree$ML_bs,
    p = 20,
    frame = "circle",
    method = "TBE"
  )
  plot(phangorn::consensusNet(df_tree$ML_bs))
  plot(phangorn::consensusNet(df_tree$NJ_bs))
  ps_tree <- merge_phyloseq(df, df_tree$ML$tree)
}
```

chimera_detection_vs *Detect for chimera taxa using R href="https://github.com/torognes/vsearchvsearch*

Description

[Experimental]

Usage

```
chimera_detection_vs(
  seq2search,
  nb_seq,
  vsearchpath = "vsearch",
  abskew = 2,
  min_seq_length = 100,
  vsearch_args = "--fasta_width 0",
  keep_temporary_files = FALSE
)
```

Arguments

| | |
|----------------------|--|
| seq2search | (required) a list of DNA sequences coercible by function Biostrings::DNAStringSet() |
| nb_seq | (required) a numeric vector giving the number of sequences for each DNA sequences |
| vsearchpath | (default: vsearch) path to vsearch |
| abskew | (int, default 2) The abundance skew is used to distinguish in a three way alignment which sequence is the chimera and which are the parents. The assumption is that chimeras appear later in the PCR amplification process and are therefore less abundant than their parents. The default value is 2.0, which means that the parents should be at least 2 times more abundant than their chimera. Any positive value equal or greater than 1.0 can be used. |
| min_seq_length | (int, default 100)) Minimum length of sequences to be part of the analysis |
| vsearch_args | (default "-fasta_width 0") A list of other args for vsearch command |
| keep_temporary_files | (logical, default: FALSE) Do we keep temporary files ? <ul style="list-style-type: none"> • non_chimeras.fasta • chimeras.fasta • borderline.fasta |

Details

This function is mainly a wrapper of the work of others. Please make [vsearch](#).

Value

A list of 3 including non-chimera taxa (\$non_chimera), chimera taxa (\$chimera) and borderline taxa (\$borderline)

Author(s)

Adrien Taudière

Examples

```
chimera_detection_vs(
  seq2search = data_fungi@refseq,
  nb_seq = taxa_sums(data_fungi)
)
```

| | |
|--------------------|---|
| chimera_removal_vs | <i>Search for a list of sequence in an object to remove chimera taxa using R href="https://github.com/torognes/vsearchvsearch</i> |
|--------------------|---|

Description

[Experimental]

Usage

```
chimera_removal_vs(object, type = "Discard_only_chim", clean_pq = FALSE, ...)
```

Arguments

| | |
|----------|--|
| object | (required) A phyloseq-class object or one of dada, derep, data.frame or list coercible to sequences table using the function <code>dada2::makeSequenceTable()</code> |
| type | (default "Discard_only_chim"). The type define the type of filtering. <ul style="list-style-type: none"> "Discard_only_chim" will only discard taxa classify as chimera by vsearch "Select_only_non_chim" will only select taxa classify as non-chimera by vsearch(after filtering taxa based on their sequence length by the parameter <code>min_seq_length</code> from the <code>chimera_detection_vs()</code> function) "Select_only_chim" will only select taxa classify as chimera by vsearch (after filtering taxa based on their sequence length by the parameter <code>min_seq_length</code> from the <code>chimera_detection_vs()</code> function) |
| clean_pq | (logical; default FALSE) If TRUE, return the phyloseq object after cleaning using the default parameter of <code>clean_pq()</code> function. |
| ... | Others arguments passed on to <code>chimera_detection_vs()</code> function |

Details

This function is mainly a wrapper of the work of others. Please make [vsearch](#).

Value

- I/ a sequences tables () if object is of class dada, derep, data.frame or list.
- II/ a phyloseq object without (or with if type = 'Select_only_chim') chimeric taxa

Author(s)

Adrien Taudière

See Also

[chimera_detection_vs\(\)](#)

Examples

```
data_fungi_nochim <- chimera_removal_vs(data_fungi)
data_fungi_nochim_16 <- chimera_removal_vs(data_fungi,
  abskew = 16,
  min_seq_length = 10
)
data_fungi_nochim2 <-
  chimera_removal_vs(data_fungi, type = "Select_only_non_chim")
data_fungi_chimera <-
  chimera_removal_vs(data_fungi, type = "Select_only_chim")
```

circle_pq

Plot OTU circle for phyloseq-class object

Description

[Maturing]

Usage

```
circle_pq(
  physeq = NULL,
  fact = NULL,
  taxa = "Order",
  nproc = 1,
  add_nb_seq = TRUE,
  rarefy = FALSE,
```

```

min_prop_tax = 0.01,
min_prop_mod = 0.1,
gap_degree = NULL,
start_degree = NULL,
row_col = NULL,
grid_col = NULL,
log10trans = FALSE,
...
)

```

Arguments

| | |
|--------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| fact | (required) Name of the factor to cluster samples by modalities. Need to be in physeq@sam_data. |
| taxa | (default: 'Order') Name of the taxonomic rank of interest |
| nproc | (default 1) Set to number of cpus/processors to use for parallelization |
| add_nb_seq | (default: TRUE) Represent the number of sequences or the number of OTUs (add_nb_seq = FALSE) |
| rarefy | (logical) Does each samples modalities need to be rarefy in order to compare them with the same amount of sequences? |
| min_prop_tax | (default: 0.01) The minimum proportion for taxon to be plotted |
| min_prop_mod | (default: 0.1) The minimum proportion for modalities to be plotted |
| gap_degree | Gap between two neighbour sectors. It can be a single value or a vector. If it is a vector, the first value corresponds to the gap after the first sector. |
| start_degree | The starting degree from which the circle begins to draw. Note this degree is measured in the standard polar coordinate which means it is always reverse-clockwise. |
| row_col | Color vector for row |
| grid_col | Grid colors which correspond to sectors. The length of the vector should be either 1 or the number of sectors. It's preferred that grid_col is a named vector of which names correspond to sectors. If it is not a named vector, the order of grid_col corresponds to order of sectors. |
| log10trans | (logical) Should sequence be log10 transformed (more precisely by log10(1+x))? |
| ... | Additional arguments passed on to chordDiagram or circos.par |

Value

A [chordDiagram](#) plot representing the distribution of OTUs or sequences in the different modalities of the factor fact

Author(s)

Adrien Taudière

See Also

[chordDiagram](#)
[circos.par](#)

Examples

```
data("GlobalPatterns", package = "phyloseq")
GP <- subset_taxa(GlobalPatterns, GlobalPatterns@tax_table[, 1] == "Archaea")
circle_pq(GP, "SampleType")
circle_pq(GP, "SampleType", add_nb_seq = FALSE)
circle_pq(GP, "SampleType", taxa = "Class")
```

clean_pq*Clean phyloseq object by removing empty samples and taxa***Description****[Experimental]**

In addition, this function check for discrepancy (and rename) between (i) taxa names in refseq, taxonomy table and otu_table and between (ii) sample names in sam_data and otu_table.

Usage

```
clean_pq(
  physeq,
  remove_empty_samples = TRUE,
  remove_empty_taxa = TRUE,
  clean_samples_names = TRUE,
  silent = FALSE,
  verbose = FALSE,
  force_taxa_as_columns = FALSE,
  force_taxa_as_rows = FALSE,
  reorder_asv = FALSE,
  rename_asv = FALSE,
  simplify_taxo = FALSE
)
```

Arguments

| | |
|-----------------------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| remove_empty_samples | (logical) Do you want to remove samples without sequences (this is done after removing empty taxa) |

```

remove_empty_taxa
  (logical) Do you want to remove taxa without sequences (this is done before
  removing empty samples)
clean_samples_names
  (logical) Do you want to clean samples names?
silent      (logical) If true, no message are printing.
verbose     (logical) Additional informations in the message the verbose parameter over-
  write the silent parameter.
force_taxa_as_columns
  (logical) If true, if the taxa are rows transpose the otu_table and set taxa_are_rows
  to false
force_taxa_as_rows
  (logical) If true, if the taxa are columns transpose the otu_table and set taxa_are_rows
  to true
reorder_asv   (logical) if TRUE the otu_table is ordered by the number of sequences of ASV
  (descending order). Default to FALSE.
rename_asv    (logical) if TRUE, ASV are renamed by their position in the OTU_table (asv_1,
  asv_2, ...). Default to FALSE. If rename ASV is true, the ASV names in verbose
  information can be misleading.
simplify_taxo (logical) if TRUE, correct the taxonomy_table using the MiscMetabar::simplify_taxo()
  function

```

Value

A new [phyloseq-class](#) object

| | |
|------------------|---|
| compare_pairs_pq | <i>Compare samples in pairs using diversity and number of ASV includ- ing shared ASV.</i> |
|------------------|---|

Description

[Experimental] #' For the moment refseq slot need to be not Null.

Usage

```

compare_pairs_pq(
  physeq = NULL,
  bifactor = NULL,
  modality = NULL,
  merge_sample_by = NULL,
  nb_min_seq = 0,
  veg_index = "shannon",
  na_remove = TRUE
)

```

Arguments

| | |
|------------------------------|--|
| <code>physeq</code> | (required): a <code>phyloseq-class</code> object obtained using the <code>phyloseq</code> package. |
| <code>bifactor</code> | (required) a factor (present in the <code>sam_data</code> slot of the <code>physeq</code> object) presenting the pair names |
| <code>modality</code> | the name of the column in the <code>sam_data</code> slot of the <code>physeq</code> object to split samples by pairs |
| <code>merge_sample_by</code> | a vector to determine which samples to merge using the <code>merge_samples2()</code> function. Need to be in <code>physeq@sam_data</code> |
| <code>nb_min_seq</code> | minimum number of sequences per sample to count the ASV/OTU |
| <code>veg_index</code> | (default: "shannon") index for the <code>vegan::diversity</code> function |
| <code>na_remove</code> | (logical, default TRUE) If set to TRUE, remove samples with NA in the variables set in <code>bifactor</code> , <code>modality</code> and <code>merge_sample_by</code> . NA in variables are well managed even if <code>na_remove</code> = FALSE, so <code>na_remove</code> may be useless. |

Value

A tibble with information about the number of shared ASV, shared number of sequences and diversity

Examples

```
data_fungi_low_high <- subset_samples(data_fungi, Height %in% c("Low", "High"))
compare_pairs_pq(data_fungi_low_high, bifactor = "Height", merge_sample_by = "Height")
compare_pairs_pq(data_fungi_low_high,
  bifactor = "Height",
  merge_sample_by = "Height", modality = "Time"
)
```

`count_seq`*Count sequences in fasta or fastq file***Description**

[Experimental] Use grep to count the number of line with only one '+' (fastq, fastq.gz) or lines starting with a '>' (fasta) to count sequences.

Usage

```
count_seq(file_path = NULL, folder_path = NULL, pattern = NULL)
```

Arguments

| | |
|--------------------------|---|
| <code>file_path</code> | The path to a fasta, fastq or fastq.gz file |
| <code>folder_path</code> | The path to a folder with fasta, fastq or fastq.gz files |
| <code>pattern</code> | A pattern to filter files in a folder. E.g. <code>R2</code> |

Value

the number of sequences

Author(s)

Adrien Taudière

Examples

```
count_seq(file_path = system.file(
  "extdata",
  "ex.fasta",
  package = "MiscMetabar",
  mustWork = TRUE
))
count_seq(
  folder_path = system.file("extdata", package = "MiscMetabar"),
  pattern = "*.fasta"
)
```

cutadapt_remove_primers

Remove primers using R <https://github.com/marcelm/cutadapt/cutadapt>

Description**[Experimental]**

You need to install Cutadapt

[Experimental]**Usage**

```
cutadapt_remove_primers(
  path_to_fastq,
  primer_fw = NULL,
  primer_rev = NULL,
  folder_output = "wo_primers",
  nproc = 1,
  pattern = "fastq.gz",
  pattern_R1 = "_R1",
  pattern_R2 = "_R2",
  nb_files = Inf,
  cmd_is_run = TRUE,
  args_before_cutadapt =
    "source ~/miniconda3/etc/profile.d/conda.sh && conda activate cutadaptenv && "
)
```

Arguments

path_to_fastq (Required) A path to a folder with fastq files. See [list_fastq_files\(\)](#) for help.

primer_fw (Required, String) The forward primer DNA sequence.

primer_rev (String) The reverse primer DNA sequence.

folder_output The path to a folder for output files

nproc (default 1) Set to number of cpus/processors to use for the clustering

pattern a pattern to filter files (passed on to list.files function).

pattern_R1 a pattern to filter R1 files (default "R1")

pattern_R2 a pattern to filter R2 files (default "R2")

nb_files the number of fastq files to list (default FALSE)

cmd_is_run (logical, default TRUE) Do the cutadapt command is run. If set to FALSE, the only effect of the function is to return a list of command to manually run in a terminal.

args_before_cutadapt
 (String) A one line bash command to run before to run cutadapt. For examples, "source ~/miniconda3/etc/profile.d/conda.sh && conda activate cutadaptenv &&" allow to bypass the conda init which asks to restart the shell

Details

This function is mainly a wrapper of the work of others. Please cite cutadapt ([doi:10.14806/ej.17.1.200](#)).

Value

a list of command and

Author(s)

Adrien Taudière

Examples

```
## Not run:
cutadapt_remove_primers("inst/extdata", "TTC", "GAA",
  folder_output = tempdir()
)

cutadapt_remove_primers(
  system.file("extdata",
    package = "dada2"
  ),
  pattern_R1 = "F.fastq.gz",
  pattern_R2 = "R.fastq.gz",
```

```
primer_fw = "TTC",
primer_rev = "GAA",
folder_output = tempdir()
)

cutadapt_remove_primers(
  system.file("extdata",
    package = "dada2"
  ),
  pattern_R1 = "F.fastq.gz",
  primer_fw = "TTC",
  folder_output = tempdir(),
  cmd_is_run = FALSE
)

unlink(tempdir(), recursive = TRUE)

## End(Not run)
```

data_fungi*Fungal OTU in phyloseq format*

Description

Fungal OTU in phyloseq format

Usage

```
data(data_fungi)
```

Format

A physeq object containing 1420 taxa with references sequences described by 14 taxonomic ranks and 185 samples described by 7 sample variables:

- *X*: the name of the fastq-file
- *Sample_names*: the names of ... the samples
- *Treename*: the name of an tree
- *Sample_id*: identifier for each sample
- *Height*: height of the sample in the tree
- *Diameter*: diameter of the trunk
- *Time*: time since the dead of the tree

| | |
|-----------------|--------------------------------------|
| data_fungi_mini | <i>Fungal OTU in phyloseq format</i> |
|-----------------|--------------------------------------|

Description

It is a subset of the `data_fungi` dataset including only Basidiomycota with more than 5000 sequences.

Usage

```
data(data_fungi_mini)

data(data_fungi_mini)
```

Format

A physeq object containing 45 taxa with references sequences described by 14 taxonomic ranks and 137 samples described by 7 sample variables:

- *X*: the name of the fastq-file
- *Sample_names*: the names of ... the samples
- *Treename*: the name of an tree
- *Sample_id*: identifier for each sample
- *Height*: height of the sample in the tree
- *Diameter*: diameter of the trunk
- *Time*: time since the dead of the tree

A physeq object containing 45 taxa with references sequences described by 14 taxonomic ranks and 137 samples described by 7 sample variables:

- *X*: the name of the fastq-file
- *Sample_names*: the names of ... the samples
- *Treename*: the name of an tree
- *Sample_id*: identifier for each sample
- *Height*: height of the sample in the tree
- *Diameter*: diameter of the trunk
- *Time*: time since the dead of the tree

Details

Obtain using `data_fungi_mini <- subset_taxa(data_fungi, Phylum == "Basidiomycota")` and then `data_fungi_mini <- subset_taxa_pq(data_fungi_mini, colSums(data_fungi_mini@otu_table) > 5000)`

data_fungi_sp_known *Fungal OTU in phyloseq format*

Description

It is a subset of the data_fungi dataset including only taxa with information at the species level

Usage

```
data(data_fungi_sp_known)
```

Format

A physeq object containing 651 taxa with references sequences described by 14 taxonomic ranks and 185 samples described by 7 sample variables:

- *X*: the name of the fastq-file
- *Sample_names*: the names of ... the samples
- *Treename*: the name of an tree
- *Sample_id*: identifier for each sample
- *Height*: height of the sample in the tree
- *Diameter*: diameter of the trunk
- *Time*: time since the dead of the tree

Details

Obtain using `data_fungi_sp_known <- subset_taxa(data_fungi, !is.na(data_fungi@tax_table[, "Species"]))`

diff_fct_diff_class *Compute different functions for different class of vector.*

Description

[Experimental] Mainly an internal function useful in "lapply(..., tapply)" methods

Usage

```
diff_fct_diff_class(  
  x,  
  numeric_fonction = mean,  
  logical_method = "TRUE_if_one",  
  character_method = "unique_or_na",  
  ...  
)
```

Arguments

`x` : a vector
`numeric_fonction` : a function for numeric vector. For ex. `sum` or `mean`
`logical_method` : A method for logical vector. One of :
 • `TRUE_if_one` (default)
 • `NA_if_not_all_TRUE`
 • `FALSE_if_not_all_TRUE`
`character_method` : A method for character vector (and factor). One of :
 • `unique_or_na` (default)
 • `more_frequent`
 • `more_frequent_without_equality`
`...` other arguments passed on to the numeric function (ex. `na.rm=TRUE`)

Value

a single value

Author(s)

Adrien Taudière

Examples

```
diff_fct_diff_class(
  data_fungi@sam_data$Sample_id,
  numeric_fonction = sum,
  na.rm = TRUE
)
diff_fct_diff_class(
  data_fungi@sam_data$Time,
  numeric_fonction = mean,
  na.rm = TRUE
)
diff_fct_diff_class(
  data_fungi@sam_data$Height == "Low",
  logical_method = "TRUE_if_one"
)
diff_fct_diff_class(
  data_fungi@sam_data$Height == "Low",
  logical_method = "NA_if_not_all_TRUE"
)
diff_fct_diff_class(
  data_fungi@sam_data$Height == "Low",
  logical_method = "FALSE_if_not_all_TRUE"
)
diff_fct_diff_class(
```

```

    data_fungi@sam_data$Height,
    character_method = "unique_or_na"
)
diff_fct_diff_class(
  c("IE", "IE"),
  character_method = "unique_or_na"
)
diff_fct_diff_class(
  c("IE", "IE", "TE", "TE"),
  character_method = "more_frequent"
)
diff_fct_diff_class(
  c("IE", "IE", "TE", "TE"),
  character_method = "more_frequent_without_equality"
)

```

dist_bycol*Compute paired distances among matrix (e.g. otu_table)***Description****[Experimental]****Usage**

```
dist_bycol(x, y, method = "bray", nperm = 99, ...)
```

Arguments

| | |
|---------------------|---|
| <code>x</code> | (required) A first matrix. |
| <code>y</code> | (required) A second matrix. |
| <code>method</code> | (default: 'bray') the method to use internally in the vegdist function. |
| <code>nperm</code> | (default: 99) The number of permutations |
| <code>...</code> | others argument for vegan::vegdist function |

Value

A list of length two : (i) a vector of observed distance (\$obs) and (ii) a matrix of the distance after randomization (\$null)

Note

the first column of the first matrix is compare to the first column of the second matrix, the second column of the first matrix is compare to the second column of the second matrix and so on.

Author(s)

Adrien Taudière

See Also[vegdist](#)

| | |
|-------------------------------|--|
| <code>dist_pos_control</code> | <i>Calculate ecological distance among positive controls vs distance for all samples</i> |
|-------------------------------|--|

Description**[Experimental]**

Compute distance among positive controls, i.e. samples which are duplicated to test for variation, for example in (i) a step in the sampling, (ii) a step in the extraction, (iii) a step in the sequencing.

Usage

```
dist_pos_control(physeq, samples_names, method = "bray")
```

Arguments

- `physeq` (required): a [phyloseq-class](#) object obtained using the phyloseq package.
- `samples_names` (required) a vector of names for samples with positives controls of the same samples having the same name
- `method` (default: "bray") a method to calculate the distance, parsed to [vegan::vegdist\(\)](#). See ?vegdist for a list of possible values.

Value

A list of two data-frames with (i) the distance among positive controls and (ii) the distance among all samples

Author(s)

Adrien Taudière

Examples

```
data("enterotype")
sam_name_factice <- gsub("TS1_V2", "TS10_V2", sample.names(enterotype))
res_dist_cont <- dist_pos_control(enterotype, sam_name_factice)
hist(unlist(res_dist_cont$distAllSamples))
abline(
  v = mean(unlist(res_dist_cont$dist_controlontrolSamples), na.rm = TRUE),
  col = "red", lwd = 3
)
```

| | |
|-------------------------------|---|
| <code>filter_asv_blast</code> | <i>Filter undesirable taxa using blast against a against a custom database.</i> |
|-------------------------------|---|

Description

[Experimental]

Usage

```
filter_asv_blast(
  physeq,
  fasta_for_db = NULL,
  database = NULL,
  clean_pq = TRUE,
  add_info_to_taxtable = TRUE,
  id_filter = 90,
  bit_score_filter = 50,
  min_cover_filter = 50,
  e_value_filter = 1e-30,
  ...
)
```

Arguments

| | |
|-----------------------------------|---|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>fasta_for_db</code> | path to a fasta file to make the blast database |
| <code>database</code> | path to a blast database |
| <code>clean_pq</code> | (logical) If set to TRUE, empty samples and empty ASV are discarded after filtering. |
| <code>add_info_to_taxtable</code> | (logical, default TRUE) Does the blast information are added to the taxtable ? |
| <code>id_filter</code> | (default: 90) cut of in identity percent to keep result |
| <code>bit_score_filter</code> | (default: 50) cut of in bit score to keep result The higher the bit-score, the better the sequence similarity. The bit-score is the requires size of a sequence database in which the current match could be found just by chance. The bit-score is a log2 scaled and normalized raw-score. Each increase by one doubles the required database size (2bit-score). |
| <code>min_cover_filter</code> | (default: 50) cut of in query cover (%) to keep result |
| <code>e_value_filter</code> | (default: 1e-30) cut of in e-value (%) to keep result The BLAST E-value is the number of expected hits of similar quality (score) that could be found just by chance. |
| <code>...</code> | Others options for the <code>blast_pq()</code> function. See <code>?blast_pq</code> . Note that params <code>unique_per_seq</code> must be left to TRUE and <code>score_filter</code> must be left to FALSE. |

Value

A new `phyloseq-class` object.

`filter_trim`

A wrapper of the function `dada2::filterAndTrim()` to use in R href="https://books.ropensci.org/targets/targets pipeline

Description**[Maturing]**

This function filter and trim (with parameters passed on to `dada2::filterAndTrim()` function) forward sequences or paired end sequence if 'rev' parameter is set. It return the list of files to subsequent analysis in a targets pipeline.

Usage

```
filter_trim(
  fw = NULL,
  rev = NULL,
  output_fw = paste(getwd(), "/output/filterAndTrim_fwd", sep = ""),
  output_rev = paste(getwd(), "/output/filterAndTrim_rev", sep = ""),
  ...
)
```

Arguments

| | |
|-------------------------|--|
| <code>fw</code> | (required) a list of forward fastq files |
| <code>rev</code> | a list of reverse fastq files for paired end trimming |
| <code>output_fw</code> | Path to output folder for forward files. By default, this function will create a folder "output/filterAndTrim_fwd" in the current working directory. |
| <code>output_rev</code> | Path to output folder for reverse files. By default, this function will create a folder "output/filterAndTrim_rev" in the current working directory. |
| ... | Other parameters passed on to <code>dada2::filterAndTrim()</code> function. |

Value

A list of files. If rev is set, will return a list of two lists. The first list is a list of forward files, and the second one is a list of reverse files.

Author(s)

Adrien Taudière

See Also

`dada2::filterAndTrim()`

Examples

```

testFastqs_fw <- c(
  system.file("extdata", "sam1F.fastq.gz", package = "dada2"),
  system.file("extdata", "sam2F.fastq.gz", package = "dada2")
)
testFastqs_rev <- c(
  system.file("extdata", "sam1R.fastq.gz", package = "dada2"),
  system.file("extdata", "sam2R.fastq.gz", package = "dada2")
)

filt_fastq_fw <- filter_trim(testFastqs_fw, output_fw = tempdir())
derep_fw <- derepFastq(filt_fastq_fw[1])
derep_fw

filt_fastq_pe <- filter_trim(testFastqs_fw,
  testFastqs_rev,
  output_fw = tempdir("fw"),
  output_rev = tempdir("rev"))
)
derep_fw_pe <- derepFastq(filt_fastq_pe[[1]])
derep_rev_pe <- derepFastq(filt_fastq_pe[[2]])
derep_fw_pe
derep_rev_pe

```

Description

[Stable]

The original function and documentation was written by Brendan Furneaux in the [FUNGuildR](#) package.

These functions have identical behavior if supplied with a database; however they download the database corresponding to their name by default.

Taxa present in the database are matched to the taxa present in the supplied `otu_table` by exact name. In the case of multiple matches, the lowest (most specific) rank is chosen. No attempt is made to check or correct the classification in `otu_table$Taxonomy`.

Usage

```

funguild_assign(
  otu_table,
  db_funguild = get_funguild_db(),
  tax_col = "Taxonomy"
)

```

Arguments

| | |
|--------------------------|---|
| <code>otu_table</code> | A <code>data.frame</code> with a character column named "Taxonomy" (or another name as specified in <code>tax_col</code>), as well as any other columns. Each entry in " <code>otu_table\$Taxonomy</code> " should be a comma-, colon-, underscore-, or semicolon-delimited classification of an organism. Rank indicators as given by Sintax ("k:", "p:...") or Unite ("k___", "p___", ...) are also allowed. A character vector, representing only the taxonomic classification, is also accepted. |
| <code>db_funguild</code> | A <code>data.frame</code> representing the FUNGuild as returned by <code>get_funguild_db()</code> . If not supplied, the default database will be downloaded. |
| <code>tax_col</code> | A character string, optionally giving an alternate column name in <code>otu_table</code> to use instead of <code>otu_table\$Taxonomy</code> . |

Value

A `tibble::tibble` containing all columns of `otu_table`, plus relevant columns of information from the FUNGuild

Author(s)

Brendan Furneaux (orcid: [0000-0003-3522-7363](#)), modified by Adrien Taudière

References

Nguyen NH, Song Z, Bates ST, Branco S, Tedersoo L, Menke J, Schilling JS, Kennedy PG. 2016. *FUNGuild: An open annotation tool for parsing fungal community datasets by ecological guild*. Fungal Ecology 20:241-248.

| | |
|--------------------------|----------------------------|
| <code>funky_color</code> | <i>Funky palette color</i> |
|--------------------------|----------------------------|

Description

Funky palette color

Usage

```
funky_color(n)
```

Arguments

| | |
|----------------|--------------------|
| <code>n</code> | a number of colors |
|----------------|--------------------|

Value

a color palette

Author(s)

Thibaut Jombart

get_file_extension *Get the extension of a file*

Description

[Maturing]

Usage

```
get_file_extension(file_path)
```

Arguments

file_path (required): path to a file

Value

A [phyloseq-class](#) object with simplified taxonomy

Author(s)

Adrien Taudière

get_funguild_db *Retrieve the FUNGuild database*

Description

[**Stable**] The original function and documentation was written by Brendan Furneaux in the [FUN-GuildR](#) package.

Please cite this [publication](#).

Usage

```
get_funguild_db(db_url = "http://www.stbates.org/funguild_db_2.php")
```

Arguments

db_url a length 1 character string giving the URL to retrieve the database from

Value

a [tibble::tibble](#) containing the database, which can be passed to the db argument of [funguild_assign\(\)](#)

Author(s)

Brendan Furneaux (orcid: [0000-0003-3522-7363](#)), modified by Adrien Taudière

References

Nguyen NH, Song Z, Bates ST, Branco S, Tedersoo L, Menke J, Schilling JS, Kennedy PG. 2016. *FUNGuild: An open annotation tool for parsing fungal community datasets by ecological guild.* Fungal Ecology 20:241-248.

ggbetween_pq

Box/Violin plots for between-subjects comparisons of Hill Number

Description

[Experimental]

Note that contrary to `hill_pq()`, this function does not take into account for difference in the number of sequences per samples/modalities. You may use `rarefy_by_sample = TRUE` if the mean number of sequences per samples differs among modalities.

Basically a wrapper of function `ggstatsplot::ggbetweenstats()` for object of class phyloseq

Usage

```
ggbetween_pq(physeq, variable, one_plot = FALSE, rarefy_by_sample = FALSE, ...)
```

Arguments

| | |
|------------------|---|
| physeq | (required): a <code>phyloseq-class</code> object obtained using the <code>phyloseq</code> package. |
| variable | (required): The variable to test. Must be present in the <code>sam_data</code> slot of the <code>physeq</code> object. |
| one_plot | (logical, default FALSE) If TRUE, return a unique plot with the three plot inside using the <code>patchwork</code> package. |
| rarefy_by_sample | (logical, default FALSE) If TRUE, rarefy samples using <code>phyloseq::rarefy_even_depth()</code> function |
| ... | Other arguments passed on to <code>ggstatsplot::ggbetweenstats()</code> function. |

Details

This function is mainly a wrapper of the work of others. Please make a reference to `ggstatsplot::ggbetweenstats()` if you use this function.

Value

Either an unique `ggplot2` object (if `one_plot` is TRUE) or a list of 3 `ggplot2` plot:

- `plot_Hill_0` : the ggbetweenstats of Hill number 0 (= species richness) against the variable
- `plot_Hill_1` : the ggbetweenstats of Hill number 1 (= Shannon index) against the variable
- `plot_Hill_2` : the ggbetweenstats of Hill number 2 (= Simpson index) against the variable

Author(s)

Adrien Taudière

Examples

```
p <- ggbetween_pq(data_fungi, variable = "Time", p.adjust.method = "BH")
p[[1]]
ggbetween_pq(data_fungi, variable = "Height", one_plot = TRUE)
ggbetween_pq(data_fungi, variable = "Height", one_plot = TRUE, rarefy_by_sample = TRUE)
```

`ggvenn_pq`

Venn diagram of phyloseq-class object using ggVennDiagram::ggVennDiagram function

Description**[Maturing]**

Note that you can use `ggplot2` function to customize the plot for ex. `+ scale_fill_distiller(palette = "BuPu", direction = 1)` and `+ scale_x_continuous(expand = expansion(mult = 0.5))`. See examples.

Usage

```
ggvenn_pq(
  physeq = NULL,
  fact = NULL,
  min_nb_seq = 0,
  taxonomic_rank = NULL,
  split_by = NULL,
  add_nb_samples = TRUE,
  add_nb_seq = FALSE,
  rarefy_before_merging = FALSE,
  rarefy_after_merging = FALSE,
  ...
)
```

Arguments

| | |
|-------------------------|---|
| <code>physeq</code> | (required): a <code>phyloseq-class</code> object obtained using the <code>phyloseq</code> package. |
| <code>fact</code> | (required): Name of the factor to cluster samples by modalities. Need to be in <code>physeq@sam_data</code> . |
| <code>min_nb_seq</code> | minimum number of sequences by OTUs by samples to take into count this OTUs in this sample. For example, if <code>min_nb_seq=2</code> , each value of 2 or less in the OTU table will not count in the venn diagram |

taxonomic_rank Name (or number) of a taxonomic rank to count. If set to Null (the default) the number of OTUs is counted.

split_by Split into multiple plot using variable split_by. The name of a variable must be present in sam_data slot of the physeq object.

add_nb_samples (logical, default TRUE) Add the number of samples to levels names

add_nb_seq (logical, default FALSE) Add the number of sequences to levels names

rarefy_before_merging
Rarefy each sample before merging by the modalities of args fact. Use phyloseq::rarefy_even_depth function

rarefy_after_merging
Rarefy each sample after merging by the modalities of args fact.

... other arguments for the ggVennDiagram::ggVennDiagram function for ex. category.names.

Value

A [ggplot2](#) plot representing Venn diagram of modalities of the argument factor or if split_by is set a list of plots.

Author(s)

Adrien Taudière

See Also

[upset_pq\(\)](#)

Examples

```
ggvenn_pq(data_fungi, fact = "Height")

ggvenn_pq(data_fungi, fact = "Height") +
  ggplot2::scale_fill_distiller(palette = "BuPu", direction = 1)
  pl <- ggvenn_pq(data_fungi, fact = "Height", split_by = "Time")
  for (i in 1:length(pl)) {
    p <- pl[[i]] +
      scale_fill_distiller(palette = "BuPu", direction = 1) +
      theme(plot.title = element_text(hjust = 0.5, size = 22))
    print(p)
  }

  data_fungi2 <- subset_samples(data_fungi, data_fungi@sam_data$Tree_name == "A10-005" |
    data_fungi@sam_data$Height %in% c("Low", "High"))
  ggvenn_pq(data_fungi2, fact = "Height")

  ggvenn_pq(data_fungi, fact = "Height", add_nb_seq = TRUE, set_size = 4)
  ggvenn_pq(data_fungi, fact = "Height", rarefy_before_merging = TRUE)
  ggvenn_pq(data_fungi, fact = "Height", rarefy_after_merging = TRUE) +
    scale_x_continuous(expand = expansion(mult = 0.5))
```

| | |
|----------------------------|--|
| <code>graph_test_pq</code> | <i>Performs graph-based permutation tests on phyloseq object</i> |
|----------------------------|--|

Description

[Maturing]

A wrapper of [phyloseqGraphTest::graph_perm_test\(\)](#) for quick plot with important statistics

Usage

```
graph_test_pq(
  physeq,
  fact,
  merge_sample_by = NULL,
  nperm = 999,
  return_plot = TRUE,
  title = "Graph Test",
  na_remove = FALSE,
  ...
)
```

Arguments

| | |
|------------------------------|---|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>fact</code> | (required) Name of the factor to cluster samples by modalities. Need to be in <code>physeq@sam_data</code> . This should be a factor with two or more levels. |
| <code>merge_sample_by</code> | a vector to determine which samples to merge using merge_samples2() function. Need to be in <code>physeq@sam_data</code> |
| <code>nperm</code> | (int) The number of permutations to perform. |
| <code>return_plot</code> | (logical) Do we return only the result of the test or do we plot the result? |
| <code>title</code> | The title of the Graph. |
| <code>na_remove</code> | (logical, default FALSE) If set to TRUE, remove samples with NA in the variables set in formula. |
| <code>...</code> | other params for be passed on to phyloseqGraphTest::graph_perm_test() function |

Details

This function is mainly a wrapper of the work of others. Please cite [phyloseqGraphTest](#) package.

Value

A [ggplot2](#) plot with a subtitle indicating the pvalue and the number of permutations

Author(s)

Adrien Taudière

Examples

```
data(enterotype)
graph_test_pq(enterotype, fact = "SeqTech")
graph_test_pq(enterotype, fact = "Enterotype", na_remove = TRUE)
```

heat_tree_pq

Heat tree from metacoder package using tax_table slot

Description**[Maturing]**

Note that the number of ASV is store under the name n_obs and the number of sequences under the name nb_sequences

Usage

```
heat_tree_pq(physeq, taxonomic_level = NULL, ...)
```

Arguments

| | |
|-----------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| taxonomic_level | (default: NULL): a vector of selected taxonomic level using their column numbers (e.g. taxonomic_level = 1:7) |
| ... | Arguments passed on to heat_tree |

Value

A plot

Author(s)

Adrien Taudière

Examples

```

if (!requireNamespace("metacoder")) {
  data("GlobalPatterns", package = "phyloseq")

  GPsubset <- subset_taxa(
    GlobalPatterns,
    GlobalPatterns@tax_table[, 1] == "Bacteria"
  )

  GPsubset <- subset_taxa(
    GPsubset,
    rowSums(GPsubset@otu_table) > 5000
  )

  GPsubset <- subset_taxa(
    GPsubset,
    rowSums(is.na(GPsubset@tax_table)) == 0
  )

  heat_tree_pq(GPsubset,
    node_size = n_obs,
    node_color = n_obs,
    node_label = taxon_names,
    tree_label = taxon_names,
    node_size_trans = "log10 area"
  )

  heat_tree_pq(GPsubset,
    node_size = nb_sequences,
    node_color = n_obs,
    node_label = taxon_names,
    tree_label = taxon_names,
    node_size_trans = "log10 area"
  )
}

```

hill_pq

Graphical representation of hill number 0, 1 and 2 across a factor

Description

[Experimental] Note that this function use a sqrt of the read numbers in the linear model in order to correct for uneven sampling depth.

Usage

```
hill_pq(
```

```

physeq,
variable,
color_fac = NA,
letters = FALSE,
add_points = FALSE,
add_info = TRUE,
one_plot = FALSE,
plot_with_tuckey = TRUE,
correction_for_sample_size = TRUE
)

```

Arguments

| | |
|---|--|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>variable</code> | (required): The variable to test. Must be present in the <code>sam_data</code> slot of the <code>physeq</code> object. |
| <code>color_fac</code> | (optional): The variable to color the barplot |
| <code>letters</code> | (optional, default=FALSE): If set to TRUE, the plot show letters based on p-values for comparison. Use the multcompLetters function from the package multcompLetters. BROKEN for the moment. Note that na values in The variable param need to be removed (see examples) to use letters. |
| <code>add_points</code> | (logical): add jitter point on boxplot |
| <code>add_info</code> | (logical, default TRUE) Do we add a subtitle with information about the number of samples per modality ? |
| <code>one_plot</code> | (logical, default FALSE) If TRUE, return a unique plot with the four plot inside using the patchwork package. Note that if letters and one_plot are both TRUE, tuckey HSD results are discarded from the unique plot. In that case, use one_plot = FALSE to see the tuckey HSD results in the fourth plot of the resulting list. |
| <code>plot_with_tuckey</code> | (logical, default TRUE). If one_plot is set to TRUE and letters to FALSE, allow to discard the tuckey plot part with <code>plot_with_tuckey = FALSE</code> |
| <code>correction_for_sample_size</code> | (logical, default TRUE) This function use a sqrt of the read numbers in the linear model in order to correct for uneven sampling depth. |

Value

Either an unique ggplot2 object (if `one_plot` is TRUE) or a list of 4 ggplot2 plot:

- `plot_Hill_0` : the boxplot of Hill number 0 (= species richness) against the variable
- `plot_Hill_1` : the boxplot of Hill number 1 (= Shannon index) against the variable
- `plot_Hill_2` : the boxplot of Hill number 2 (= Simpson index) against the variable
- `plot_tuckey` : plot the result of the Tuckey HSD test

Author(s)

Adrien Taudière

Examples

```

p <- hill_pq(data_fungi_mini, "Height")
p_h1 <- p[[1]] + theme(legend.position = "none")
p_h2 <- p[[2]] + theme(legend.position = "none")
p_h3 <- p[[3]] + theme(legend.position = "none")
multiplot(plotlist = list(p_h1, p_h2, p_h3, p[[4]]), cols = 4)

# Artificially modify data_fungi to force alpha-diversity effect
data_fungi_modif <- clean_pq(subset_samples_pq(data_fungi, !is.na(data_fungi@sam_data$Height)))
data_fungi_modif@otu_table[data_fungi_modif@sam_data$Height == "High", ] <-
  data_fungi_modif@otu_table[data_fungi_modif@sam_data$Height == "High", ] +
  sample(c(rep(0, ntaxa(data_fungi_modif) / 2), rep(100, ntaxa(data_fungi_modif) / 2)))
p2 <- hill_pq(data_fungi_modif, "Height", letters = TRUE)

```

hill_tuckey_pq

Calculate hill number and compute Tuckey post-hoc test

Description

[Maturing] Note that, by default, this function use a sqrt of the read numbers in the linear model in order to correct for uneven sampling depth.

Usage

```
hill_tuckey_pq(
  physeq,
  modality,
  silent = TRUE,
  correction_for_sample_size = TRUE
)
```

Arguments

| | |
|----------------------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| modality | (required) the variable to test |
| silent | (logical) If TRUE, no message are printing. |
| correction_for_sample_size | (logical, default TRUE) This function use a sqrt of the read numbers in the linear model in order to correct for uneven sampling depth. |

Value

A ggplot2 object

Author(s)

Adrien Taudière

Examples

```
data("GlobalPatterns", package = "phyloseq")
GlobalPatterns@sam_data[, "Soil_logical"] <-
  ifelse(GlobalPatterns@sam_data[, "SampleType"] == "Soil", "Soil", "Not Soil")
hill_tuckey_pq(GlobalPatterns, "Soil_logical")
```

iNEXT_pq

iNterpolation and EXTrapolation of Hill numbers (with iNEXT)

Description

[Experimental]

Usage

```
iNEXT_pq(physeq, merge_sample_by = NULL, ...)
```

Arguments

| | |
|-----------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| merge_sample_by | (default: NULL) if not NULL samples of physeq are merged using the vector set by merge_sample_by. This merging used the merge_samples2() . In the case of biplot_pq() this must be a factor with two levels only. |
| ... | other arguments for the iNEXT::iNEXT() function |

Value

see [iNEXT::iNEXT\(\)](#) documentation

Author(s)

Adrien Taudière This function is mainly a wrapper of the work of others. Please make a reference to [iNEXT::iNEXT\(\)](#) if you use this function.

Examples

```
if (!requireNamespace("iNEXT")) {
  data("GlobalPatterns", package = "phyloseq")
  GSubset <- subset_taxa(
    GlobalPatterns,
    GlobalPatterns@tax_table[, 1] == "Bacteria"
  )
```

```

GPsubset <- subset_taxa(
  GPsubset,
  rowSums(GPsubset@otu_table) > 20000
)
GPsubset <- subset_taxa(
  GPsubset,
  rowSums(is.na(GPsubset@tax_table)) == 0
)
GPsubset@sam_data$human <- GPsubset@sam_data$SampleType %in%
  c("Skin", "Feces", "Tong")
res_iNEXT <- iNEXT_pq(
  GPsubset,
  merge_sample_by = "human",
  q = 1,
  datatype = "abundance",
  nboot = 2
)
iNEXT::ggiNEXT(res_iNEXT)
iNEXT::ggiNEXT(res_iNEXT, type = 2)
iNEXT::ggiNEXT(res_iNEXT, type = 3)
}

```

`is_cutadapt_installed` *Test if cutadapt is installed.*

Description

[Maturing]

Useful for testthat and examples compilation for R CMD CHECK and test coverage

Usage

```

is_cutadapt_installed(
  args_before_cutadapt =
    "source ~/miniconda3/etc/profile.d/conda.sh && conda activate cutadaptenv && "
)

```

Arguments

`args_before_cutadapt`
 : (String) A one line bash command to run before to run cutadapt. For examples,
`"source ~/miniconda3/etc/profile.d/conda.sh && conda activate cutadaptenv &&"`
 allow to bypass the conda init which asks to restart the shell

Value

A logical that say if cutadapt is install in

Author(s)

Adrien Taudière

Examples

```
MiscMetabar::is_cutadapt_installed()
```

is_falco_installed *Test if falco is installed.*

Description**[Maturing]**

Useful for testthat and examples compilation for R CMD CHECK and test coverage

Usage

```
is_falco_installed(path = "falco")
```

Arguments

path (default: falco) Path to falco

Value

A logical that say if falco is install in

Author(s)

Adrien Taudière

Examples

```
MiscMetabar::is_falco_installed()
```

is_krona_installed *Test if krona is installed.*

Description

[Maturing]

Useful for testthat and examples compilation for R CMD CHECK and test coverage

Usage

```
is_krona_installed(path = "ktImportKrona")
```

Arguments

path (default: krona) Path to krona

Value

A logical that say if krona is install in

Author(s)

Adrien Taudière

Examples

```
MiscMetabar::is_krona_installed()
```

is_mumu_installed *Test if mumu is installed.*

Description

[Maturing]

Useful for testthat and examples compilation for R CMD CHECK and test coverage

Usage

```
is_mumu_installed(path = "mumu")
```

Arguments

path (default: mumu) Path to mumu

Value

A logical that say if mumu is install in

Author(s)

Adrien Taudière

Examples

```
MiscMetabar::is_mumu_installed()
```

is_swarm_installed *Test if swarm is installed.*

Description**[Maturing]**

Useful for testthat and examples compilation for R CMD CHECK and test coverage

Usage

```
is_swarm_installed(path = "swarm")
```

Arguments

path (default: swarm) Path to falco

Value

A logical that say if swarm is install in

Author(s)

Adrien Taudière

Examples

```
MiscMetabar::is_swarm_installed()
```

is_vsearch_installed *Test if vsearch is installed.*

Description

[Maturing]

Useful for testthat and examples compilation for R CMD CHECK and test coverage

Usage

```
is_vsearch_installed(path = "vsearch")
```

Arguments

path (default: vsearch) Path to vsearch

Value

A logical that say if vsearch is install in

Author(s)

Adrien Taudière

Examples

```
MiscMetabar::is_vsearch_installed()
```

krona *Make Krona files using R href<https://github.com/marbl/Krona/wiki/KronaTools>*.

Description

[Maturing]

Need the installation of kronatools on the computer ([installation instruction](#)).

Usage

```
krona(  
  physeq,  
  file = "krona.html",  
  nb_seq = TRUE,  
  ranks = "All",  
  add_unassigned_rank = 0,  
  name = NULL  
)
```

Arguments

| | |
|---------------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| file | (required) the location of the html file to save |
| nb_seq | (logical) If true, Krona set the distribution of sequences in the taxonomy. If False, Krona set the distribution of ASVs in the taxonomy. |
| ranks | Number of the taxonomic ranks to plot (num of the column in tax_table slot of your physeq object). Default setting plot all the ranks (argument 'All'). |
| add_unassigned_rank | (int) Add unassigned for rank inferior to 'add_unassigned_rank' when necessary. |
| name | A name for intermediary files, Useful to name your krona result files before merging using merge_krona() |

Details

This function is mainly a wrapper of the work of others. Please cite [Krona](#) if you use this function.

Value

A html file

Author(s)

Adrien Taudière

See Also

[merge_krona](#)

Examples

```
data("GlobalPatterns", package = "phyloseq")
GA <- subset_taxa(GlobalPatterns, Phylum == "Acidobacteria")
## Not run:
krona(GA, "Number.of.sequences.html")
krona(GA, "Number.of.ASVs.html", nb_seq = FALSE)
merge_krona(c("Number.of.sequences.html", "Number.of.ASVs.html"))

## End(Not run)
```

| | |
|---------|---|
| LCBD_pq | <i>Compute and test local contributions to beta diversity (LCBD) of samples</i> |
|---------|---|

Description

[Experimental]

A wrapper for the [adespatial::beta.div\(\)](#) function in the case of physeq object.

Usage

```
LCBD_pq(physeq, p_adjust_method = "BH", ...)
```

Arguments

physeq (required): a [phyloseq-class](#) object obtained using the phyloseq package.
p_adjust_method (chr, default "BH"): the method used to adjust p-value
... Others arguments passed on to [adespatial::beta.div\(\)](#) function

Value

An object of class beta.div see [adespatial::beta.div\(\)](#) function for more information

Author(s)

Adrien Taudière This function is mainly a wrapper of the work of others. Please make a reference to [adespatial::beta.div\(\)](#) if you use this function.

See Also

[plot_LCBD_pq](#), [adespatial::beta.div\(\)](#)

Examples

```
res <- LCBD_pq(data_fungi_sp_known, nperm = 5)
str(res)
length(res$LCBD)
length(res$SCBD)

LCBD_pq(data_fungi_sp_known, nperm = 5, method = "jaccard")
```

list_fastq_files *List fastq files*

Description**[Maturing]****Usage**

```
list_fastq_files(  
  path,  
  paired_end = TRUE,  
  pattern = "fastq",  
  pattern_R1 = "_R1_",  
  pattern_R2 = "_R2_",  
  nb_files = Inf  
)
```

Arguments

| | |
|------------|---|
| path | path to files (required) |
| paired_end | do you have paired_end files? (default TRUE) |
| pattern | a pattern to filter files (passed on to list.files function). |
| pattern_R1 | a pattern to filter R1 files (default "R1") |
| pattern_R2 | a pattern to filter R2 files (default "R2") |
| nb_files | the number of fastq files to list (default FALSE) |

Value

a list of one (single end) or two (paired end) list of files files are sorted by names (default behavior of `list.files()`)

Author(s)

Adrien Taudière

Examples

```
list_fastq_files("extdata")  
list_fastq_files("extdata", paired_end = FALSE, pattern_R1 = "")
```

`lulu`

Post Clustering Curation of Amplicon Data.

Description

[Stable]

The original function and documentation was written by Tobias Guldberg Frøslev in the `lulu` package.

This algorithm `lulu` consumes an OTU table and a matchlist, and evaluates cooccurrence of 'daughters' (potential analytical artefacts) and their 'parents' (\sim real biological species/OTUs). The algorithm requires an OTU table (species/site matrix), and a match list. The OTU table can be made with various r-packages (e.g. DADA2) or external pipelines (VSEARCH, USEARCH, QIIME, etc.), and the match-list can be made with external bioinformatic tools like VSEARCH, USEARCH, BLASTN or another algorithm for pair-wise sequence matching.

Usage

```
lulu(  
  otu_table,  
  matchlist,  
  minimum_ratio_type = "min",  
  minimum_ratio = 1,  
  minimum_match = 84,  
  minimum_relative_cooccurrence = 0.95,  
  progress_bar = TRUE,  
  log_conserved = FALSE  
)
```

Arguments

| | |
|---------------------------------|--|
| <code>otu_table</code> | a data.frame with with an OTU table that has sites/samples as columns and OTUs (unique OTU id's) as rows, and observations as read counts. |
| <code>matchlist</code> | a data.frame containing three columns: (1) OTU id of potential child, (2) OTU id of potential parent, (3) match - % identiti between the sequences of the potential parent and potential child OTUs. NB: The matchlist is the product of a mapping of OTU sequences against each other. This is currently carried out by an external script in e.g. Blastn or VSEARCH, prior to running lulu! |
| <code>minimum_ratio_type</code> | sets whether a potential error must have lower abundance than the parent in all samples <code>min</code> (default), or if an error just needs to have lower abundance on average <code>avg</code> . Choosing lower abundance on average over globally lower abundance will greatly increase the number of designated errors. This option was introduced to make it possible to account for non-sufficiently clustered intraspecific variation, but is not generally recommended, as it will also increase the potential of cluster well-separated, but co-occurring, sequence similar species. |

| | |
|--|---|
| <code>minimum_ratio</code> | sets the minimim abundance ratio between a potential error and a potential parent to be identified as an error. If the <code>minimum_ratio_type</code> is set to <code>min</code> (default), the <code>minimum_ratio</code> applies to the lowest observed ration across the samples. If the <code>minimum_ratio_type</code> is set to <code>avg</code> (default), the <code>minimum_ratio</code> applies to the mean of observed ration across the samples. <code>avg</code> . (default is 1). |
| <code>minimum_match</code> | minimum threshold of sequence similarity for considering any OTU as an error of another can be set (default 84%). |
| <code>minimum_relative_cooccurrence</code> | minimum co-occurrence rate, i.e. the lower rate of occurrence of the potential error explained by co-occurrence with the potential parent for considering error state. |
| <code>progress_bar</code> | (Logical, default TRUE) print progress during the calculation or not. |
| <code>log_conserved</code> | (Logical, default FALSE) conserved log files writed in the disk |

Details

Please cite the lulu original paper: <https://www.nature.com/articles/s41467-017-01312-x>

Value

Function `lulu` returns a list of results based on the input OTU table and match list.

- `curated_table` - a curated OTU table with daughters merged with their matching parents.
- `curated_count` - number of curated (parent) OTUs.
- `curated_otus` - ids of the OTUs that were accepted as valid OTUs.
- `discarded_count` - number of discarded (merged with parent) OTUs.
- `discarded_otus` - ids of the OTUs that were identified as errors (daughters) and merged with respective parents.
- `runtime` - time used by the script.
- `minimum_match` - the id threshold (minimum match \ by user).
- `minimum_relative_cooccurrence` - minimum ratio of daughter-occurences explained by co-occurrence with parent (set by user).
- `otu_map` - information of which daughters were mapped to which parents.
- `original_table` - original OTU table.

The matchlist is the product of a mapping of OTU sequences against each other. This is currently carried out by an external script in e.g. BLASTN or VSEARCH, prior to running `lulu!` Producing the match list requires a file with all the OTU sequences (centroids) - e.g. `OTUcentroids.fasta`. The matchlist can be produced by mapping all OTUs against each other with an external algorithm like VSEARCH or BLASTN. In VSEARCH a matchlist can be produced e.g. with the following command: `vfsearch --usearch_global OTUcentroids.fasta --db OTUcentroids.fasta --strand plus --self --id .80 --iddef 1 --userout matchlist.txt --userfields query+target+id --maxaccepts 0 --query_cov .9 --maxhits 10`. In BLASTN a matchlist can be produced e.g. with the following commands. First we produce a blast-database from the fasta file: `makeblastdb -in OTUcentroids.fasta -parse_seqids -dbtype nucl`, then we match the centroids against that database: `blastn -db OTUcentroids.fasta -num_threads 10 -outfmt '6 qseqid sseqid pident' -out matchlist.txt -qcov_hsp_perc .90 -perc_identity .84 -query OTUcentroids.fasta`

Author(s)

Tobias Guldberg Frøslev (orcid: [0000-0002-3530-013X](#)), modified by Adrien Taudière

lulu_pq

Lulu reclustering of class physeq

Description

[Experimental]

See <https://www.nature.com/articles/s41467-017-01312-x> for more information on the method.

Usage

```
lulu_pq(  
  physeq,  
  nproc = 1,  
  id = 0.84,  
  vsearchpath = "vsearch",  
  verbose = FALSE,  
  clean_pq = FALSE,  
  keep_temporary_files = FALSE,  
  ...  
)
```

Arguments

| | |
|----------------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| nproc | (default 1) Set to number of cpus/processors to use for the clustering |
| id | (default: 0.84) id for –usearch_global. |
| vsearchpath | (default: vsearch) path to vsearch. |
| verbose | (logical) if true, print some additional messages. |
| clean_pq | (logical) if true, empty samples and empty ASV are discarded before clustering. |
| keep_temporary_files | (logical, default: FALSE) Do we keep temporary files |
| ... | Others args for function lulu() |

Details

The version of LULU is a fork of Adrien Taudière (<https://github.com/adrientaudiere/lulu>) from <https://github.com/tobiasgf/lulu>

Value

a list of for object

- "new_physeq": The new phyloseq object (class physeq)
- "discrepancy_vector": A vector of discrepancy showing for each taxonomic level the proportion of identic value before and after lulu reclustering. A value of 0.6 stands for 60% of ASV before re-clustering have identical value after re-clustering. In other word, 40% of ASV are assigned to a different taxonomic value. NA value are not counted as discrepancy.
- "res_lulu": A list of the result from the lulu function
- "merged_ASV": the data.frame used to merged ASV

Author(s)

Tobias Guldberg Frøslev <tobiasgf@snm.ku.dk> & Adrien Taudière <adrien.taudiere@zaclys.net>

References

- LULU : <https://github.com/adrientaudiere/lulu> forked from <https://github.com/tobiasgf/lulu>.
- VSEARCH can be downloaded from <https://github.com/torognes/vsearch>.

Examples

```
lulu_pq(data_fungi_sp_known)
```

merge_krona

Merge Krona files using R [ref https://github.com/marbl/Krona/wiki/KronaTools](https://github.com/marbl/Krona/wiki/KronaTools).

Description**[Maturing]**

Need the installation of kronatools on the computer ([installation instruction](#)). Function merge_krona allows merging multiple html files in one interactive krona file

Note that you need to use the name args in krona() function before merge_krona() in order to give good name to each krona pie in the output.

Usage

```
merge_krona(files = NULL, output = "mergeKrona.html")
```

Arguments

| | |
|--------|---|
| files | (required) path to html files to merged |
| output | path to the output file |

Details

This function is mainly a wrapper of the work of others. Please cite [Krona](#) if you use this function.

Value

A html file

Author(s)

Adrien Taudière

See Also

[krona](#)

Examples

```
## Not run:
data("GlobalPatterns", package = "phyloseq")
GA <- subset_taxa(GlobalPatterns, Phylum == "Acidobacteria")
krona(GA, "Number.of.sequences.html", name = "Nb_seq_GP_acidobacteria")
krona(GA, "Number.of.ASVs.html", nb_seq = FALSE, name = "Nb_asv_GP_acidobacteria")
merge_krona(c("Number.of.sequences.html", "Number.of.ASVs.html"), "mergeKrona.html")
unlink(c("Number.of.sequences.html", "Number.of.ASVs.html", "mergeKrona.html"))

## End(Not run)
```

Description

[Stable]

Firstly release in the [speedyseq](#) R package by Michael R. McLaren.

This function provides an alternative to phyloseq:::merge_samples() that better handles sample variables of different types, especially categorical sample variables. It combines the samples in x defined by the sample variable or factor group by summing the abundances in otu_table(x) and combines sample variables by the summary functions in funs. The default summary function, unique_or_na(), collapses the values within a group to a single unique value if it exists and otherwise returns NA. The new (merged) samples are named by the values in group.

Usage

```
merge_samples2(x, group, fun_otu = sum, funs = list(), reorder = FALSE)

## S4 method for signature 'phyloseq'
merge_samples2(x, group, fun_otu = sum, funs = list(), reorder = FALSE)

## S4 method for signature 'otu_table'
merge_samples2(x, group, fun_otu = sum, reorder = FALSE)

## S4 method for signature 'sample_data'
merge_samples2(x, group, funs = list(), reorder = FALSE)
```

Arguments

| | |
|---------|--|
| x | A phyloseq, otu_table, or sample_data object |
| group | A sample variable or a vector of length nsamples(x) defining the sample grouping. A vector must be supplied if x is an otu_table |
| fun_otu | Function for combining abundances in the otu table; default is sum. Can be a formula to be converted to a function by purrr::as_mapper() |
| funs | Named list of merge functions for sample variables; default is unique_or_na |
| reorder | Logical specifying whether to reorder the new (merged) samples by name |

Value

A new phyloseq-class, otu_table or sam_data object depending on the class of the x param

Author(s)

Michael R. McLaren (orcid: [0000-0003-1575-473X](#)) modified by Adrien Taudiere

Examples

```
data(enterotype)

# Merge samples with the same project and clinical status
ps <- enterotype
sample_data(ps) <- sample_data(ps) %>%
  transform(Project.ClinicalStatus = Project:ClinicalStatus)
sample_data(ps) %>% head()
ps0 <- merge_samples2(ps, "Project.ClinicalStatus",
  fun_otu = mean,
  funs = list(Age = mean))
sample_data(ps0) %>% head()
```

| | |
|----------------|--|
| merge_taxa_vec | <i>Merge taxa in groups (vectorized version)</i> |
|----------------|--|

Description

[Stable]

Firstly release in the [speedyseq](#) R package by Michael R. McLaren.

Merge taxa in `x` into a smaller set of taxa defined by the vector `group`. Taxa whose value in `group` is NA will be dropped. New taxa will be named according to the most abundant taxon in each group (`phyloseq` and `otu_table` objects) or the first taxon in each group (all other `phyloseq` component objects).

If `x` is a `phyloseq` object with a phylogenetic tree, then the new taxa will be ordered as they are in the tree. Otherwise, the taxa order can be controlled by the `reorder` argument, which behaves like the `reorder` argument in [base:::rowsum\(\)](#). `reorder = FALSE` will keep taxa in the original order determined by when the member of each group first appears in `taxa_names(x)`; `reorder = TRUE` will order new taxa according to their corresponding value in `group`.

The `tax_adjust` argument controls the handling of taxonomic disagreements within groups. Setting `tax_adjust == 0` causes no adjustment; the taxonomy of the new group is set to the archetype taxon (see below). Otherwise, disagreements within a group at a given rank cause the values at lower ranks to be set to NA. If `tax_adjust == 1` (the default), then a rank where all taxa in the group are already NA is not counted as a disagreement, and lower ranks may be kept if the taxa agree. This corresponds to the original `phyloseq` behavior. If `tax_adjust == 2`, then these NAs are treated as a disagreement; all ranks are set to NA after the first disagreement or NA.

Usage

```
merge_taxa_vec(x, group, reorder = FALSE, tax_adjust = 1L)

## S4 method for signature 'phyloseq'
merge_taxa_vec(x, group, reorder = FALSE, tax_adjust = 1L)

## S4 method for signature 'otu_table'
merge_taxa_vec(x, group, reorder = FALSE)

## S4 method for signature 'taxonomyTable'
merge_taxa_vec(x, group, reorder = FALSE, tax_adjust = 1L)

## S4 method for signature 'phylo'
merge_taxa_vec(x, group)

## S4 method for signature 'XStringSet'
merge_taxa_vec(x, group, reorder = FALSE)
```

Arguments

| | |
|---|--|
| x | A <code>phyloseq</code> object or component object |
|---|--|

| | |
|------------|--|
| group | A vector with one element for each taxon in physeq that defines the new groups. see <code>base::rowsum()</code> . |
| reorder | Logical specifying whether to reorder the taxa by their group values. Ignored if x has (or is) a phylogenetic tree. |
| tax_adjust | 0: no adjustment; 1: phyloseq-compatible adjustment; 2: conservative adjustment |

Value

A new phyloseq-class, otu_table, tax_table, XStringset or sam_data object depending on the class of the x param

Author(s)

Michael R. McLaren (orcid: [0000-0003-1575-473X](#)) modified by Adrien Taudiere

See Also

Function in MiscMetabar that use this function: [asv2otu\(\)](#)
[base::rowsum\(\)](#)
[phyloseq::merge_taxa\(\)](#)

MiscMetabar-deprecated

Deprecated function(s) in the MiscMetabar package

Description

These functions are provided for compatibility with older version of the MiscMetabar package. They may eventually be completely removed.

Usage

`physeq_graph_test(...)`

Arguments

... Parameters to be passed on to the modern version of the function

Value

Depend on the functions.

Details

| | |
|-------------------------------|---|
| <code>graph_test_pq</code> | now a synonym for <code>physeq_graph_test</code> |
| <code>adonis_pq</code> | now a synonym for <code>adonis_phyloseq</code> |
| <code>clean_pq</code> | now a synonym for <code>clean_physeq</code> |
| <code>lulu_pq</code> | now a synonym for <code>lulu_phyloseq</code> |
| <code>circle_pq</code> | now a synonym for <code>otu_circle</code> |
| <code>biplot_pq</code> | now a synonym for <code>biplot_physeq</code> |
| <code>read_pq</code> | now a synonym for <code>read_phyloseq</code> |
| <code>write_pq</code> | now a synonym for <code>write_phyloseq</code> |
| <code>sankey_pq</code> | now a synonym for <code>sankey_phyloseq</code> |
| <code>summary_plot_pq</code> | now a synonym for <code>summary_plot_phyloseq</code> |
| <code>plot_edgeR_pq</code> | now a synonym for <code>plot_edgeR_phyloseq</code> |
| <code>plot_deseq2_pq</code> | now a synonym for <code>plot_deseq2_phyloseq</code> |
| <code>venn_pq</code> | now a synonym for <code>venn_phyloseq</code> |
| <code>ggvenn_pq</code> | now a synonym for <code>ggVenn_phyloseq</code> |
| <code>hill_tuckey_pq</code> | now a synonym for <code>hill_tuckey_phyloseq</code> |
| <code>hill_pq</code> | now a synonym for <code>hill_phyloseq</code> |
| <code>heat_tree_pq</code> | now a synonym for <code>physeq_heat_tree</code> |
| <code>compare_pairs_pq</code> | now a synonym for <code>multiple_share_bisamples</code> |

`multipatt_pq`*Test and plot multipatt result*

Description

[Experimental]

A wrapper for the `indicspecies::multipatt()` function in the case of physeq object.

Usage

```
multipatt_pq(
  physeq,
  fact,
  p_adjust_method = "BH",
  pval = 0.05,
  control = permute::how(nperm = 999),
  ...
)
```

Arguments

| | |
|-----------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| fact | (required) Name of the factor in physeq@sam_data used to plot different lines |
| p_adjust_method | (chr, default "BH"): the method used to adjust p-value |
| pval | (int, default 0.05): the value to determine the significance of LCBD |
| control | see ?indicspecies::multipatt() |
| ... | Others arguments passed on to indicspecies::multipatt() function |

Details

This function is mainly a wrapper of the work of others. Please make a reference to [indicspecies::multipatt\(\)](#) if you use this function.

Value

A ggplot object

Author(s)

Adrien Taudière

Examples

```
data(data_fungi)
data_fungi_ab <- subset_taxa_pq(data_fungi, taxa_sums(data_fungi) > 10000)
multipatt_pq(subset_samples(data_fungi_ab, !is.na(Time)), fact = "Time")

multipatt_pq(subset_samples(data_fungi_ab, !is.na(Time)),
             fact = "Time",
             max.order = 1, control = permute::how(nperm = 99)
)
```

multiplot

Multiple plot function

Description

[Stable]

Usage

```
multiplot(..., plotlist = NULL, cols = 1, layout = NULL)
```

Arguments

| | |
|----------|--|
| ... | list of ggplot objects |
| plotlist | list of ggplot objects |
| cols | number of columns |
| layout | A matrix specifying the layout. If present, 'cols' is ignored. |

Value

Nothing. Print the list of ggplot objects

`multitax_bar_pq`

Plot taxonomic distribution across 3 taxonomic levels and optionally one sample factor

Description**[Experimental]**

Note that lvl3 need to be nested in lvl2 which need to be nested in lvl1

Usage

```
multitax_bar_pq(
  physeq,
  lvl1,
  lvl2,
  lvl3,
  fact = NULL,
  nb_seq = TRUE,
  log10trans = TRUE
)
```

Arguments

| | |
|------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| lvl1 | (required) Name of the first (higher) taxonomic rank of interest |
| lvl2 | (required) Name of the second (middle) taxonomic rank of interest |
| lvl3 | (required) Name of the first (lower) taxonomic rank of interest |
| fact | Name of the factor to cluster samples by modalities. Need to be in physeq@sam_data. If not set, the taxonomic distribution is plot for all samples together. |
| nb_seq | (logical; default TRUE) If set to FALSE, only the number of ASV is count. Concretely, physeq otu_table is transformed in a binary otu_table (each value different from zero is set to one) |
| log10trans | (logical, default TRUE) If TRUE, the number of sequences (or ASV if nb_seq = FALSE) is log10 transformed. |

Value

A ggplot2 graphic

Author(s)

Adrien Taudière

Examples

```
multitax_bar_pq(data_fungi_sp_known, "Phylum", "Class", "Order", "Time")
multitax_bar_pq(data_fungi_sp_known, "Phylum", "Class", "Order")
multitax_bar_pq(data_fungi_sp_known, "Phylum", "Class", "Order",
  nb_seq = FALSE, log10trans = FALSE
)
```

multi_biplot_pq

Visualization of a collection of couples of samples for comparison

Description**[Experimental]**

This allow to plot all the possible `biplot_pq()` combination using one factor.

Usage

```
multi_biplot_pq(physeq, split_by = NULL, pairs = NULL, na_remove = TRUE, ...)
```

Arguments

| | |
|------------------------|--|
| <code>physeq</code> | (required): a <code>phyloseq-class</code> object obtained using the phyloseq package. |
| <code>split_by</code> | (required if pairs is NULL) the name of the factor to make all combination of couples of values |
| <code>pairs</code> | (required if pairs is NULL) the name of the factor in physeq@sam_data` slot to make plot by pairs of samples. Each level must be present only two times. Note that if you set pairs, you also must set fact arguments to pass on to <code>biplot_pq()</code> . |
| <code>na_remove</code> | (logical, default TRUE) if TRUE remove all the samples with NA in the <code>split_by</code> variable of the physeq@sam_data slot |
| <code>...</code> | all other parameters passed on to <code>biplot_pq()</code> |

Value

a list of ggplot object

Author(s)

Adrien Taudière

Examples

```
data_fungi_abun <- subset_taxa_pq(data_fungi, taxa_sums(data_fungi) > 10000)
p <- multi_biplot_pq(data_fungi_abun, "Height")
lapply(p, print)
```

mumu_pq

MUMU reclustering of class physeq

Description**[Experimental]**

See <https://www.nature.com/articles/s41467-017-01312-x> for more information on the original method LULU. This is a wrapper of **mumu** a C++ re-implementation of LULU by Frédéric Mahé

Usage

```
mumu_pq(
  physeq,
  nproc = 1,
  id = 0.84,
  vsearchpath = "vsearch",
  mumupath = "mumu",
  verbose = FALSE,
  clean_pq = TRUE,
  keep_temporary_files = FALSE
)
```

Arguments

| | |
|----------------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| nproc | (default 1) Set to number of cpus/processors to use for the clustering |
| id | (default: 0.84) id for –usearch_global. |
| vsearchpath | (default: vsearch) path to vsearch. |
| mumupath | path to mumu . See mumu for installation instruction |
| verbose | (logical) if true, print some additional messages. |
| clean_pq | (logical) if true, empty samples and empty ASV are discarded before clustering. |
| keep_temporary_files | (logical, default: FALSE) Do we keep temporary files |

Details

This function is mainly a wrapper of the work of others. Please cite **mumu** and **lulu** if you use this function for your work.

Value

a list of for object

- "new_physeq": The new phyloseq object (class physeq)
- "mumu_results": The log file of the mumu software. Run `man mumu` into bash to obtain details about columns' signification.

Author(s)

Frédéric Mahé & Adrien Taudière <adrien.taudiere@zaclys.net>

References

- MUMU: <https://github.com/frederic-mahe/mumu>
- VSEARCH can be downloaded from <https://github.com/torognes/vsearch>.

Examples

```
## Not run:  
mumu_pq(data_fungi_sp_known)  
  
## End(Not run)
```

perc

Convert a value (or a fraction x/y) in percentage

Description

[Maturing]

Usage

```
perc(x, y = NULL, accuracy = 0, add_symbol = FALSE)
```

Arguments

| | |
|------------|--|
| x | (required): value |
| y | if y is set, compute the division of x by y |
| accuracy | number of digits (number of digits after zero) |
| add_symbol | if set to TRUE add the % symbol to the value |

Value

The percentage value (number or character if add_symbol is set to TRUE)

Author(s)

Adrien Taudière

phyloseq_to_edgeR *Convert phyloseq OTU count data into DGEList for edgeR package*

Description

Convert phyloseq OTU count data into DGEList for edgeR package

Usage

```
phyloseq_to_edgeR(physeq, group, method = "RLE", ...)
```

Arguments

| | |
|--------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| group | (required) A character vector or factor giving the experimental group/condition for each sample/library. Alternatively, you may provide the name of a sample variable. This name should be among the output of <code>sample_variables(physeq)</code> , in which case <code>get_variable(physeq, group)</code> would return either a character vector or factor. This is passed on to DGEList , and you may find further details or examples in its documentation. |
| method | The label of the edgeR-implemented normalization to use. See calcNormFactors for supported options and details. The default option is "RLE", which is a scaling factor method proposed by Anders and Huber (2010). At time of writing, the edgeR package supported the following options to the <code>method</code> argument: <code>c("TMM", "RLE", "upperquartile", "none")</code> . |
| ... | Additional arguments passed on to DGEList |

Value

A DGEList object. See `edgeR::estimateTagwiseDisp()` for more details.

physeq_or_string_to_dna

Return a DNAStringSet object from either a character vector of DNA sequences or the refseq slot of a phyloseq-class object

Description**[Stable]**

Internally used in [vsearch_clustering\(\)](#), [swarm_clustering\(\)](#) and [asv2otu\(\)](#).

Usage

```
physeq_or_string_to_dna(physeq = NULL, dna_seq = NULL)
```

Arguments

- | | |
|---------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| dna_seq | You may directly use a character vector of DNA sequences in place of physeq args. When physeq is set, dna sequences take the value of physeq@refseq |

Value

An object of class DNAStringSet (see the [Biostrings::DNAStringSet\(\)](#) function)

Author(s)

Adrien Taudière

See Also

[Biostrings::DNAStringSet\(\)](#)

Examples

```
dna <- physeq_or_string_to_dna(data_fungi)
dna

sequences_ex <- c(
  "TACCTATGTTGCCTTGGGGCTAACCTACCCGGGATTGATGGGGCGAATTAAACGAATTCAATTGAATCA",
  "TACCTATGTTGCCTTGGGGCTAACCTACCCGGGATTGATGGGGCGAATTACCTGGTAAGGCCACTT",
  "TACCTATGTTGCCTTGGGGCTAACCTACCCGGGATTGATGGGGCGAATTACCTGGTAGAGGTG",
  "TACCTATGTTGCCTTGGGGCTAACCTACC",
  "CGGGATTTGATGGCGAATTACCTGGTATTAGCCCCACTTACCCGTACCATGAGGTG",
  "GCGGCTAACCTACCCGGGATTGATGGCGAATTACCTGG",
  "GCGGCTAACCTACCCGGGATTGATGGCGAATTACAAG",
  "GCGGCTAACCTACCCGGGATTGATGGCGAATTACAAG",
  "GCGGCTAACCTACCCGGGATTGATGGCGAATTACAAG"
```

```
)
dna2 <- physeq_or_string_to_dna(dna_seq = sequences_ex)
dna2
```

plot_deseq2_pq *Plot DESeq2 results for a phyloseq or a DESeq2 object.*

Description

[Experimental]

Usage

```
plot_deseq2_pq(
  data,
  contrast = NULL,
  tax_table = NULL,
  pval = 0.05,
  taxolev = "Genus",
  select_taxa = NULL,
  color_tax = "Phylum",
  tax_depth = NULL,
  verbose = TRUE,
  jitter_width = 0.1,
  ...
)
```

Arguments

| | |
|--------------------|--|
| data | (required) a phyloseq-class or a DESeqDataSet-class object. |
| contrast | (required) contrast specifies what comparison to extract from the object to build a results table. See results man page for more details. |
| tax_table | Required if data is a DESeqDataSet-class object. The taxonomic table used to find the taxa and color_taxa arguments. If data is a phyloseq-class object, data@tax_table is used. |
| pval | (default: 0.05) the significance cutoff used for optimizing the independent filtering. If the adjusted p-value cutoff (FDR) will be a value other than 0.05, pval should be set to that value. |
| taxolev | taxonomic level of interest |
| select_taxa | Either the name of the taxa (in the form of DESeq2::results()) or a logical vector (length of the results from DESeq2::results()) to select taxa to plot. |
| color_tax | taxonomic level used for color or a color vector. |
| tax_depth | Taxonomic depth to test for differential distribution among contrast. If Null the analysis is done at the OTU (i.e. Species) level. If not Null, data need to be a column name in the tax_table slot of the phyloseq-class object. |

verbose whether the function print some information during the computation
jitter_width width for the jitter positioning
... Additional arguments passed on to [DESeq](#) or [ggplot](#)

Details

Please cite [DESeq2](#) package if you use chis function.

Value

A [ggplot2](#) plot representing [DESeq2](#) results

Author(s)

Adrien Taudière

See Also

[DESeq](#)
[results](#)
[plot_edgeR_pq](#)

Examples

```
data("GlobalPatterns", package = "phyloseq")
GP <- subset_taxa(GlobalPatterns, GlobalPatterns@tax_table[, 1] == "Archaea")
GP <- subset_samples(GP, SampleType %in% c("Soil", "Skin"))
res <- DESeq2::DESeq(phyloseq_to_deseq2(GP, ~SampleType),
  test = "Wald", fitType = "local")
)
plot_deseq2_pq(res, c("SampleType", "Soil", "Skin"),
  tax_table = GP@tax_table, color_tax = "Kingdom")
)
plot_deseq2_pq(res, c("SampleType", "Soil", "Skin"),
  tax_table = GP@tax_table, color_tax = "Kingdom",
  pval = 0.7
)
plot_deseq2_pq(res, c("SampleType", "Soil", "Skin"),
  tax_table = GP@tax_table, color_tax = "Class",
  select_taxa = c("522457", "271582")
)
```

plot_edgeR_pq *Plot edgeR results for a phyloseq or a edgeR object.*

Description

[Maturing]

Usage

```
plot_edgeR_pq(  
  physeq,  
  contrast = NULL,  
  pval = 0.05,  
  taxolev = "Genus",  
  color_tax = "Phylum",  
  verbose = TRUE,  
  ...  
)
```

Arguments

| | |
|-----------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| contrast | (required): This argument specifies what comparison to extract from the object to build a results table. See results man page for more details. |
| pval | (default: 0.05): the significance cutoff used for optimizing the independent filtering. If the adjusted p-value cutoff (FDR) will be a value other than 0.05, pval should be set to that value. |
| taxolev | taxonomic level of interest |
| color_tax | taxonomic level used for color assignation |
| verbose | (logical): whether the function print some information during the computation |
| ... | Additional arguments passed on to exactTest or ggplot |

Value

A [ggplot2](#) plot representing edgeR results

Author(s)

Adrien Taudière

See Also

[exactTest](#)
[plot_deseq2_pq](#)

Examples

```
data("GlobalPatterns", package = "phyloseq")
GP_archae <- subset_taxa(GlobalPatterns, GlobalPatterns@tax_table[, 1] == "Archaea")

plot_edgeR_pq(GP_archae, c("SampleType", "Soil", "Feces"),
  color_tax = "Kingdom"
)

plot_edgeR_pq(GP_archae, c("SampleType", "Soil", "Feces"),
  taxolev = "Class", color_tax = "Kingdom"
)
```

plot_guild_pq

Plot information about Guild from tax_table slot previously created with [add_funguild_info\(\)](#)

Description

[Experimental]

Usage

```
plot_guild_pq(physeq, levels_order = NULL, clean_pq = TRUE, ...)
```

Arguments

| | |
|--------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| levels_order | (Default NULL) A character vector to reorder the levels of guild. See examples. |
| clean_pq | (logical, default TRUE): Does the phyloseq object is cleaned using the clean_pq() function? |
| ... | other params for be passed on to clean_pq() function |

Value

A ggplot2 object

Author(s)

Adrien Taudière

See Also

[add_funguild_info\(\)](#)

Examples

```
d_fung_mini <- add_funguild_info(data_fungi_mini,
  taxLevels = c(
    "Domain",
    "Phylum",
    "Class",
    "Order",
    "Family",
    "Genus",
    "Species"
  )
)
sort(table(d_fung_mini@tax_table[, "guild"])), decreasing = TRUE)

p <- plot_guild_pq(d_fung_mini)
if (!requireNamespace("patchwork")) {
  (plot_guild_pq(subset_samples(d_fung_mini, Height == "Low"),
    levels_order = p$data$Guild[order(p$data$nb_seq)])
  ) + theme(legend.position = "none")) +
  (plot_guild_pq(subset_samples(d_fung_mini, Height == "High"),
    levels_order = p$data$Guild[order(p$data$nb_seq)])
  ) + ylab("") + theme(axis.text.y = element_blank())
}
```

plot_LCBD_pq

Plot and test local contributions to beta diversity (LCBD) of samples

Description

[Experimental]

A wrapper for the [adespatial::beta.div\(\)](#) function in the case of physeq object.

Usage

```
plot_LCBD_pq(
  physeq,
  p_adjust_method = "BH",
  pval = 0.05,
  sam_variables = NULL,
  only_plot_significant = TRUE,
  ...
)
```

Arguments

physeq (required): a [phyloseq-class](#) object obtained using the phyloseq package.
 p_adjust_method (chr, default "BH"): the method used to adjust p-value
 pval (int, default 0.05): the value to determine the significance of LCBD
 sam_variables A vector of variables names present in the `sam_data` slot to plot alongside the LCBD value
 only_plot_significant (logical, default TRUE) Do we plot all LCBD values or only the significant ones
 ... Others arguments passed on to [adespatial::beta.div\(\)](#) function

Details

This function is mainly a wrapper of the work of others. Please make a reference to `vegan::beta.div()` if you use this function.

Value

A ggplot object build with the package patchwork

Author(s)

Adrien Taudière

See Also

[LCBD_pq](#), [adespatial::beta.div\(\)](#)

Examples

```

data(data_fungi)
plot_LCBD_pq(data_fungi_mini,
  nperm = 100, only_plot_significant = FALSE,
  pval = 0.2
)

plot_LCBD_pq(data_fungi_mini,
  nperm = 100, only_plot_significant = TRUE,
  pval = 0.2
)
if (!requireNamespace("patchwork")) {
  plot_LCBD_pq(data_fungi_mini,
    nperm = 100, only_plot_significant = FALSE,
    sam_variables = c("Time", "Height")
  )
  plot_LCBD_pq(data_fungi_mini,
    nperm = 100, only_plot_significant = TRUE, pval = 0.2,
    sam_variables = c("Time", "Height", "Tree_name")
  ) &
}

```

```
theme(  
  legend.key.size = unit(0.4, "cm"),  
  legend.text = element_text(size = 10),  
  axis.title.x = element_text(size = 6)  
)  
}
```

plot_mt

Plot the result of a mt test [phyloseq::mt\(\)](#)

Description

[Maturing]

Usage

```
plot_mt(mt = NULL, alpha = 0.05, color_tax = "Class", taxa = "Species")
```

Arguments

| | |
|-----------|---|
| mt | (required) Result of a mt test from the function phyloseq::mt() . |
| alpha | (default: 0.05) Choose the cut off p-value to plot taxa. |
| color_tax | (default: "Class") A taxonomic level to color the points. |
| taxa | (default: "Species") The taxonomic level you choose for x-positioning. |

Value

a [ggplot2](#) plot of result of a mt test

Author(s)

Adrien Taudière

See Also

[phyloseq::mt\(\)](#)

Examples

```
# Filter samples that don't have Time  
data_fungi_mini2 <- subset_samples(data_fungi_mini, !is.na(Time))  
res <- mt(data_fungi_mini2, "Time", method = "fdr", test = "f", B = 300)  
plot_mt(res)  
plot_mt(res, taxa = "Genus", color_tax = "Order")
```

`plot_SCBD_pq`*Plot species contributions to beta diversity (SCBD) of samples*

Description

[Experimental]

A wrapper for the [adespatial::beta.div\(\)](#) function in the case of physeq object.

Usage

```
plot_SCBD_pq(
  physeq,
  tax_level = "ASV",
  tax_col = "Order",
  min_SCBD = 0.01,
  ...
)
```

Arguments

| | |
|------------------------|--|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>tax_level</code> | Taxonomic level to used in y axis |
| <code>tax_col</code> | Taxonomic level to colored points |
| <code>min_SCBD</code> | (default: 0.01) the minimum SCBD value to plot the taxa |
| ... | Others arguments passed on to adespatial::beta.div() function |

Details

This function is mainly a wrapper of the work of others. Please make a reference to [vegan::beta.div\(\)](#) if you use this function.

Value

A ggplot object build with the package patchwork

Author(s)

Adrien Taudière

See Also

[LCBD_pq](#), [adespatial::beta.div\(\)](#)

Examples

```
data(data_fungi)
plot_SCBD_pq(data_fungi) +
  geom_text(aes(label = paste(Genus, Species)), hjust = 1, vjust = 2) +
  xlim(c(0, NA))

plot_SCBD_pq(data_fungi, tax_level = "Class", tax_col = "Phylum", min_SCBD = 0) +
  geom_jitter()
```

plot_tax_pq

Plot taxonomic distribution in function of a factor with stacked bar in %

Description

[Experimental]

An alternative to phyloseq::plot_bar() function.

Usage

```
plot_tax_pq(
  physeq,
  fact = NULL,
  merge_sample_by = NULL,
  type = "nb_seq",
  taxa_fill = "Order",
  print_values = TRUE,
  color_border = "lightgrey",
  linewidth = 0.1,
  prop_print_value = 0.01,
  nb_print_value = NULL,
  add_info = TRUE,
  na_remove = TRUE,
  clean_pq = TRUE
)
```

Arguments

| | |
|-----------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| fact | (required) Name of the factor to cluster samples by modalities. Need to be in physeq@sam_data. |
| merge_sample_by | a vector to determine which samples to merge using the merge_samples2() function. Need to be in physeq@sam_data |

| | |
|-------------------------|--|
| type | If "nb_seq" (default), the number of sequences is used in plot. If "nb_asv", the number of ASV is plotted. If both, return a list of two plots, one for nbSeq and one for ASV. |
| taxa_fill | (default: 'Order'): Name of the taxonomic rank of interest |
| print_values | (logical, default TRUE): Do we print some values on plot? |
| color_border | color for the border |
| linewidth | The line width of geom_bar |
| prop_print_value | minimal proportion to print value (default 0.01) |
| nb_print_value | number of higher values to print (replace prop_print_value if both are set). |
| add_info | (logical, default TRUE) Do we add title and subtitle with information about the total number of sequences and the number of samples per modality. |
| na_remove | (logical, default TRUE) if TRUE remove all the samples with NA in the split_by variable of the physeq@sam_data slot |
| clean_pq | (logical) If set to TRUE, empty samples are discarded after subsetting ASV |

Value

A ggplot2 graphic

Author(s)

Adrien Taudière

See Also

[tax_bar_pq\(\)](#) and [multitax_bar_pq\(\)](#)

Examples

```
data(data_fungi_sp_known)
plot_tax_pq(data_fungi_sp_known,
            "Time",
            merge_sample_by = "Time",
            taxa_fill = "Class"
            )

plot_tax_pq(data_fungi_sp_known,
            "Height",
            merge_sample_by = "Height",
            taxa_fill = "Class",
            na_remove = TRUE,
            color_border = rgb(0, 0, 0, 0)
            )

plot_tax_pq(data_fungi_sp_known,
            "Height",
            merge_sample_by = "Height",
```

```

taxa_fill = "Class",
na_remove = FALSE,
clean_pq = FALSE
)

```

plot_tsne_pq

*Plot a tsne low dimensional representation of a phyloseq object***Description****[Experimental]****Usage**

```

plot_tsne_pq(
  physeq,
  method = "bray",
  dims = 2,
  theta = 0,
  perplexity = 30,
  fact = NA,
  ellipse_level = 0.95,
  plot_dims = c(1, 2),
  na_remove = TRUE,
  force_factor = TRUE,
  ...
)

```

Arguments

| | |
|----------------------------|--|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>method</code> | A method to calculate distance using <code>vegan::vegdist()</code> function (default: "bray") |
| <code>dims</code> | (Int) Output dimensionality (default: 2) |
| <code>theta</code> | (Numeric) Speed/accuracy trade-off (increase for less accuracy), set to 0.0 for exact TSNE (default: 0.0 see details in the man page of <code>Rtsne::Rtsne</code>). |
| <code>perplexity</code> | (Numeric) Perplexity parameter (should not be bigger than $3 * \text{perplexity} < \text{nrow}(X) - 1$, see details in the man page of <code>Rtsne::Rtsne</code>) |
| <code>fact</code> | Name of the column in <code>physeq@sam_data</code> used to color points and compute ellipses. |
| <code>ellipse_level</code> | The level used in <code>stat_ellipse</code> . Set to NULL to discard ellipse (default = 0.95) |
| <code>plot_dims</code> | A vector of 2 values defining the rank of dimension to plot (default: c(1,2)) |
| <code>na_remove</code> | (logical, default TRUE) Does the samples with NA values in fact are removed? (default: true) |
| <code>force_factor</code> | (logical, default TRUE) Force the fact column to be a factor. |
| <code>...</code> | : other arguments passed on to <code>Rtsne::Rtsne()</code> |

Details

Partially inspired by `phylosmith::tsne_phyloseq()` function developed by Schuyler D. Smith.

Value

A `ggplot` object

Author(s)

Adrien Taudière

Examples

```
data(data_fungi)
plot_tsne_pq(data_fungi, fact = "Height", perplexity = 15)

plot_tsne_pq(data_fungi, fact = "Time") + geom_label(aes(label = Sample_id, fill = Time))
plot_tsne_pq(data_fungi, fact = "Time", na_remove = FALSE, force_factor = FALSE)
```

read_pq

Read phyloseq object from multiple csv tables and a phylogenetic tree in Newick format.

Description

[Maturing]

Usage

```
read_pq(
  path = NULL,
  taxa_are_rows = FALSE,
  sam_names = NULL,
  sep_csv = "\t",
  ...
)
```

Arguments

| | |
|----------------------------|---|
| <code>path</code> | (required) a path to the folder to read the phyloseq object |
| <code>taxa_are_rows</code> | (required, default to FALSE) see <code>?phyloseq</code> for details |
| <code>sam_names</code> | The name of the variable (column) in <code>sam_data.csv</code> to rename samples. Note that if you use <code>write_phyloseq()</code> function to save your physeq object, you may use <code>sam_names = "X"</code> to rename the samples names as before. |
| <code>sep_csv</code> | (default tabulation) separator for column |
| ... | Other arguments passed on to <code>utils::write.table()</code> function. |

Value

One to four csv tables (refseq.csv, otu_table.csv, tax_table.csv, sam_data.csv) and if present a phy_tree in Newick format. At least the otu_table.csv need to be present.

Examples

```
write_pq(data_fungi, path = paste0(tempdir(), "/phyloseq"))
read_pq(path = paste0(tempdir(), "/phyloseq"))
unlink(paste0(tempdir(), "/phyloseq"), recursive = TRUE)
```

| | |
|----------------|--|
| rename_samples | <i>Rename the samples of a phyloseq slot</i> |
|----------------|--|

Description

[Maturing]

Usage

```
rename_samples(phyloseq_component, names_of_samples)
```

Arguments

phyloseq_component
 (required) one of otu_table or sam_data slot of a phyloseq-class object
names_of_samples
 (required) A vector of samples names

Value

The otu_table or the sam_data slot with new samples names

Author(s)

Adrien Taudière

Examples

```
otutab <- rename_samples(
  data_fungi@otu_table,
  paste0("data_f", sample_names(data_fungi))
)
otutab2 <- rename_samples(
  clean_pq(data_fungi,
    force_taxa_as_rows = TRUE
  )@otu_table,
  paste0("data_f", sample_names(data_fungi))
)
samda <- rename_samples(
```

```
data_fungi@sam_data,  
paste0("data_f", sample_names(data_fungi))  
)
```

rename_samples_otu_table

Rename samples of an otu_table

Description

[Experimental]

Usage

```
rename_samples_otu_table(physeq, names_of_samples)
```

Arguments

physeq (required): a [phyloseq-class](#) object obtained using the phyloseq package.
names_of_samples
 (required) The new names of the samples

Value

the matrix with new colnames (or rownames if `taxa_are_rows` is true)

Author(s)

Adrien Taudière

Examples

```
rename_samples_otu_table(data_fungi, as.character(seq_along(sample_names(data_fungi))))
```

reorder_taxa_pq *Reorder taxa in otu_table/tax_table/refseq slot of a phyloseq object*

Description

[Experimental]

Note that the taxa order in a physeq object with a tree is locked by the order of leaf in the phylogenetic tree.

Usage

```
reorder_taxa_pq(physeq, names_ordered, remove_phy_tree = FALSE)
```

Arguments

physeq (required): a [phyloseq-class](#) object obtained using the phyloseq package.
names_ordered (required): Names of the taxa (must be the same as taxa_names(physeq))
 in a given order
remove_phy_tree (logical, default FALSE) If TRUE, the phylogenetic tree is removed. It is

Value

A phyloseq object

Author(s)

Adrien Taudière

Examples

```
data_fungi_ordered_by_genus <- reorder_taxa_pq(  
  data_fungi,  
  taxa_names(data_fungi)[order(as.vector(data_fungi@tax_table[, "Genus"]))]  
)  
  
data_fungi_mini_asc_ordered_by_abundance <- reorder_taxa_pq(  
  data_fungi_mini,  
  taxa_names(data_fungi_mini)[order(taxa_sums(data_fungi_mini))])  
)
```

| | |
|------------------------|--|
| <code>ridges_pq</code> | <i>Ridge plot of a phyloseq object</i> |
|------------------------|--|

Description

[Experimental]

Usage

```
ridges_pq(physeq, fact, nb_seq = TRUE, log10trans = TRUE, ...)
```

Arguments

| | |
|-------------------------|---|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>fact</code> | (required) Name of the factor in <code>physeq@sam_data</code> used to plot different lines |
| <code>nb_seq</code> | (logical; default TRUE) If set to FALSE, only the number of ASV is count. Concretely, <code>physeq\$otu_table</code> is transformed in a binary <code>otu_table</code> (each value different from zero is set to one) |
| <code>log10trans</code> | (logical, default TRUE) If TRUE, the number of sequences (or ASV if <code>nb_seq</code> = FALSE) is log10 transformed. |
| <code>...</code> | Other params passed on to ggridges::geom_density_ridges() |

Value

A [ggplot2](#) plot with bar representing the number of sequence en each taxonomic groups

Author(s)

Adrien Taudière

Examples

```
ridges_pq(data_fungi_mini, "Time", alpha = 0.5, log10trans = FALSE) + xlim(c(0, 1000))

ridges_pq(data_fungi_mini, "Time", alpha = 0.5, scale = 0.9)
ridges_pq(data_fungi_mini, "Sample_names", log10trans = TRUE)

ridges_pq(data_fungi_mini,
          "Time",
          jittered_points = TRUE,
          position = ggridges::position_points_jitter(width = 0.05, height = 0),
          point_shape = "|", point_size = 3, point_alpha = 1, alpha = 0.7,
          scale = 0.8
        )
```

rotl_pq *rotl wrapper for phyloseq data*

Description

[Experimental] Make a phylogenetic tree using the ASV names of a physeq object and the Open Tree of Life tree.

Usage

```
rotl_pq(physeq, species_colnames = "Genus_species", context_name = "All life")
```

Arguments

| | |
|------------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| species_colnames | (default: "Genus_species"): the name of the column where the species binomial name is stored in @tax_table slot. Can also be a vector of two columns names e.g. c("Genus", "Species") |
| context_name | : can be used to select only a part of the Open Tree of Life. See ?rotl::tnrs_contexts() for available values |

Details

This function is mainly a wrapper of the work of others. Please make a reference to rotl package if you use this function.

Value

A plot

Author(s)

Adrien Taudière

Examples

```
if (!requireNamespace("rotl")) {  
  tr <- rotl_pq(data_fungi_mini, species_colnames = "Genus_species")  
  plot(tr)  
  
  tr_Astro <- rotl_pq(data_fungi, species_colnames = "Genus_species", context_name = "Ascomycetes")  
  plot(tr_Astro)  
}
```

`sample_data_with_new_names`

Load sample data from file and rename samples using names of samples and an optional order

Description

[Maturing]

Usage

```
sample_data_with_new_names(
  file_path,
  names_of_samples,
  samples_order = NULL,
  ...
)
```

Arguments

| | |
|-------------------------------|--|
| <code>file_path</code> | (required) a path to the sample_data file |
| <code>names_of_samples</code> | (required) a vector of sample names |
| <code>samples_order</code> | Optional numeric vector to sort sample names |
| <code>...</code> | Other arguments passed on to utils::read.delim() function. |

Value

A data.frame from file_path and new names

Author(s)

Adrien Taudière

See Also

[rename_samples\(\)](#)

Examples

```
sam_file <- system.file("extdata", "sam_data.csv", package = "MiscMetabar")
sample_data_with_new_names(sam_file, paste0("Samples_", seq(1, 185)))
```

sankey_pq*Sankey plot of phyloseq-class object*

Description

[Maturing]

Usage

```
sankey_pq(
  physeq = NULL,
  fact = NULL,
  taxa = 1:4,
  add_nb_seq = FALSE,
  min_prop_tax = 0,
  tax2remove = NULL,
  units = NULL,
  symbol2sub = c("\\.", "-"),
  ...
)
```

Arguments

| | |
|--------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| fact | Name of the factor to cluster samples by modalities. Need to be in physeq@sam_data. |
| taxa | a vector of taxonomic rank to plot |
| add_nb_seq | Represent the number of sequences or the number of OTUs (add_nb_seq = FALSE). Note that plotting the number of sequences is slower. |
| min_prop_tax | (default: 0) The minimum proportion for taxon to be plotted. EXPERIMENTAL. For the moment each links below the min.prop. tax is discard from the sankey network resulting in sometimes weird plot. |
| tax2remove | a vector of taxonomic groups to remove from the analysis (e.g. c('Incertae sedis', 'unidentified')) |
| units | character string describing physical units (if any) for Value |
| symbol2sub | (default: c('\\.', '-')) vector of symbol to delete in the taxonomy |
| ... | Additional arguments passed on to sankeyNetwork |

Value

A [sankeyNetwork](#) plot representing the taxonomic distribution of OTUs or sequences. If fact is set, represent the distribution of the last taxonomic level in the modalities of fact

Author(s)

Adrien Taudière

See Also

[sankeyNetwork](#)

Examples

```
data("GlobalPatterns", package = "phyloseq")
GP <- subset_taxa(GlobalPatterns, GlobalPatterns@tax_table[, 1] == "Archaea")
sankey_pq(GP, fact = "SampleType")

sankey_pq(GP, taxa = 1:4, min_prop_tax = 0.01)
sankey_pq(GP, taxa = 1:4, min_prop_tax = 0.01, add_nb_seq = TRUE)
```

save_pq

A wrapper of write_pq to save in all three possible formats

Description

A wrapper of write_pq to save in all three possible formats

Usage

```
save_pq(physeq, path = NULL, ...)
```

Arguments

- | | |
|--------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| path | a path to the folder to save the phyloseq object |
| ... | Other arguments passed on to write_pq() or utils::write.table() function. |

Details**[Maturing]**

Write :

- 4 separate tables
- 1 table version
- 1 RData file

Value

Build a folder (in path) with four csv tables (refseq.csv, otu_table.csv, tax_table.csv, sam_data.csv) + one table with all tables together + a rdata file (physeq.RData) that can be loaded using [base::load\(\)](#) function + if present a phylogenetic tree in Newick format (phy_tree.txt)

Author(s)

Adrien Taudière

See Also

[write_pq\(\)](#)

Examples

```
save_pq(data_fungi, path = paste0(tempdir(), "/phyloseq"))
unlink(paste0(tempdir(), "/phyloseq"), recursive = TRUE)
```

search_exact_seq_pq *Search for exact matching of sequences using complement, reverse and reverse-complement*

Description

[Experimental]

Usage

```
search_exact_seq_pq(physeq, seq2search)
```

Arguments

| | |
|------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| seq2search | A DNAStringSet object of sequences to search for. |

Value

A list of data-frames for each input sequences with the name, the sequences and the number of occurrences of the original sequence, the complement sequence, the reverse sequence and the reverse-complement sequence.

Author(s)

Adrien Taudière

Examples

```
data("data_fungi")
search_primers <- search_exact_seq_pq(data_fungi,
  seq2search = Biostrings::DNAStringSet(c("TTGAACGCACATTGCGCC", "ATCCCTACCTGATCCGAG"))
)
```

`select_one_sample` *Select one sample from a physeq object*

Description

[Experimental]

Mostly for internal used, for example in function `track_wkflow_samples()`.

Usage

```
select_one_sample(physeq, sam_name, silent = FALSE)
```

Arguments

| | |
|-----------------------|--|
| <code>physeq</code> | (required): a <code>phyloseq-class</code> object obtained using the <code>phyloseq</code> package. |
| <code>sam_name</code> | (required) The sample name to select |
| <code>silent</code> | (logical) If true, no message are printing. |

Value

a physeq object with one sample

Author(s)

Adrien Taudière

Examples

```
A8_005 <- select_one_sample(data_fungi, "A8-005_S4_MERGED.fastq.gz")
A8_005
```

`select_taxa` *Select a subset of taxa in a specified order where possible*

Description

Select (a subset of) taxa; if `x` allows taxa to be reordered, then taxa are given in the specified order.

Usage

```
select_taxa(x, taxa, reorder = TRUE)

## S4 method for signature 'sample_data,character'
select_taxa(x, taxa)

## S4 method for signature 'otu_table,character'
select_taxa(x, taxa, reorder = TRUE)

## S4 method for signature 'taxonomyTable,character'
select_taxa(x, taxa, reorder = TRUE)

## S4 method for signature 'XStringSet,character'
select_taxa(x, taxa, reorder = TRUE)

## S4 method for signature 'phylo,character'
select_taxa(x, taxa)

## S4 method for signature 'phyloseq,character'
select_taxa(x, taxa, reorder = TRUE)
```

Arguments

| | |
|---------|---|
| x | A phyloseq object or phyloseq component object |
| taxa | Character vector of taxa to select, in requested order |
| reorder | Logical specifying whether to use the order in taxa (TRUE) or keep the order in taxa_names(x) (FALSE) |

Details

This is a simple selector function that is like prune_taxa(taxa, x) when taxa is a character vector but always gives the taxa in the order taxa if possible (that is, except for phy_tree's and phyloseq objects that contain phy_tree's).

Author(s)

Michael R. McLaren (orcid: [0000-0003-1575-473X](#))

| | |
|---------------|---|
| simplify_taxo | <i>Simplify taxonomy by removing some unused characters such as "k__"</i> |
|---------------|---|

Description

[Maturing]

Usage

```
simplify_taxo(physeq, remove_space = TRUE)
```

Arguments

- physeq (required): a [phyloseq-class](#) object obtained using the phyloseq package.
- remove_space (logical; default TRUE): do we remove space?

Value

A [phyloseq-class](#) object with simplified taxonomy

Author(s)

Adrien Taudière

SRS_curve_pq

Scaling with ranked subsampling (SRS) curve of phyloseq object

Description

[Experimental]

Usage

```
SRS_curve_pq(physeq, clean_pq = FALSE, ...)
```

Arguments

- physeq (required): a [phyloseq-class](#) object obtained using the phyloseq package.
- clean_pq (logical): Does the phyloseq object is cleaned using the [clean_pq\(\)](#) function?
- ... Other arguments passed on to SRS::SRScurve()

Value

A plot

Examples

```
SRS_curve_pq(data_fungi_mini,
  max.sample.size = 200,
  rarefy.comparison = TRUE, rarefy.repeats = 5
)
SRS_curve_pq(data_fungi_mini, max.sample.size = 1000, metric = "shannon")
```

| | |
|-----------------|---|
| subsample_fastq | <i>Subsample a fastq file copying the n_seq first sequences in a given folder</i> |
|-----------------|---|

Description

[Experimental]

Usage

```
subsample_fastq(fastq_files, folder_output = "subsample", nb_seq = 1000)
```

Arguments

| | |
|---------------|---|
| fastq_files | The path to one fastq file or a list of fastq files (see examples) |
| folder_output | The path to a folder for output files |
| nb_seq | (int; default 1000) : Number of sequences kept (every sequence spread across 4 lines) |

Value

Nothing, create subsampled fastq files in a folder

Author(s)

Adrien Taudière

Examples

```
ex_file <- system.file("extdata", "ex_R1_001.fastq.gz",
  package = "MiscMetabar",
  mustWork = TRUE
)
subsample_fastq(ex_file, paste0(tempdir(), "/output_fastq"))
subsample_fastq(list_fastq_files("extdata"), paste0(tempdir(), "/output_fastq"), n = 10)
unlink(paste0(tempdir(), "/output_fastq"), recursive = TRUE)
```

| | |
|--------------------------------|---|
| <code>subset_samples_pq</code> | <i>Subset samples using a conditional boolean vector.</i> |
|--------------------------------|---|

Description

[Experimental]

The main objective of this function is to complete the `phyloseq::subset_samples()` function by propose a more easy (but more prone to error) way of subset_samples. It replace the subsetting expression which used the name of the variable in the sam_data by a boolean vector.

Warnings: you must verify the result of this function as the boolean condition must match the order of samples in the sam_data slot.

This function is robust when you use the sam_data slot of the phyloseq object used in physeq (see examples)

Usage

```
subset_samples_pq(physeq, condition)
```

Arguments

| | |
|------------------------|---|
| <code>physeq</code> | (required): a <code>phyloseq-class</code> object obtained using the phyloseq package. |
| <code>condition</code> | A boolean vector to subset samples. Length must fit the number of samples |

Value

a new phyloseq object

Examples

```
cond_samp <- grepl("A1", data_fungi@sam_data[["Sample_names"]])
subset_samples_pq(data_fungi, cond_samp)

subset_samples_pq(data_fungi, data_fungi@sam_data[["Height"]] == "Low")
```

| | |
|-----------------------------|--|
| <code>subset_taxa_pq</code> | <i>Subset taxa using a conditional named boolean vector.</i> |
|-----------------------------|--|

Description

[Experimental]

The main objective of this function is to complete the `phyloseq::subset_taxa()` function by propose a more easy way of subset_taxa using a named boolean vector. Names must match taxa_names.

Usage

```
subset_taxa_pq(  
  physeq,  
  condition,  
  verbose = TRUE,  
  clean_pq = TRUE,  
  taxa_names_from_physeq = FALSE  
)
```

Arguments

| | |
|------------------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| condition | A named boolean vector to subset taxa. Length must fit the number of taxa and names must match taxa_names. Can also be a condition using a column of the tax_table slot (see examples). If the order of condition is the same as taxa_names(physeq), you can use the parameter taxa_names_from_physeq = TRUE. |
| verbose | (logical) Informations are printed |
| clean_pq | (logical) If set to TRUE, empty samples are discarded after subsetting ASV |
| taxa_names_from_physeq | (logical) If set to TRUE, rename the condition vector using taxa_names(physeq). Carefully check the result of this function if you use this parameter. No effect if the condition is of class tax_table. |

Value

a new phyloseq object

Examples

```
subset_taxa_pq(data_fungi, data_fungi@tax_table[, "Phylum"] == "Ascomycota")  
  
cond_taxa <- grepl("Endophyte", data_fungi@tax_table[, "Guild"])  
names(cond_taxa) <- taxa_names(data_fungi)  
subset_taxa_pq(data_fungi, cond_taxa)  
  
subset_taxa_pq(data_fungi, grepl("mycor", data_fungi@tax_table[, "Guild"]),  
  taxa_names_from_physeq = TRUE  
)
```

subset_taxa_tax_control

Subset taxa using a taxa control (e.g. truffle root tips) through 3 methods.

Description

[Experimental]

Usage

```
subset_taxa_tax_control(
  physeq,
  taxa_distri,
  method = "mean",
  min_diff_for_cutoff = NULL
)
```

Arguments

| | |
|----------------------------------|--|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the phyloseq package. |
| <code>taxa_distri</code> | (required) a vector of length equal to the number of samples with the number of sequences per samples for the taxa control |
| <code>method</code> | (default: "mean") a method to calculate the cut-off value. There is 6 available methods: |
| | 1. <code>cutoff_seq</code> : discard taxa with less than the number of sequence than taxa control, |
| | 2. <code>cutoff_mixt</code> : using mixture models, |
| | 3. <code>cutoff_diff</code> : using a minimum difference threshold (need the argument <code>min_diff_for_cutoff</code>) |
| | 4. <code>min</code> : the minimum of the three firsts methods |
| | 5. <code>max</code> : the maximum of the three firsts methods |
| | 6. <code>mean</code> : the mean of the three firsts methods |
| <code>min_diff_for_cutoff</code> | (int) argument for method <code>cutoff_diff</code> . Required if method is <code>cutoff_diff</code> , <code>min</code> , <code>max</code> or <code>mean</code> |

Value

A new [phyloseq-class](#) object.

Author(s)

Adrien Taudière

Examples

```
subset_taxa_tax_control(data_fungi,
  as.numeric(data_fungi@otu_table[, 300]),
  min_diff_for_cutoff = 2
)
```

summary_plot_pq

Summarise a phyloseq-class object using a plot.

Description

[Maturing]

Usage

```
summary_plot_pq(
  physeq,
  add_info = TRUE,
  min_seq_samples = 500,
  clean_pq = TRUE
)
```

Arguments

| | |
|-----------------|---|
| physeq | (required): a phyloseq-class object obtained using the <code>phyloseq</code> package. |
| add_info | Does the bottom down corner contain extra informations? |
| min_seq_samples | (int): Used only when <code>add_info</code> is set to true to print the number of samples with less sequences than this number. |
| clean_pq | (logical): Does the <code>phyloseq</code> object is cleaned using the <code>clean_pq()</code> function? |

Value

A `ggplot2` object

Examples

```
summary_plot_pq(data_fungi)
summary_plot_pq(data_fungi, add_info = FALSE) + scale_fill_viridis_d()
```

| | |
|------------------|---|
| swarm_clustering | <i>Re-cluster sequences of an object of class physeq or cluster a list of DNA sequences using SWARM</i> |
|------------------|---|

Description

[Maturing]

Usage

```
swarm_clustering(
  physeq = NULL,
  dna_seq = NULL,
  d = 1,
  swarmpath = "swarm",
  vsearch_path = "vsearch",
  nproc = 1,
  swarm_args = "--fastidious",
  tax_adjust = 0,
  keep_temporary_files = FALSE
)
```

Arguments

| | |
|----------------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| dna_seq | NOT WORKING FOR THE MOMENT You may directly use a character vector of DNA sequences in place of physeq args. When physeq is set, dna sequences take the value of physeq@refseq |
| d | (default: 1) maximum number of differences allowed between two amplicons, meaning that two amplicons will be grouped if they have d (or less) differences |
| swarmpath | (default: swarm) path to swarm |
| vsearch_path | (default: vsearch) path to vsearch, used only if physeq is NULL and dna_seq is provided. |
| nproc | (default: 1) Set to number of cpus/processors to use for the clustering |
| swarm_args | (default : "-fastidious") a one length character element defining other parameters to passed on to swarm See other possible methods in the SWARM pdf manual |
| tax_adjust | (Default 0) See the man page of merge_taxa_vec() for more details. To con-served the taxonomic rank of the most abundant ASV, |
| keep_temporary_files | (logical, default: FALSE) Do we keep temporary files ? <ul style="list-style-type: none"> • temp.fasta (refseq in fasta or dna_seq sequences) • temp_output (classical output of SWARM) • temp_uclust (clusters output of SWARM) |

Details

This function use the `merge_taxa_vec` function to merge taxa into clusters. By default tax_adjust = 0. See the man page of [merge_taxa_vec\(\)](#).

This function is mainly a wrapper of the work of others. Please cite **SWARM**.

Value

A new object of class physeq or a list of cluster if dna_seq args was used.

References

SWARM can be downloaded from <https://github.com/torognes/swarm/>.

SWARM can be downloaded from <https://github.com/torognes/swarm>. More information in the associated publications [doi:10.1093/bioinformatics/btab493](https://doi.org/10.1093/bioinformatics/btab493) and [doi:10.7717/peerj.593](https://doi.org/10.7717/peerj.593)

See Also

[asv2otu\(\)](#), [vsearch_clustering\(\)](#)

Examples

```
summary_plot_pq(data_fungi)
system2("swarm", "-h")

data_fungi_swarm <- swarm_clustering(data_fungi)
summary_plot_pq(data_fungi_swarm)

sequences_ex <- c(
  "TACCTATGTTGCCTTGGCGGCTAACCTACCCGGGATTGATGGGGCGAATTAAACGAATTCAATTGAATCA",
  "TACCTATGTTGCCTTGGCGGCTAACCTACCCGGGATTGATGGGGCGAATTACCTGGTAAGGCCACTT",
  "TACCTATGTTGCCTTGGCGGCTAACCTACCCGGGATTGATGGGGCGAATTACCTGGTAGAGGTG",
  "TACCTATGTTGCCTTGGCGGCTAACCTACC",
  "CGGGATTTGATGGCGAATTACCTGGTATTTAGCCCACCTACCCGGTACCATGAGGTG",
  "GCGGCTAACCTACCCGGGATTGATGGCGAATTACCTGG",
  "GCGGCTAACCTACCCGGGATTGATGGCGAATTACAAAG",
  "GCGGCTAACCTACCCGGGATTGATGGCGAATTACAAAG",
  "GCGGCTAACCTACCCGGGATTGATGGCGAATTACAAAG"
)

sequences_ex_swarm <- swarm_clustering(
  dna_seq = sequences_ex
)
```

tax_bar_pq*Plot the distribution of sequences or ASV in one taxonomic levels*

Description**[Experimental]****Usage**

```
tax_bar_pq(
  physeq,
  fact = "Sample",
  taxa = "Order",
  percent_bar = FALSE,
  nb_seq = TRUE
)
```

Arguments

| | |
|-------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| fact | Name of the factor to cluster samples by modalities. Need to be in physeq@sam_data. |
| taxa | (default: 'Order') Name of the taxonomic rank of interest |
| percent_bar | (default FALSE) If TRUE, the stacked bar fill all the space between 0 and 1. It just set position = "fill" in the ggplot2::geom_bar() function |
| nb_seq | (logical; default TRUE) If set to FALSE, only the number of ASV is count. Concretely, physeq otu_table is transformed in a binary otu_table (each value different from zero is set to one) |

Value

A [ggplot2](#) plot with bar representing the number of sequence en each taxonomic groups

Author(s)

Adrien Taudière

See Also

[plot_tax_pq\(\)](#) and [multitax_bar_pq\(\)](#)

Examples

```
data_fungi_ab <- subset_taxa_pq(data_fungi, taxa_sums(data_fungi) > 10000)
tax_bar_pq(data_fungi_ab) + theme(legend.position = "none")

tax_bar_pq(data_fungi_ab, taxa = "Class")
```

```
tax_bar_pq(data_fungi_ab, taxa = "Class", percent_bar = TRUE)
tax_bar_pq(data_fungi_ab, taxa = "Class", fact = "Time")
```

tax_datatable

Make a datatable with the taxonomy of a phyloseq-class object

Description

[Maturing]

Usage

```
tax_datatable(
  physeq,
  abundance = TRUE,
  taxonomic_level = NULL,
  modality = NULL,
  ...
)
```

Arguments

| | |
|-----------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| abundance | (default: TRUE) Does the number of sequences is print |
| taxonomic_level | (default: NULL) a vector of selected taxonomic level using their column numbers (e.g. taxonomic_level = 1:7) |
| modality | (default: NULL) A sample modality to split OTU abundance by level of the modality |
| ... | Other argument for the datatable function |

Value

A datatable

Author(s)

Adrien Taudière

Examples

```
data("GlobalPatterns", package = "phyloseq")
tax_datatable(subset_taxa(
  GlobalPatterns,
  rowSums(GlobalPatterns@otu_table) > 10000
))

# Using modality
tax_datatable(GlobalPatterns,
  modality = GlobalPatterns@sam_data$SampleType
)
```

tbl_sum_samdata

Summarize information from sample data in a table

Description

[Experimental]

A wrapper for the [gtsummary::tbl_summary\(\)](#) function in the case of physeq object.

Usage

```
tbl_sum_samdata(physeq, remove_col_unique_value = TRUE, ...)
```

Arguments

| | |
|-------------------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| remove_col_unique_value | (logical, default TRUE) Do we remove informative columns (categorical column with one value per samples), e.g. samples names ? |
| ... | Others arguments pass on to gtsummary::tbl_summary() . |

Details

This function is mainly a wrapper of the work of others. Please make a reference to [gtsummary::tbl_summary\(\)](#) if you use this function.

Value

a physeq object with a larger slot tax_table

Author(s)

Adrien Taudière

Examples

```
tbl_sum_samdata(data_fungi) %>%
  gtsummary::as_kable()

summary_samdata <- tbl_sum_samdata(data_fungi,
  include = c("Time", "Height"),
  type = list(Time ~ "continuous2", Height ~ "categorical"),
  statistic = list(Time ~ c("{median} ({p25}, {p75})", "{min}, {max}")))
)

data(enterotype)

summary_samdata <- tbl_sum_samdata(enterotype)
summary_samdata <- tbl_sum_samdata(enterotype, include = !contains("SampleId"))
```

Tengeler2020_pq

This tutorial explore the dataset from Tengeler et al. (2020) available in the mia package. obtain using mia::makePhyloseqFromTreeSE(Tengeler2020)

Description

This is a phyloseq version of the Tengeler2020 dataset.

Usage

```
data(Tengeler2020_pq)
```

Format

A phyloseq object

Details

Tengeler2020 includes gut microbiota profiles of 27 persons with ADHD. A standard bioinformatic and statistical analysis done to demonstrate that altered microbial composition could be a driver of altered brain structure and function and concomitant changes in the animals behavior. This was investigated by colonizing young, male, germ-free C57BL/6JOlaHsd mice with microbiota from individuals with and without ADHD.

Tengeler, A.C., Dam, S.A., Wiesmann, M. et al. Gut microbiota from persons with attention-deficit/hyperactivity disorder affects the brain in mice. *Microbiome* 8, 44 (2020). <https://microbiomejournal.biomedcentral.com/10.1186/s40168-020-00816-x>

| | |
|---------------------------|---|
| <code>track_wkflow</code> | <i>Track the number of reads (= sequences), samples and cluster (e.g. ASV) from various objects including dada-class and derep-class.</i> |
|---------------------------|---|

Description

[Maturing]

- List of fastq and fastg.gz files -> nb of reads and samples
- List of dada-class -> nb of reads, clusters (ASV) and samples
- List of derep-class -> nb of reads, clusters (unique sequences) and samples
- Matrix of samples x clusters (e.g. otu_table) -> nb of reads, clusters and samples
- Phyloseq-class -> nb of reads, clusters and samples

Usage

```
track_wkflow(
  list_of_objects,
  obj_names = NULL,
  clean_pq = FALSE,
  taxonomy_rank = NULL,
  ...
)
```

Arguments

| | |
|------------------------------|---|
| <code>list_of_objects</code> | (required) a list of objects |
| <code>obj_names</code> | A list of names corresponding to the list of objects |
| <code>clean_pq</code> | (logical) If set to TRUE, empty samples and empty ASV are discarded before clustering. |
| <code>taxonomy_rank</code> | A vector of int. Define the column number of taxonomic rank in physeq@tax_table to compute the number of unique value. Default is NULL and do not compute values for any taxonomic rank |
| ... | Other arguments passed on to <code>clean_pq()</code> function. |

Value

The number of sequences, clusters (e.g. OTUs, ASVs) and samples for each object.

See Also

[track_wkflow_samples\(\)](#)

Examples

```
data(enterotype)
track_wkflow(list(data_fungi, enterotype), taxonomy_rank = c(3, 5))
```

track_wkflow_samples *Track the number of reads (= sequences), samples and cluster (e.g. ASV) for each samples.*

Description

[Experimental]

Contrary to [track_wkflow\(\)](#), only phyloseq object are possible. More information are available in the manual of the function [track_wkflow\(\)](#)

Usage

```
track_wkflow_samples(list_pq_obj, ...)
```

Arguments

list_pq_obj (required): a list of object passed on to [track_wkflow\(\)](#) Only phyloseq object will return value because information of sample is needed
... : other args passed on to [track_wkflow\(\)](#)

Value

A list of dataframe. cf [track_wkflow\(\)](#) for more information

Author(s)

Adrien Taudière

Examples

```
tree_A10_005 <- subset_samples(data_fungi, Tree_name == "A10-005")
track_wkflow_samples(tree_A10_005)
```

treemap_pq*Plot treemap of 2 taxonomic levels*

Description

[Experimental]

Note that lvl2 need to be nested in lvl1

Usage

```
treemap_pq(
  physeq,
  lvl1,
  lvl2,
  nb_seq = TRUE,
  log10trans = TRUE,
  plot_legend = FALSE,
  ...
)
```

Arguments

| | |
|-------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| lvl1 | (required) Name of the first (higher) taxonomic rank of interest |
| lvl2 | (required) Name of the second (lower) taxonomic rank of interest |
| nb_seq | (logical; default TRUE) If set to FALSE, only the number of ASV is count. Concretely, physeq otu_table is transformed in a binary otu_table (each value different from zero is set to one) |
| log10trans | (logical, default TRUE) If TRUE, the number of sequences (or ASV if nb_seq = FALSE) is log10 transformed. |
| plot_legend | (logical, default FALSE) If TRUE, plot the legend of color for lvl 1 |
| ... | Other arguments passed on to treemapify::geom_treemap() function. |

Value

A ggplot2 graphic

Author(s)

Adrien Taudière

Examples

```
data(data_fungi_sp_known)
treemap_pq(
  clean_pq(subset_taxa(
    data_fungi_sp_known,
    Phylum == "Basidiomycota"
  )),
  "Order", "Class",
  plot_legend = TRUE
)

treemap_pq(
  clean_pq(subset_taxa(
    data_fungi_sp_known,
    Phylum == "Basidiomycota"
  )),
  "Order", "Class",
  log10trans = FALSE
)
treemap_pq(
  clean_pq(subset_taxa(
    data_fungi_sp_known,
    Phylum == "Basidiomycota"
  )),
  "Order", "Class",
  nb_seq = FALSE, log10trans = FALSE
)
```

tsne_pq

Compute tSNE position of samples from a phyloseq object

Description

Compute tSNE position of samples from a phyloseq object

Usage

```
tsne_pq(physeq, method = "bray", dims = 2, theta = 0, perplexity = 30, ...)
```

Arguments

| | |
|--------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| method | A method to calculate distance using <code>vegan::vegdist()</code> function |
| dims | (Int) Output dimensionality (default: 2) |
| theta | (Numeric) Speed/accuracy trade-off (increase for less accuracy), set to 0.0 for exact TSNE (default: 0.0 see details in the man page of <code>Rtsne::Rtsne</code>). |

`perplexity` (Numeric) Perplexity parameter (should not be bigger than $3 * \text{perplexity} < \text{nrow}(X) - 1$, see details in the man page of `Rtsne::Rtsne`)
`...` : other arguments passed on to `Rtsne::Rtsne()`

Value

A list of element including the matrix `Y` containing the new representations for the objects. See `?Rtsne::Rtsne()` for more information

Examples

```
res_tsne <- tsne_pq(data_fungi)
```

| | |
|---------------------------|--|
| <code>unique_or_na</code> | <i>Get the unique value in x or NA if none</i> |
|---------------------------|--|

Description

If `unique(x)` is a single value, return it; otherwise, return an NA of the same type as `x`. If `x` is a factor, then the levels and ordered status will be kept in either case. If `x` is a non-atomic vector (i.e. a list), then the logical NA will be used.

Usage

```
unique_or_na(x)
```

Arguments

`x` A vector

Value

Either a single value (if `unique(x)` return a single value) or a NA

Author(s)

Michael R. McLaren (orcid: [0000-0003-1575-473X](#))

Examples

```
f <- factor(c("a", "a", "b", "c"), ordered = TRUE)
unique_or_na(f)
unique_or_na(f[1:2])

x <- c("a", "b", "a")
unique_or_na(x[c(1, 3)])
unique_or_na(x)
unique_or_na(x) %>% typeof()
```

| | |
|----------|---|
| upset_pq | <i>Make upset plot for phyloseq object.</i> |
|----------|---|

Description

[Experimental]

Alternative to venn plot.

Usage

```
upset_pq(  
  physeq,  
  fact,  
  taxa_fill = NULL,  
  min_nb_seq = 0,  
  na_remove = TRUE,  
  numeric_fonction = sum,  
  rarefy_after_merging = FALSE,  
  ...  
)
```

Arguments

| | |
|----------------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| fact | (required): Name of the factor to cluster samples by modalities. Need to be in physeq@sam_data. |
| taxa_fill | (default NULL) fill the ASV upset using a column in tax_table slot. |
| min_nb_seq | minimum number of sequences by OTUs by samples to take into count this OTUs in this sample. For example, if min_nb_seq=2, each value of 2 or less in the OTU table will not count in the venn diagram |
| na_remove | : if TRUE (the default), NA values in fact are removed if FALSE, NA values are set to "NA" |
| numeric_fonction | (default : sum) the function for numeric vector useful only for complex plot (see examples) |
| rarefy_after_merging | Rarefy each sample after merging by the modalities of fact parameter |
| ... | other arguments passed on to the ComplexUpset::upset() |

Value

A [ggplot2](#) plot

Author(s)

Adrien Taudière

See Also

[ggvenn_pq\(\)](#)

Examples

```
upset_pq(data_fungi_mini,
  fact = "Height", width_ratio = 0.2,
  taxa_fill = "Class"
)

upset_pq(data_fungi_mini, fact = "Height", min_nb_seq = 1000)
upset_pq(data_fungi_mini, fact = "Height", na_remove = FALSE)

upset_pq(data_fungi_mini, fact = "Time", width_ratio = 0.2, rarefy_after_merging = TRUE)

upset_pq(
  data_fungi_mini,
  fact = "Time",
  width_ratio = 0.2,
  annotations = list(
    "Sequences per ASV \n (log10)" = (
      ggplot(mapping = aes(y = log10(Abundance)))
      +
      geom_jitter(aes(
        color =
          Abundance
      ), na.rm = TRUE)
      +
      geom_violin(alpha = 0.5, na.rm = TRUE) +
      theme(legend.key.size = unit(0.2, "cm")) +
      theme(axis.text = element_text(size = 12))
    ),
    "ASV per phylum" = (
      ggplot(mapping = aes(fill = Phylum))
      +
      geom_bar() +
      ylab("ASV per phylum") +
      theme(legend.key.size = unit(0.2, "cm")) +
      theme(axis.text = element_text(size = 12))
    )
  )
)

upset_pq(
  data_fungi_mini,
  fact = "Time",
  width_ratio = 0.2,
  numeric_fonction = mean,
  annotations = list(
    "Sequences per ASV \n (log10)" = (
```

```
ggplot(mapping = aes(y = log10(Abundance)))
+
  geom_jitter(aes(
    color =
      Abundance
  ), na.rm = TRUE)
+
  geom_violin(alpha = 0.5, na.rm = TRUE) +
  theme(legend.key.size = unit(0.2, "cm")) +
  theme(axis.text = element_text(size = 12))
),
"ASV per phylum" = (
  ggplot(mapping = aes(fill = Phylum))
+
  geom_bar() +
  ylab("ASV per phylum") +
  theme(legend.key.size = unit(0.2, "cm")) +
  theme(axis.text = element_text(size = 12))
)
)
)

upset_pq(
  subset_taxa(data_fungi_mini, Phylum == "Basidiomycota"),
  fact = "Time",
  width_ratio = 0.2,
  base_annotations = list(),
  annotations = list(
    "Sequences per ASV \n (log10)" = (
      ggplot(mapping = aes(y = log10(Abundance)))
+
      geom_jitter(aes(
        color =
          Abundance
      ), na.rm = TRUE)
+
      geom_violin(alpha = 0.5, na.rm = TRUE) +
      theme(legend.key.size = unit(0.2, "cm")) +
      theme(axis.text = element_text(size = 12))
),
    "ASV per phylum" = (
      ggplot(mapping = aes(fill = Class))
+
      geom_bar() +
      ylab("ASV per Class") +
      theme(legend.key.size = unit(0.2, "cm")) +
      theme(axis.text = element_text(size = 12))
)
)
)

data_fungi2 <- data_fungi_mini
```

```

data_fungi2@sam_data[["Time_0"]] <- data_fungi2@sam_data$Time == 0
data_fungi2@sam_data[["Height__Time_0"]] <-
  paste0(data_fungi2@sam_data[["Height"]], " __ ", data_fungi2@sam_data[["Time_0"]])
data_fungi2@sam_data[["Height__Time_0"]][grep1("NA", data_fungi2@sam_data[["Height__Time_0"]])] <-
  NA
upset_pq(data_fungi2, fact = "Height__Time_0", width_ratio = 0.2, min_size = 2)

```

upset_test_pq

*Test for differences between intersections***Description****[Experimental]****Usage**

```

upset_test_pq(
  physeq,
  fact,
  var_to_test = "OTU",
  min_nb_seq = 0,
  na_remove = TRUE,
  numeric_fonction = sum,
  ...
)

```

Arguments

| | |
|-------------------------------|---|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the <code>phyloseq</code> package. |
| <code>fact</code> | (required): Name of the factor to cluster samples by modalities. Need to be in <code>physeq@sam_data</code> . |
| <code>var_to_test</code> | (default c("OTU")) : a vector of column present in the <code>tax_table</code> slot from the <code>physeq</code> object |
| <code>min_nb_seq</code> | minimum number of sequences by OTUs by samples to take into count this OTUs in this sample. For example, if <code>min_nb_seq=2</code> , each value of 2 or less in the OTU table will not count in the venn diagram |
| <code>na_remove</code> | : if TRUE (the default), NA values in fact are removed if FALSE, NA values are set to "NA" |
| <code>numeric_fonction</code> | (default : <code>sum</code>) the function for numeric vector useful only for complex plot (see examples) |
| <code>...</code> | other arguments passed on to the ComplexUpset::upset_test() |

ValueA `ggplot2` plot

Author(s)

Adrien Taudière

See Also

[upset_pq\(\)](#)

Examples

```
data(data_fungi)
upset_test_pq(data_fungi, "Height", var_to_test = c("OTU", "Class", "Guild"))
upset_test_pq(data_fungi, "Time")
```

venn_pq

Venn diagram of phyloseq-class object

Description

[Maturing]

Usage

```
venn_pq(physeq, fact, min_nb_seq = 0, print_values = TRUE)
```

Arguments

| | |
|--------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| fact | (required): Name of the factor to cluster samples by modalities. Need to be in <code>physeq@sam_data</code> . |
| min_nb_seq | (default: 0)): minimum number of sequences by OTUs by samples to take into count this OTUs in this sample. For example, if <code>min_nb_seq=2</code> , each value of 2 or less in the OTU table will be change into 0 for the analysis |
| print_values | (logical) Print (or not) the table of number of OTUs for each combination. If <code>print_values</code> is TRUE the object is not a ggplot object. Please use <code>print_values = FALSE</code> if you want to add ggplot function (cf example). |

Value

A [ggplot2](#) plot representing Venn diagram of modalities of the argument `factor`

Author(s)

Adrien Taudière

See Also

[venneuler](#)

Examples

```
data("enterotype")
venn_pq(enterotype, fact = "SeqTech")

venn_pq(enterotype, fact = "ClinicalStatus")
venn_pq(enterotype, fact = "Nationality", print_values = FALSE)
venn_pq(enterotype, fact = "ClinicalStatus", print_values = FALSE) +
  scale_fill_hue()
venn_pq(enterotype, fact = "ClinicalStatus", print_values = FALSE) +
  scale_fill_hue()
```

verify_pq

Verify the validity of a phyloseq object

Description

[Maturing]

Mostly for internal use in MiscMetabar functions.

Usage

```
verify_pq(
  physeq,
  verbose = FALSE,
  min_nb_seq_sample = 500,
  min_nb_seq_taxa = 1
)
```

Arguments

| | |
|--------------------------------|--|
| <code>physeq</code> | (required): a phyloseq-class object obtained using the <code>phyloseq</code> package. |
| <code>verbose</code> | (logical, default FALSE) If TRUE, prompt some warnings. |
| <code>min_nb_seq_sample</code> | (numeric) Only used if <code>verbose</code> = TRUE. Minimum number of sequences per samples to not show warning. |
| <code>min_nb_seq_taxa</code> | (numeric) Only used if <code>verbose</code> = TRUE. Minimum number of sequences per taxa to not show warning. |

Value

Nothing if the `phyloseq` object is valid. An error in the other case. Warnings if `verbose` = TRUE

vsearch_clustering *Recluster sequences of an object of class physeq or cluster a list of DNA sequences using vsearch software*

Description

[Maturing]

Usage

```
vsearch_clustering(  
  physeq = NULL,  
  dna_seq = NULL,  
  nproc = 1,  
  id = 0.97,  
  vsearchpath = "vsearch",  
  tax_adjust = 0,  
  vsearch_cluster_method = "--cluster_size",  
  vsearch_args = "--strand both",  
  keep_temporary_files = FALSE  
)
```

Arguments

| | |
|------------------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| dna_seq | You may directly use a character vector of DNA sequences in place of physeq args. When physeq is set, dna sequences take the value of physeq@refseq |
| nproc | (default: 1) Set to number of cpus-processors to use for the clustering |
| id | (default: 0.97) level of identity to cluster |
| vsearchpath | (default: vsearch) path to vsearch |
| tax_adjust | (Default 0) See the man page of merge_taxa_vec() for more details. To conserved the taxonomic rank of the most abundant ASV, set tax_adjust to 0 (default). For the moment only tax_adjust = 0 is robust |
| vsearch_cluster_method | (default: "--cluster_size") See other possible methods in the vsearch manual (e.g. --cluster_size or --cluster_smallmem) <ul style="list-style-type: none">• --cluster_fast : Clusterize the fasta sequences in filename, automatically sort by decreasing sequence length beforehand.• --cluster_size : Clusterize the fasta sequences in filename, automatically sort by decreasing sequence abundance beforehand.• --cluster_smallmem : Clusterize the fasta sequences in filename without automatically modifying their order beforehand. Sequence are expected to be sorted by decreasing sequence length, unless <i>-usersort</i> is used. In that case you may set vsearch_args to vsearch_args = "-strand both -usersort" |

```
vsearch_args (default : "-strand both") a one length character element defining other parameters to passed on to vsearch.  
keep_temporary_files  
          (logical, default: FALSE) Do we keep temporary files ?  
          • temp.fasta (refseq in fasta or dna_seq sequences)  
          • cluster.fasta (centroid if method = "vsearch")  
          • temp.uc (clusters if method = "vsearch")
```

Details

This function use the [merge_taxa_vec\(\)](#) function to merge taxa into clusters. By default tax_adjust = 0. See the man page of [merge_taxa_vec\(\)](#).

This function is mainly a wrapper of the work of others. Please cite [vsearch](#).

Value

A new object of class physeq or a list of cluster if dna_seq args was used.

Author(s)

Adrien Taudière

References

VSEARCH can be downloaded from <https://github.com/torognes/vsearch>. More information in the associated publication <https://pubmed.ncbi.nlm.nih.gov/27781170>.

See Also

[asv2otu\(\)](#), [swarm_clustering\(\)](#)

Examples

```
summary_plot_pq(data_fungi)
d_vs <- vsearch_clustering(data_fungi)
summary_plot_pq(d_vs)
```

| | |
|------------------|--|
| vs_search_global | <i>Search for a list of sequence in a fasta file against physeq reference sequences using R href="https://github.com/torognes/vsearchvsearch</i> |
|------------------|--|

Description

[Maturing]

Usage

```
vs_search_global(  
  physeq,  
  seq2search = NULL,  
  path_to_fasta = NULL,  
  vsearchpath = "vsearch",  
  id = 0.8,  
  iddef = 0,  
  keep_temporary_files = FALSE  
)
```

Arguments

| | |
|----------------------|---|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| seq2search | (required if path_to_fasta is NULL) Either (i) a DNAStringSet object or (ii) a character vector that will be convert to DNAStringSet using Biostrings::DNAStringSet() |
| path_to_fasta | (required if seq2search is NULL) a path to fasta file if seq2search is est to NULL. |
| vsearchpath | (default: vsearch) path to vsearch |
| id | (default: 0.8) id for the option --usearch_global of the vsearch software |
| iddef | (default: 0) iddef for the option --usearch_global of the vsearch software |
| keep_temporary_files | (logical, default: FALSE) Do we keep temporary files <ul style="list-style-type: none">• temp.fasta (refseq in fasta)• cluster.fasta (centroid)• temp.uc (clusters) |

Details

This function is mainly a wrapper of the work of others. Please cite [vsearch](#).

Value

A dataframe with uc results (invisible)

Author(s)

Adrien Taudière

Examples

```

file_dna <- tempfile("dna.fa")
seqinr::write.fasta("GCCCATTAGTATTCTAGTGGCATGCCTGTCGAGCGTCATTTCAACC",
  file = file_dna, names = "seq1"
)

res <- vs_search_global(data_fungi, path_to_fasta = file_dna)
unlink(file_dna)

res[res$identity != "*", ]

clean_pq(subset_taxa(data_fungi, res$identity != "*"))

```

write_pq*Save phyloseq object in the form of multiple csv tables.***Description****[Maturing]****Usage**

```

write_pq(
  physeq,
  path = NULL,
  rdata = FALSE,
  one_file = FALSE,
  write_sam_data = TRUE,
  sam_data_first = FALSE,
  clean_pq = TRUE,
  reorder_asv = FALSE,
  rename_asv = FALSE,
  remove_empty_samples = TRUE,
  remove_empty_taxa = TRUE,
  clean_samples_names = TRUE,
  silent = FALSE,
  verbose = FALSE,
  quote = FALSE,
  sep_csv = "\t",
  ...
)

```

Arguments

| | |
|----------------------|--|
| physeq | (required): a phyloseq-class object obtained using the phyloseq package. |
| path | a path to the folder to save the phyloseq object |
| rdata | (logical) does the phyloseq object is also saved in Rdata format? |
| one_file | (logical) if TRUE, combine all data in one file only |
| write_sam_data | (logical) does the samples data are add to the file. Only used if one_file is TRUE. Note that these option result in a lot of NA values. |
| sam_data_first | (logical) if TRUE, put the sample data at the top of the table Only used if one_file and write_sam_data are both TRUE. |
| clean_pq | (logical) If set to TRUE, empty samples are discarded after subsetting ASV |
| reorder_asv | (logical) if TRUE the otu_table is ordered by the number of sequences of ASV (descending order). Default to TRUE. Only possible if clean_pq is set to TRUE. |
| rename_asv | reorder_asv (logical) if TRUE, ASV are renamed by their position in the OTU_table (asv_1, asv_2, ...). Default to FALSE. Only possible if clean_pq is set to TRUE. |
| remove_empty_samples | (logical) Do you want to remove samples without sequences (this is done after removing empty taxa) |
| remove_empty_taxa | (logical) Do you want to remove taxa without sequences (this is done before removing empty samples) |
| clean_samples_names | (logical) Do you want to clean samples names? |
| silent | (logical) If true, no message are printing. |
| verbose | (logical) Additional informations in the message the verbose parameter over-write the silent parameter. |
| quote | a logical value (default FALSE) or a numeric vector. If TRUE, any character or factor columns will be surrounded by double quotes. If a numeric vector, its elements are taken as the indices of columns to quote. In both cases, row and column names are quoted if they are written. If FALSE nothing is quoted. |
| sep_csv | (default tabulation) separator for column |
| ... | Other arguments passed on to utils::write.table() function. |

Value

Build a folder (path) containing one to four csv tables (refseq.csv, otu_table.csv, tax_table.csv, sam_data.csv) and if present a phy_tree in Newick format

Author(s)

Adrien Taudière

See Also

[save_pq\(\)](#)

Examples

```
write_pq(data_fungi, path = paste0(tempdir(), "/phyloseq"))
write_pq(data_fungi, path = paste0(tempdir(), "/phyloseq"), one_file = TRUE)
unlink(paste0(tempdir(), "/phyloseq"), recursive = TRUE)
```

Index

* datasets
 data_fungi, 37
 data_fungi_mini, 38
 data_fungi_sp_known, 39
 Tengeler2020_pq, 115

accu_plot, 5
accu_plot(), 7
accu_samp_threshold, 6
accu_samp_threshold(), 6
add_blast_info, 7
add_dna_to_phyloseq, 8
add_funguild_info, 9
add_funguild_info(), 84
add_info_to.sam_data, 10
add_new_taxonomy_pq, 11
adespatial::beta.div(), 63, 85, 86, 88
adonis_phyloseq
 (MiscMetabar-deprecated), 72
adonis_pq, 12, 73
all_object_size, 13
ANCOMBC::ancombc2(), 14
ancombc_pq, 14
are_modality_even_depth, 15
as_binary_otu_table, 18
asv2otu, 16
asv2otu(), 72, 80, 111, 128

base::load(), 100
base::rowsum(), 71, 72
Biostrings::DNAStringSet(), 28, 80, 129
biplot_physeq (MiscMetabar-deprecated),
 72
biplot_pq, 19, 73
biplot_pq(), 20, 56, 76
blast_pq, 21
blast_pq(), 7, 8, 24, 25
blast_to_derep, 22
blast_to_phyloseq, 24
blast_to_phyloseq(), 22, 24

build_phytree_pq, 26

calcNormFactors, 79
chimera_detection_vs, 28
chimera_detection_vs(), 29, 30
chimera_removal_vs, 29
chordDiagram, 31, 32
circle_pq, 30, 73
circos.par, 31, 32
clean_physeq (MiscMetabar-deprecated),
 72
clean_pq, 32, 73
clean_pq(), 29, 84, 104, 109, 116
compare_pairs_pq, 33, 73
ComplexUpset::upset(), 121
ComplexUpset::upset_test(), 124
count_seq, 34
cutadapt_remove_primers, 35

dada2::filterAndTrim(), 44
dada2::makeSequenceTable(), 29
data_fungi, 37
data_fungi_mini, 38
data_fungi_sp_known, 39
DECIPHER::Clusterize(), 16, 17
derep-class, 22
DESeq, 82
DESeq2::results(), 81
DGEList, 79
diff_fct_diff_class, 39
dist_bycol, 41
dist_pos_control, 42

edgeR, 79
edgeR::estimateTagwiseDisp(), 79
exactTest, 83

filter_asv_blast, 43
filter_trim, 44
funguild_assign, 45

funguild_assign(), 47
 funky_color, 46

 get_file_extension, 47
 get_funguild_db, 47
 get_funguild_db(), 46
 ggbetween_pq, 48
 ggplot, 6, 50, 51, 82, 83, 87, 96, 112, 121, 124, 125
 ggplot2::geom_label(), 20
 ggplot2::geom_text(), 20
 ggridges::geom_density_ridges(), 96
 ggstatsplot::ggbetweenstats(), 48
 ggVenn_phyloseq
 (MiscMetabar-deprecated), 72
 ggvenn_pq, 49, 73
 ggvenn_pq(), 122
 graph_test_pq, 51, 73
 gtsummary::tbl_summary(), 114

 heat_tree, 52
 heat_tree_pq, 52, 73
 hill_phyloseq (MiscMetabar-deprecated), 72
 hill_pq, 53, 73
 hill_pq(), 48
 hill_tuckey_phyloseq
 (MiscMetabar-deprecated), 72
 hill_tuckey_pq, 55, 73

 indicspecies::multipatt(), 73, 74
 iNEXT::iNEXT(), 56
 iNEXT_pq, 56
 is_cutadapt_installed, 57
 is_falco_installed, 58
 is_krona_installed, 59
 is_mumu_installed, 59
 is_swarm_installed, 60
 is_vsearch_installed, 61

 krona, 61, 69

 LCBD_pq, 63, 86, 88
 list_fastq_files, 64
 list_fastq_files(), 36
 lulu, 65
 lulu(), 67
 lulu_phyloseq (MiscMetabar-deprecated), 72

 lulu_pq, 67, 73

 merge_krona, 62, 68
 merge_krona(), 62
 merge_samples2, 69
 merge_samples2(), 12, 20, 34, 51, 56, 89
 merge_samples2, otu_table-method
 (merge_samples2), 69
 merge_samples2, phyloseq-method
 (merge_samples2), 69
 merge_samples2, sample_data-method
 (merge_samples2), 69
 merge_taxa_vec, 71
 merge_taxa_vec(), 17, 110, 111, 127, 128
 merge_taxa_vec, otu_table-method
 (merge_taxa_vec), 71
 merge_taxa_vec, phylo-method
 (merge_taxa_vec), 71
 merge_taxa_vec, phyloseq-method
 (merge_taxa_vec), 71
 merge_taxa_vec, taxonomyTable-method
 (merge_taxa_vec), 71
 merge_taxa_vec, XStringSet-method
 (merge_taxa_vec), 71
 MiscMetabar-deprecated, 72
 MiscMetabar-package, 4
 multcompLetters, 54
 multi_biplot_pq, 76
 multipatt_pq, 73
 multiplot, 74
 multitax_bar_pq, 75
 multitax_bar_pq(), 90, 112
 mumu_pq, 77

 otu_circle (MiscMetabar-deprecated), 72

 perc, 78
 phangorn::bootstrap.pml(), 27
 phangorn::optim.pml(), 26, 27
 phyloseq-class, 5, 18, 21, 24, 30, 49, 99, 109, 113, 125
 phyloseq::distance(), 12
 phyloseq::distanceMethodList(), 12
 phyloseq::merge_taxa(), 72
 phyloseq::mt(), 87
 phyloseq::rarefy_even_depth(), 48
 phyloseq::subset_samples(), 106
 phyloseq::subset_taxa(), 106
 phyloseq_to_edgeR, 79

phyloseqGraphTest::graph_perm_test(),
 51
physeq_graph_test
 (MiscMetabar-deprecated), 72
physeq_heat_tree
 (MiscMetabar-deprecated), 72
physeq_or_string_to_dna, 80
plot, 6
plot_deseq2_phyloseq
 (MiscMetabar-deprecated), 72
plot_deseq2_pq, 73, 81, 83
plot_edgeR_phyloseq
 (MiscMetabar-deprecated), 72
plot_edgeR_pq, 73, 82, 83
plot_guild_pq, 84
plot_guild_pq(), 9
plot_LCBD_pq, 63, 85
plot_mt, 87
plot_SCBD_pq, 88
plot_tax_pq, 89
plot_tax_pq(), 112
plot_tsne_pq, 91
plotly::ggplotly(), 20
purrr::as_mapper(), 70

read_phyloseq (MiscMetabar-deprecated),
 72
read_pq, 73, 92
rename_samples, 93
rename_samples(), 98
rename_samples_otu_table, 94
reorder_taxa_pq, 95
results, 81–83
ridges_pq, 96
rotl_pq, 97

sample_data_with_new_names, 98
sankey_phyloseq
 (MiscMetabar-deprecated), 72
sankey_pq, 73, 99
sankeyNetwork, 99, 100
save_pq, 100
save_pq(), 131
search_exact_seq_pq, 101
select_one_sample, 102
select_taxa, 102
select_taxa, otu_table, character-method
 (select_taxa), 102
select_taxa, phylo, character-method
 (select_taxa), 102
select_taxa, phyloseq, character-method
 (select_taxa), 102
select_taxa, sample_data, character-method
 (select_taxa), 102
select_taxa, taxonomyTable, character-method
 (select_taxa), 102
select_taxa, XStringSet, character-method
 (select_taxa), 102
simplify_taxo, 103
specaccum, 6
SRS_curve_pq, 104
subsample_fastq, 105
subset_samples_pq, 106
subset_taxa_pq, 106
subset_taxa_pq(), 10
subset_taxa_tax_control, 108
summary_plot_phyloseq
 (MiscMetabar-deprecated), 72
summary_plot_pq, 73, 109
swarm_clustering, 110
swarm_clustering(), 18, 80, 128

tax_bar_pq, 112
tax_bar_pq(), 90
tax_datatable, 113
tbl_sum_samdata, 114
Tengeler2020_pq, 115
tibble::tibble, 46, 47
track_wkflow, 116
track_wkflow(), 117
track_wkflow_samples, 117
track_wkflow_samples(), 102, 116
treemap_pq, 118
treemapify::geom_treemap(), 118
tsne_pq, 119

unique_or_na, 120
upset_pq, 121
upset_pq(), 50, 125
upset_test_pq, 124
utils::read.delim(), 98
utils::write.table(), 92, 100, 131

vegan::adonis2(), 12, 13
vegan::vegdist(), 12, 42
vegdist, 42

venn_phyloseq (MiscMetabar-deprecated),
 72
venn_pq, 73, 125
venneuler, 125
verify_pq, 126
vs_search_global, 129
vsearch_clustering, 127
vsearch_clustering(), 18, 80, 111

write_phyloseq
 (MiscMetabar-deprecated), 72
write_phyloseq(), 92
write_pq, 73, 130
write_pq(), 100, 101