

Package ‘cdlsim’

April 20, 2026

Title Simulation of Cropland Data Layer Products from the USDA

Version 0.1.0

Description Provides tools to simulate categorical raster data, including objects from the 'terra' package. Functions focus on generating edge pixel values from reclassified raster data derived from the United States Department of Agriculture (USDA) Cropland Data Layer products.

License MIT + file LICENSE

Depends R (>= 4.1.0)

Encoding UTF-8

RoxygenNote 7.3.3

Imports dplyr, terra, landscapemetrics, readxl, utils, Rcpp

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

LinkingTo Rcpp

VignetteBuilder knitr

NeedsCompilation yes

Author Haley Burger [aut, cre, cph]

Maintainer Haley Burger <A02425259@usu.edu>

Repository CRAN

Date/Publication 2026-04-20 13:00:21 UTC

Contents

collapse_and_combined	2
download_cdl_mat_files	2
find_patches	3
generate_transition_vectors	3
get_mat_data	4
get_mat_data_dep	4
get_trans_mat	5

get_trans_mat_dep	6
modify_matrix	7
simulate_raster_patch	7

Index 9

collapse_and_combined *Function to resize patches in a SpatRaster using the terra and landscapemetrics packages*

Description

Function to resize patches in a SpatRaster using the terra and landscapemetrics packages

Usage

```
collapse_and_combined(patch_raster, og_raster)
```

Arguments

patch_raster The SpatRaster object representing the categorical data.
 og_raster The values of the classes of interest, default is "all".

Value

A SpatRaster where each patch is defined as a unique value and each class has its own layer in the spatraster.

download_cdl_mat_files
Function to Read in and unzip confusion matrix files from the web

Description

Function to Read in and unzip confusion matrix files from the web

Usage

```
download_cdl_mat_files(years, temp_dir = "extracted_files")
```

Arguments

years The years of data that you want to be downloaded.
 temp_dir The file name you want the extracted files to be stored in.

Value

The raw excel books containing the confusion matrix data for every US state's USDA Crop Land Data Layer.

find_patches	<i>Function to resize patches in a SpatRaster using the terra and landscapemetrics packages</i>
--------------	---

Description

Function to resize patches in a SpatRaster using the terra and landscapemetrics packages

Usage

```
find_patches(raster)
```

Arguments

raster The SpatRaster object representing the categorical data.

Value

A SpatRaster where each patch is defined as a unique value and each class has its own layer in the spatraster.

generate_transition_vectors	<i>Function to generate transition vectors for negative cell values</i>
-----------------------------	---

Description

Function to generate transition vectors for negative cell values

Usage

```
generate_transition_vectors(r, transition_matrix, iterations = 10)
```

Arguments

r The SpatRaster object from get_patches with one layer for each class.

transition_matrix The transition matrix you want to use.

iterations The number of iterations desired.

Value

A matrix of vector for each patch in each layer.

get_mat_data	<i>Function to retrieve confusion matrix data for multiple states of interest</i>
--------------	---

Description

Function to retrieve confusion matrix data for multiple states of interest

Usage

```
get_mat_data(  
  state_abbreviation,  
  file_path = "inst/extdata/extracted_files",  
  verbose = FALSE  
)
```

Arguments

state_abbreviation	A vector of two-letter abbreviations for US states.
file_path	The path to the directory where files are stored (default is "inst/extdata/extracted_files").
verbose	The stops the messages from printing to the console.

Value

A named list where each element is a list of data frames representing confusion matrices for each state.

Examples

```
# example code  
# Get data from UT in 2008  
ut_mat_data <- get_mat_data(c("UT"))
```

get_mat_data_dep	<i>Function to retrieve confusion matrix data for multiple states of interest</i>
------------------	---

Description

Function to retrieve confusion matrix data for multiple states of interest

Usage

```

get_mat_data_dep(
  state_abbreviation,
  file_path = "inst/extdata/extracted_files",
  verbose = FALSE
)

```

Arguments

state_abbreviation A vector of two-letter abbreviations for US states.

file_path The path to the directory where files are stored (default is "inst/extdata/extracted_files").

verbose The stops the messages from printing to the console.

Value

A named list where each element is a list of data frames representing confusion matrices for each state.

get_trans_mat *Function to format the confusion matrices as transition matrices*

Description

Function to format the confusion matrices as transition matrices

Usage

```
get_trans_mat(df_list, categories)
```

Arguments

df_list A single data frame or a list of lists of data frames extracted using get_mat_data(). If a list, each sublist should contain two or more data frames to be summed.

categories A list of categories defining the numbers between 1 and 256.

Value

A list of data frames where row names represent pixels that will transition and column names represent the class they will transition to.

Examples

```

# make the data frame
bl_mat_data <- get_mat_data(c("UT"))

# List of categories with their corresponding vectors
# Define the values that represent our classes of interest
non_ag <- c(61:65, 81:83, 87:88, 92, 111:112, 121:124, 131, 141:143, 152, 176, 181, 190, 195)
alfalfa <- c(36:37)
major_ag <- c(1, 2, 5, 12, 13, 22:24, 26, 225:226, 228, 234, 236, 238:241, 254)
all_numbers <- 1:256
ag <- setdiff(all_numbers, c(non_ag, alfalfa, major_ag))

cat_5 <- list(non_ag = non_ag, ag = ag, alfalfa = alfalfa, major_ag = major_ag)

# get the confusion matrix for just 2008
trans_mat_5 <- get_trans_mat(bl_mat_data, cat_5)

```

get_trans_mat_dep *Function to format the confusion matrices as transition matrices*

Description

Function to format the confusion matrices as transition matrices

Usage

```
get_trans_mat_dep(df_list, categories)
```

Arguments

df_list A list of lists of data frames extracted using `get_mat_data()`. Each sublist should contain two or more data frames to be summed.

categories A list of categories defining the numbers between 1 and 256.

Value

A list of data frames where row names represent pixels that will transition and column names represent the class they will transition to.

modify_matrix	<i>Function to modify transition matrix based on user input.</i>
---------------	--

Description

Function to modify transition matrix based on user input.

Usage

```
modify_matrix(mat, indices = 0)
```

Arguments

mat	The transition matrix the you want to update.
indices	The vector of classes you want to remain unsimulated.

Value

A transition matrix modified to not transition some classes.

simulate_raster_patch	<i>Function to simulate tagged patch values in a single layer spatraster.</i>
-----------------------	---

Description

Function to simulate tagged patch values in a single layer spatraster.

Usage

```
simulate_raster_patch(  
  original_raster,  
  transition_matrix,  
  non_trans = 0,  
  iterations = 10  
)
```

Arguments

original_raster	The SpatRaster object representing the categorical data.
transition_matrix	Transition matrix values that define transitions based on class values.
non_trans	Class(es) that the user would like to remain unsimulated. Default is class 0 since this is the background class.
iterations	The number of simulations to be performed.

Value

A `SpatRaster` where the patches values have been simulated.

Examples

```
library(terra)

r <- rast(nrows = 20, ncols = 20)
values(r) <- rep(1:3, length.out = ncell(r))

trans_mat <- matrix(1/3, 3, 3)
rownames(trans_mat) <- colnames(trans_mat) <- c("1", "2", "3")

simulate_raster_patch(r, trans_mat, iterations = 1)
```


Index

`collapse_and_combined`, 2

`download_cdl_mat_files`, 2

`find_patches`, 3

`generate_transition_vectors`, 3

`get_mat_data`, 4

`get_mat_data_dep`, 4

`get_trans_mat`, 5

`get_trans_mat_dep`, 6

`modify_matrix`, 7

`simulate_raster_patch`, 7