

The draftwatermark package^{*}

Sergio Callegari[†]

2020/06/29

Abstract

The draftwatermark package extends L^AT_EX providing a means to add a watermark (typically textual and light gray, but possibly more sophisticated) on the pages of a document (either on every page, on the first page, or on selected pages). Typical usage may consist in writing words such as “DRAFT” or “CONFIDENTIAL” across the pages. The package may remind in some sense draftcopy by Dr. Juergen Vollmer, but its implementation is lighter (as the reduced code footprint shows) and does not rely on postscript specials, making the package fully compatible with pdfl^AT_EX, X^AT_EX and L^Au^AT_EX. The draftwatermark package depends on *everypage* by the same author. Its feature set is somehow restricted because the emphasis is on the simplicity of the interface. For complex layouts, *scrlayer.sty* from the *KOMA script* bundle may represent a valuable alternative.

1 Introduction

This package extends L^AT_EX providing a means to add a textual, usually light gray (but possibly colored) watermark on every page, the first page, or selected pages of a document. Typical usage may consist in writing words such as “DRAFT” or “CONFIDENTIAL” across document pages.

The package may remind in some sense draftcopy by Dr. Juergen Vollmer, but its implementation differs in a few points:

1. Code footprint is smaller, although this does not mean much on modern computers.
2. There is no use of Postscript specials or other driver-dependent tricks, so the package should be compatible with any output driver and with pdfl^AT_EX, X^AT_EX, and L^Au^AT_EX in particular. Recently, compatibility with PDF generating engines is quite important and its lack in draftcopy and was the first motivation for writing draftwatermark.
3. Reduced code footprint comes at some price. Many features of draftcopy are not supported here, most notably draftwatermark has:
 - No automatic selection of the watermark text to use, based on the language, relying on pre-stored translations of the word “DRAFT”. This may be no big loss, since one is free to choose whatever text he/she happens to prefer.

^{*}This file (*draftwatermark.dtx*) has version number 2.2, last revised 2020/06/29.

[†]Sergio Callegari can be reached at sergio.callegari@gmail.com

- No automatic possibility to watermark only the first *two* pages of a document. However, it is possible to automatically watermark only the first or to *manually* stop the watermarking after the second page.

Note that some features available as options in `draftcopy` (e.g., the possibility of time-stamping the watermark text) can be obtained working on the watermark text itself.

The emphasis of `draftwatermark` is on the simplicity of its interface. In many cases the package will do the right thing by just loading it, without any further configuration. Such simplicity pairs with some limitations. As an example, `draftwatermark` is capable of putting some text or an image on the background of the page, below the document text, but not of *stamping*, that is putting it in the foreground, above the document text. Similarly, it is not well suited for complex watermark layouts. As a further note, there may be unexpected behaviors when `draftwatermark` is used together with other packages affecting the page building, e.g., with respect to the stacking order of the objects on the page. For any complex layout, or when the Z-ordering is important, the recommendation is to look at the `scrlayer` package in the *KOMA script* bundle.

For the actual page building `draftwatermark` depends on the `everypage` package by the same author.

2 User interface

When loaded, `draftwatermark` sets up a number of defaults (detailed later and modifiable by specific commands) and immediately becomes active.

2.1 Package options and configuration

If loaded as

```
\usepackage{draftwatermark}
```

the package sets up itself to put the a large, grayed background text saying “DRAFT” at the center every page.

This behavior can be modified by passing options to the package as in

```
\usepackage[<options>]{draftwatermark}
```

`\DraftwatermarkOptions`

The package behavior can also be dynamically changed *after the package is loaded* by the command `\DraftwatermarkOptions{<options>}` that can be used anywhere in the document source. In either case, `<options>` is a comma separated list of options, each given as a `<key>` or as a `<key>=<value>` pair. Unless otherwise indicated, all options that can be used at the loading of the package can also be given via the `\DraftwatermarkOptions{<options>}` mechanism. In fact, the two things are almost equivalent, with some cautionary details. Specifically, the parsing of options by the `\usepackage` command is a bit quirky, hence when specifying options with the `<key>=<value>` syntax, some values that are accepted by `\DraftwatermarkOptions` may cause issues when specifying options with `\usepackage`.

The available options are:

- **firstpageonly=true|false**
 If no value is provided, `true` is assumed. Default is `false`.
 Instructs `draftwatermark` to only apply the watermark on the first page.
 This option cannot be used with `\DraftwatermarkOptions{<options>}`.
- **firstpage** legacy alias of `firstpageonly`.
- **stamp=true|false**
 If no value is provided, `true` is assumed. Default is `true`.
 Instructs `draftwatermark` to print the watermark.
- **nostamp** legacy alias of `stamp=false`.
- **final** legacy alias of `stamp=false`.
- **angle=<real>**
 Default is 45.
 Defines the angle, in degrees, at which the watermark text should be printed.
- **scale=<real>**
 Default is 1.
 Defines the scale at which the watermark text should be printed.
- **fontsize=<length>**
 Default is $0.25\paperwidth$.
 Defines the font size for the watermark text. See Section 3.2.
- **text=<token list>**
 Default is `DRAFT`. Defines the watermark text. See notes in Section 3.3.
- **hpos=<length>**
 Default is $0.5\paperwidth$.
 Defines the horizontal position of the watermark, based on its anchor point. See also the `pos` option.
- **vpos=<length>**
 Default is $0.5\paperheight$.
 Defines the horizontal position of the watermark, based on its anchor point. See also the `pos` option.
- **pos={<length>, <length>}**
 Defines at once the horizontal (first length) and vertical (second length) position of the watermark, based on its anchor point. See also the options `hpos` and `vpos`.
- **hanchor=l|c|r**
 Default is `c`.
 Defines the horizontal position of the watermark anchor point. Specifically, `l` stands for *left*, `c` for *center* and `r` for *right*. See also the `anchor` option.
- **vanchor=t|m|b**
 Default is `m`.
 Defines the vertical position of the watermark anchor point. Specifically, `t` stands for *top*, `m` for *middle* and `b` for *bottom*. See also the `anchor` option.

- **anchor=<string>**
Defines the anchor point for the watermark. The anchor point is placed at the page coordinates specified by the `hpos` and `vpos` options. The string used for the specification is made of the `l`, `c`, `r`, `t`, `m`, and `b` characters, whose meaning is as described for the `hanchor` and `vanchor` options. For instance, if the anchor specification is `lt`, then the top left corner of the watermark is placed at the position specified by the `hpos` and `vpos` options.
- **alignment=l|c|r**
Default is `c`.
Defines the alignment for the watermark text in case it contains line breaks. Specifically, `l` aligns left, `c` aligns at the center and `r` aligns right.
- **colormodel=<color model>**
Defaults to `gray`.
Defines the color model for the specification of the color of the watermark text. Can be any color model supported by the `color` package. Leaving it empty allows named colors to be specified. See also the `color` option.
- **colorspec=<color specification>**
Defaults to `\color{gray}{0.8}`.
Defines a color specification for the watermark text. The specification is interpreted according to the color model. For instance if the model is `rgb`, then the specification can be a color triple. See also the `color` option.
- **color=<full color specification>**
Defines the color of the watermark text. The color specification may include an optional color model and must include a color specification, following the standard set by the `color` package. For instance, some examples of valid specifications are `red`, or `\color[rgb]{1, 0, 1}`, or `\color[gray]{0.5}`.
- **markcmd=<macro>**
Default is `\DraftwatermarkStdMark`.
Defines the command used to draw the actual watermark. See also Sect. 4.

3 Some notes on the configuration options

3.1 The `stamp` option and its companion configuration directives

The `stamp`, `nostamp` and `final` options let one control whether the watermark should actually be printed or not. They can be handy for quickly removing the “draft” status from a document, without having to alter the actual watermark setup. Option `final` is a synonym for `nostamp`. Note that `final` is a commonly used global (class-level) option that can be simultaneously obeyed by multiple packages. The option `stamp` can be used to override a global `final` option and to recover the watermarking.

Via the `\DraftwatermarkOptions` command, the `stamp` option can be given at arbitrary points in the document to suspend or resume watermarking. In this way one can *manually* apply the watermark only on selected pages of a document.

3.2 The watermark text size

The package lets one control the watermark size in two different ways. One is by picking a font size via the `fontsize` option; the other one is by scaling the watermark with the `scale` option.

In principle, using a large font to produce a large textual watermark is the preferred choice. In fact, a font with a large point size is not just a scaled up version of the same font with a small point size. Conversely, it is a font where all the traits are adjusted to actually look well at a large size. This is why `draftwatermark` defaults to setting `scale=1` and to a large point size for the font (in fact, sufficiently large to get the word “DRAFT”, rotated at 45°, take about half of the page width).

Nonetheless asking for a large font may not work, if \LaTeX has not been set up to use *scalable* fonts. For this reason, the recommendation is to always use `draftwatermark` on \LaTeX or `pdfl\text{\LaTeX}` together with other packages that trigger the usage of fully scalable fonts (practical examples may be `newtx` or `mathptmx`, etc.). An even better alternative is to use modern \TeX engines, as in `X\text{\TeX}` or `Lua\text{\TeX}` with `fontspec`. In any case, recall that even with scalable fonts, \LaTeX may be unable to deal with extremely large font sizes (e.g., $\gg 5 \text{ cm}$). If really large letters are required for the watermark, a suitable combination of `fontsize` and `scale` may be needed.

One can immediately realize when \LaTeX is unable to deal with the package default or selected `fontsize` from two things: (i) a font warning from \LaTeX ; and (ii) a tiny watermark text whose size seems not to react to the `fontsize` option. In this case, either switch to scalable fonts or select a small `fontsize` (e.g., `12pt`) together with a `scale` significantly larger than 1.

3.3 The watermark text

As previously noticed, the watermark text can be specified with the `text` option. The value passed to the `text` option does not need to be a plain string. Conversely, it may include formatting marks, such as line break commands (e.g., `\backslash`) or commands to select font variants (e.g., `\bfseries`). In fact, it is also possible to use a command to include an image as the text. In case line breaks are present, the text is left, right, center aligned according to the `alignment` option. A word of caution is necessary, though. To use \LaTeX commands in the watermark text, please configure the latter via the `\DraftwatermarkOptions` command. Trying to do so by passing options to the `draftwatermark` package via the `\usepackage` mechanism may fail due to how \LaTeX parses option strings. Also note that the text may need to be surrounded by braces.

If the watermark text includes line breaks, `draftwatermark` will use a very thin interline space, according to the fact that the multi-line text is managed by surrounding the it with a \LaTeX `shortstack` command.

Also, note that the watermark typesetting happens inside a \TeX group, to make sure that any parameter setting you do in the `text` token list can stay local.

As a further remark, observe that in order to only put a watermark on selected pages, an alternative to changing the `stamp` configuration option at arbitrary points in the document can be to use conditional expressions in the watermark text itself.

3.4 The watermark positioning

The watermark position is controlled via the `hpos` and `vpos` configuration options (or alternatively, by the `pos` configuration option). It is worth underlining that these configuration

parameters require *lengths* not plain numbers.

The coordinates used by the positioning parameters are measured from the top left corner of the page. They work in conjunction with the anchoring parameters (`hanchor`, `vanchor` and `anchor`). Specifically, the anchor point of the watermark is placed at the specified position. The default is to center the watermark on the page, but it is possible to choose other positions by a smart choice of the positioning and anchoring parameters. For instance, one may want to put the watermark on the top right corner of each page, which can be easily done with an `rt` anchoring.

As a final remark, observe that the specification of the positioning coordinates can be based on L^AT_EX macros. For instance, one can set the horizontal position `hpos` at `0.5\paperwidth` (for centering) or at `\dimexpr\paperwidth-5mm` (for placement at the right hand side of the page). Interestingly, `draftwatermark` re-evaluates the positioning coordinates on every page. This means that positions based on `\paperwidth` or `\paperheight` should dynamically adjust if the page size is changed through the document. To some extent, this is also true of the anchor options. For instance, one may set the horizontal anchor `hanchor` at `\ifodd\thepage r\else l\fi` causing the anchor point to alternate between `r` and `l` at every new page. In conjunction with a similarly conditional `hpos` setting, for instance `\ifodd\thepage \dimexpr\paperwidth-5mm\else 5mm\fi`, this enables interesting effects, like placing the watermark close to the right side of the page on odd pages and to the left side of the page on even pages. Obviously, this kind of setting is only applicable with the `hanchor` and `vanchor` options, and not with the `anchor` shorthand.

4 The standard watermark and ways of overriding it

In order to simplify its usage as much as possible, the `draftwatermark` package is designed under the assumption that, most of the time, the user will need just a *textual* watermark and some basic way to tune its visual aspect, such as choosing the text font, font size, scale, rotation angle, etc.

To this aim, the macro `\DraftwatermarkStdMark` is provided to do the standard job of typesetting the watermark text according to the configuration-defined font, color, angle, and so on. Then the package arranges so that this macro is called whenever watermarking is needed.

In case the facilities provided by `\DraftwatermarkStdMark` are insufficient, the package user can set up his/her own macro to do the watermark typesetting and instruct `draftwatermark` to use it in place of `\DraftwatermarkStdMark`. This is done by using the configuration option `markcmd` that takes the new macro name as its parameter. The advice is to always write a new macro rather than redefining or patching `\DraftwatermarkStdMark`. Note that because `markcmd` can be reconfigured multiple times, one may actually define multiple macros to get different watermark layouts on different pages of the same document.

It is worth recalling that when `markcmd` is set to something different from `\DraftwatermarkStdMark`, the angle, font, scale, color parameters will be ignored. In this case, the package user is on his/her own if he/she wants to parametrize the watermark appearance.

5 Compatibility notes for package version 2.0 and later

Version 2.0 of the package is an almost complete rewrite with respect to version 1.2. Specifically, all the configuration mechanism has been overhauled, by moving to an interface based on configuration keys and associated values.

In principle, compatibility to the 1.x series should be fully preserved by the provision of a *legacy interface*. In case old documents are broken by the 2.x series, please report it as a bug.

The advice is not to use the legacy interface in new documents, unless you know that they will need to be processed in environments lacking a recent draftwatermark.

5.1 The legacy interface

The legacy interface is composed by the following commands:

- Command `\SetWatermarkAngle{<real>}` is the same as `\DraftwatermarkOptions{angle=<real>}`.
- Command `\SetWatermarkColor[<model>]{<color spec>}` is the same as `\DraftwatermarkOptions{color={[<model>]{<color spec>}}}`.
- Command `\SetWatermarkLightness{<real>}` is the same as `\DraftwatermarkOptions{color={[<gray>]{<real>}}}`. The real value should be in between 0 (for black) and 1 (for white).
- Command `\SetWatermarkFontSize{<length>}` is the same as `\DraftwatermarkOptions{fontsize=<length>}`.
- Command `\SetWatermarkScale{<real>}` is the same as `\DraftwatermarkOptions{scale=<real>}`.
- Command `\SetWatermarkHorCenter{<length>}` is the same as `\DraftwatermarkOptions{hpos=<length>, hanchor=c}`.
- Command `\SetWatermarkVerCenter{<length>}` is the same as `\DraftwatermarkOptions{vpos=<length>, vanchor=m}`.
- Command `\SetWatermarkText{<text>}` is the same as `\DraftwatermarkOptions{text=<text>}`.

Note that the legacy interface supports only a subset of what is possible with the modern interface.

6 Examples

6.1 Plain case, using the modern package interface

As an example, consider this first document source:

```
1 \documentclass{article}
2 \usepackage[named]{xcolor}
3 \usepackage[T1]{fontenc}
4 \usepackage[firstpageonly, color={[gray]{0.5}}, 
5   text=DRAFT\|COPY]{draftwatermark}
```

```

6 \usepackage{mathptmx}
7 \usepackage{lipsum}
8 \title{Sample document for the draftwatermark package}
9 \author{}
10
11 \begin{document}
12 \maketitle
13
14 \section{One}
15 \lipsum[1-3]
16
17 \section{Two}
18 \lipsum[4-6]
19
20 \end{document}

```

This produces a two pages document with placeholder content, putting a page-centered watermark on the first page only. The watermark is made a slightly darker tone of gray than the default.

6.2 Plain case, using the legacy interface

Using the legacy interface, the source for the same sample document as above would look like:

```

1 \documentclass{article}
2 \usepackage[named]{xcolor}
3 \usepackage[T1]{fontenc}
4 \usepackage[firstpage]{draftwatermark}
5 \usepackage{mathptmx}
6 \usepackage{lipsum}
7
8 \SetWatermarkLightness{0.5}
9 \SetWatermarkText{DRAFT\textbackslash\textbackslash COPY}
10
11 \title{Sample document for the draftwatermark package}
12 \author{}
13
14 \begin{document}
15 \maketitle
16
17 \section{One}
18 \lipsum[1-3]
19
20 \section{Two}
21 \lipsum[4-6]
22
23 \end{document}

```

6.3 Things that cannot be done with the legacy interface

A major limitation of the legacy interface that has been removed with the modern interface is the inability to control the watermark anchoring. For instance, one may want the

watermark to appear in the right top angle of every page. With the modern interface, such a result can be easily obtained as in the following sample code:

```

1 \documentclass{article}
2 \usepackage[named]{xcolor}
3 \usepackage[T1]{fontenc}
4 \usepackage[firstpage, anchor=tr, color=red,
5   pos={\dimexpr\paperwidth-5mm, 5mm},
6   angle=-45, fontsize=32pt]{draftwatermark}
7 \usepackage{mathptmx}
8 \usepackage{lipsum}
9 \title{Sample document for the draftwatermark package}
10 \author{}
11
12 \DraftwatermarkOptions{text=\bfseries DRAFT}
13 \begin{document}
14 \maketitle
15
16 \section{One}
17 \lipsum[1-3]
18
19 \section{Two}
20 \lipsum[4-6]
21
22 \end{document}

```

Another interesting possibility of the modern interface derives from the fact that the positioning and anchoring options are re-evaluated for every page. This allows the positioning to dynamically change following other parameters (for instance the `\paperwidth`) or to take advantage of conditionals to achieve effects such as differentiating the watermark for odd and even pages, as shown in the following code:

```

1 \documentclass{article}
2 \usepackage[named]{xcolor}
3 \usepackage[T1]{fontenc}
4 \usepackage[color=red, fontsize=32pt]{draftwatermark}
5 \usepackage{mathptmx}
6 \usepackage{lipsum}
7 \title{Sample document for the draftwatermark package}
8 \author{}
9
10 \DraftwatermarkOptions{%
11   angle=0,
12   text={\ifodd\thepage ODD\else EVEN\fi},
13   hpos={\ifodd\thepage \dimexpr\paperwidth-5mm\else 5mm\fi},
14   vpos=5mm,
15   vanchor=t,
16   hanchor={\ifodd\thepage r\else l\fi}
17 }
18
19 \begin{document}
20 \maketitle
21
22 \section{One}
23 \lipsum[1-3]
24

```

```

25 \section{Two}
26 \lipsum[4-6]
27
28 \end{document}

```

6.4 Maximum freedom with a custom watermarking command

Maximum freedom can be obtained with a custom watermarking command. The following example shows how it can be used, once again differentiating the watermark for odd and even pages.

```

1 \documentclass{article}
2 \usepackage[named]{xcolor}
3 \usepackage[T1]{fontenc}
4 \usepackage{draftwatermark}
5 \usepackage{mathptmx}
6 \usepackage[scaled]{helvet}
7 \usepackage{lipsum}
8 \title{Sample document for the draftwatermark package}
9 \author{}
10
11 \newsavebox\wmbox
12 \savebox\wmbox{%
13   \color[rgb]{1,0.8,0.8}\sffamily \fbox{DRAFT}}
14 \newcommand\MyWM{%
15   \ifodd\thepage
16     \hspace*{\dimexpr \paperwidth -\wd\wmbox-10mm}%
17     \usebox{\wmbox}%
18   \else
19     \usebox{\wmbox}%
20   \fi}
21
22 \DraftwatermarkOptions{anchor=lt, pos={5mm, 5mm}, markcmd=\MyWM}
23 \begin{document}
24 \maketitle
25
26 \section{One}
27 \lipsum[1-3]
28
29 \section{Two}
30 \lipsum[4-6]
31
32 \end{document}

```

7 Development and support

The package is developed on *github*:

<https://github.com/callegar/LaTeX-draftwatermark>

Please, refer to that site for any bug report or development information. Be so kind to refrain from opening bugs for enhancement requests that, from the present document, would evidently require moving against some fundamental design decisions.

8 Changelog

- 1.0 - 2006/06/30** Initial version.
- 1.1 - 2012/01/06** Add support for colored watermarks; options to disable watermarking; many small fixes in the documentation.
- 1.2 - 2015/02/19** Add support for watermark position.
- 2.0 - 2020/03/08** Configuration management overhaul; introduction of a legacy interface for compatibility.
- 2.1 - 2020/05/11** Allow anchor information to be re-evaluated on every page.
- 2.2 - 2020/06/29** Make line breaks in watermark text work.

9 Implementation

Announce the name and version of the package, which requires L^AT_EX 2 _{ε} .

```
1 \NeedsTeXFormat{LaTeX2e}
2 \ProvidesPackage{draftwatermark}%
3   [2020/06/29 2.2 Put a gray textual watermark on document pages]
4
```

Require the needed packages.

```
5 \RequirePackage{kvoptions}
6 \RequirePackage{everypage}[2007/06/20]
7 \RequirePackage{graphicx}
8 \RequirePackage{color}
9
```

Define the configuration options and default values.

```
10 \DeclareBoolOption[false]{firstpageonly}
11 \define@key{draftwatermark}{firstpage}{true}{%
12   \csname draftwatermark@firstpageonly#1\endcsname}
13 \DeclareBoolOption[true]{stamp}
14 \DeclareComplementaryOption{nostamp}{stamp}
15 \DeclareComplementaryOption{final}{stamp}
16 \DeclareStringOption[45]{angle}
17 \DeclareStringOption[1]{scale}
18 \DeclareStringOption[DRAFT]{text}
19 \DeclareStringOption[0.5\paperwidth]{hpos}
20 \DeclareStringOption[0.5\paperheight]{vpos}
21 \DeclareStringOption[0.25\paperwidth]{fontsize}
22 \DeclareStringOption[gray]{colormodel}
23 \DeclareStringOption[0.8]{colorspec}
24 \DeclareStringOption[c]{hanchor}
25 \DeclareStringOption[m]{vanchor}
26 \DeclareStringOption[c]{alignment}
27 \DeclareStringOption[\DraftwatermarkStdMark]{markcmd}
28 \define@key{draftwatermark}{pos}{%
29   \draftwatermark@processpos #1\@nil}
30 \define@key{draftwatermark}{anchor}{%
31   \draftwatermark@processanchor{\#1}}}
```

```

32 \define@key{draftwatermark}{color}{%
33   \draftwatermark@processcolor #1\@nil}
34

Set up some helper macros to process the options. These should be rather self-
explanatory.

35 \def\draftwatermark@processpos#1,#2\@nil{%
36   \def\draftwatermark@hpos{\#1}%
37   \def\draftwatermark@vpos{\#2}%
38
39 \def\draftwatermark@processanchor#1{%
40   \def\draftwatermark@tempa{\#1}%
41   \onelevel@sanitize \draftwatermark@tempa
42   \expandafter \atfor \expandafter \draftwatermark@tempb
43     \expandafter :\expandafter =\draftwatermark@tempa
44   \do
45   {%
46     \if \draftwatermark@tempb 1%
47       \def \draftwatermark@hanchor{l}%
48     \else \if \draftwatermark@tempb c%
49       \def \draftwatermark@hanchor{c}%
50     \else \if \draftwatermark@tempb r%
51       \def \draftwatermark@hanchor{r}%
52     \else \if \draftwatermark@tempb t%
53       \def \draftwatermark@vanchor{t}%
54     \else \if \draftwatermark@tempb m%
55       \def \draftwatermark@vanchor{m}%
56     \else \if \draftwatermark@tempb b%
57       \def \draftwatermark@vanchor{b}%
58     \else
59       \PackageError{draftwatermark}{%
60         Illegal anchor directive ‘\draftwatermark@tempb’}%
61         {Directive has been ignored.}%
62     \fi\fi\fi\fi\fi
63   }%
64
65 \def\draftwatermark@processcolor{%
66   \ifnextchar[
67     \draftwatermark@processcolor@ii\draftwatermark@processcolor@i}%
68
69 \def\draftwatermark@processcolor@i#1\@nil{%
70   \def\draftwatermark@colormodel{}%
71   \def\draftwatermark@colorspec{\#1}%
72
73 \def\draftwatermark@processcolor@ii[#1]\#2\@nil{%
74   \def\draftwatermark@colormodel{\#1}%
75   \def\draftwatermark@colorspec{\#2}}%
76

Process the package options...
77 \ProcessKeyvalOptions*
    ... and then disable the firstpageonly and firstpage options, that can only be
used at the package loading time.
78 \DisableKeyvalOption{draftwatermark}{firstpageonly}

```

```

79 \DisableKeyvalOption{draftwatermark}{firstpage}
80

\DraftwatermarkOptions Set up a command to modify the configuration as needed.
81 \newcommand{\DraftwatermarkOptions}[1]{\setkeys{draftwatermark}{#1}}
82

    Introduce the legacy interface.

\SetWatermarkAngle Legacy command to set the rotation angle for the standard watermark
83 \newcommand{\SetWatermarkAngle}[1]{\DraftwatermarkOptions{angle=#1}}

\SetWatermarkFontSize Legacy command to set the font size for the standard watermark
84 \newcommand{\SetWatermarkFontSize}[1]{\DraftwatermarkOptions{fontsize=#1}}

\SetWatermarkScale Legacy command to set the scale for the standard watermark
85 \newcommand{\SetWatermarkScale}[1]{\DraftwatermarkOptions{scale=#1}}

\SetWatermarkHorCenter Legacy commands to set the horizontal and vertical position for the standard watermark,
\SetWatermarkVerCenter also forcing it to be centered there.
86 \newcommand{\SetWatermarkHorCenter}[1]{%
87   \DraftwatermarkOptions{hpos=#1, hanchor=c}}
88 \newcommand{\SetWatermarkVerCenter}[1]{%
89   \DraftwatermarkOptions{vpos=#1, vanchor=m}}

\SetWatermarkText Legacy command to set the text of the standard watermark
90 \newcommand{\SetWatermarkText}[1]{\DraftwatermarkOptions{text=#1}}

\SetWatermarkColor Legacy commands to set the color for the standard watermark.
\SetWatermarkLightness
91 \newcommand{\SetWatermarkColor}[2][]{%
92   \DraftwatermarkOptions{colormodel=#1, colorspec=#2}}
93 \newcommand{\SetWatermarkLightness}[1]{%
94   \DraftwatermarkOptions{colormodel=gray, colorspec=#1}}
95

\DraftwatermarkStdMark The command to generate the standard watermark
96 \newcommand{\DraftwatermarkStdMark}{%
97   \rotatebox{\draftwatermark@angle}{%
98     \scalebox{\draftwatermark@scale}{%
99       \begingroup
100      \ifx\draftwatermark@colormodel\@empty
101        \color{\draftwatermark@colorspec}%
102      \else
103        \color[\draftwatermark@colormodel]{\draftwatermark@colorspec}%
104      \fi
105      \setlength{\tempdima}{\draftwatermark@fontsize}%
106      \fontsize{\tempdima}{1.2\tempdima}\selectfont
107      \shortstack[\draftwatermark@alignment]{\draftwatermark@text}%
108    \endgroup}}}
109

```

The code to actually print the watermark

```
110 \newcommand{\draftwatermark@printwm}[1]{%
111   \sbox{\@tempboxa{#1}}%
112   \setlength{\@tempdima}{\draftwatermark@hpos}%
113   \setlength{\@tempdimb}{\draftwatermark@vpos}%
114   \edef \draftwatermark@tempa{\draftwatermark@hanchor}%
115   \@onelvel@sanitize \draftwatermark@tempa
116   \expandafter\def\expandafter\expandafter{\expandafter\car \draftwatermark@tempa\@nil}%
117   \if \draftwatermark@tempb r%
118     \addtolength{\@tempdima}{-\wd{\@tempboxa}}%
119   \else\if \draftwatermark@tempb c%
120     \addtolength{\@tempdima}{-0.5\wd{\@tempboxa}}%
121   \else\if \draftwatermark@tempb l%
122     \relax
123   \else
124     \PackageError{draftwatermark}{%
125       Illegal anchor directive '\draftwatermark@tempb'}%
126       {Anchoring to left side.}%
127     \fi\fi\fi
128   \edef \draftwatermark@tempa{\draftwatermark@vanchor}%
129   \@onelvel@sanitize \draftwatermark@tempa
130   \expandafter\def\expandafter\expandafter{\expandafter\car \draftwatermark@tempb\@nil}%
131   \if \draftwatermark@tempb b%
132     \addtolength{\@tempdimb}{-\ht{\@tempboxa}}%
133     \addtolength{\@tempdimb}{-\dp{\@tempboxa}}%
134   \else\if \draftwatermark@tempb m%
135     \addtolength{\@tempdimb}{-0.5\ht{\@tempboxa}}%
136     \addtolength{\@tempdimb}{-0.5\dp{\@tempboxa}}%
137   \else\if \draftwatermark@tempb t%
138     \relax
139   \else
140     \PackageError{draftwatermark}{%
141       Illegal anchor directive '\draftwatermark@tempb'}%
142       {Anchoring to top side.}%
143     \fi\fi\fi
144   \vbox to \opt{%
145     \vspace*{-1in}%
146     \vspace*{\@tempdimb}%
147     \hbox to \opt{%
148       \hspace*{-1in}%
149       \hspace*{\@tempdima}%
150       \usebox{\@tempboxa}%
151       \hss}%
152     \vss}%
153   \vss}}
```

A wrapper to make the watermark printing conditional

```
156 \newcommand{\draftwatermark@print}[1]{%
157   \ifdraftwatermark@stamp
158     \draftwatermark@printwm{#1}%
159   \fi}
```

... and finally the code to set up the `\everypage` hooks to assure that the watermark

```

printing commands are called when needed
160 \ifdraftwatermark@firstpageonly
161   \AddThispageHook{\draftwatermark@print{\draftwatermark@markcmd}}
162 \else
163   \AddEverypageHook{\draftwatermark@print{\draftwatermark@markcmd}}
164 \fi

```

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

D	
\draftwatermark@alignment	107
\draftwatermark@angle	97
\draftwatermark@colormodel	70, 74, 100, 103
\draftwatermark@colorspec	71, 75, 101, 103
\draftwatermark@fontsize	105
\draftwatermark@hanchor	47, 49, 51, 114
\draftwatermark@hpos	36, 112
\draftwatermark@markcmd	161, 163
\draftwatermark@print	156, 161, 163
\draftwatermark@printwm	110, 158
\draftwatermark@processanchor ..	31, 39
\draftwatermark@processcolor ..	33, 65
\draftwatermark@processcolor@i ..	67, 69
\draftwatermark@processcolor@ii ..	67, 73
\draftwatermark@processpos	29, 35
\draftwatermark@scale	98
\draftwatermark@tempa	40, 41, 43, 114, 115, 117, 129, 130, 132
\draftwatermark@tempb	42, 46, 48, 50, 52, 54, 56, 60, 116, 118, 120, 122, 126, 131, 133, 136, 139, 143
\draftwatermark@text	107
\draftwatermark@vanchor	53, 55, 57, 129
\draftwatermark@vpos	37, 113
\DraftwatermarkOptions	2, 10, 12, 22, <u>81</u> , 83–85, 87, 89, 90, 92, 94
\DraftwatermarkStdMark	6, 27, <u>96</u>
I	
\ifdraftwatermark@firstpageonly	160
\ifdraftwatermark@stamp	157
S	
\SetWatermarColor	<u>91</u>
\SetWatermarkAngle	7, <u>83</u>
\SetWatermarkColor	7, 91
\SetWatermarkFontSize	7, 84
\SetWatermarkHorCenter	7, <u>86</u>
\SetWatermarkLightness	7, 8, <u>91</u>
\SetWatermarkScale	7, <u>85</u>
\SetWatermarkText	7, 9, <u>90</u>
\SetWatermarkVerCenter	7, <u>86</u>