

Package ‘LRMF3’

October 12, 2022

Title Low Rank Matrix Factorization S3 Objects

Version 0.1.0

Description Provides S3 classes to represent low rank matrix decompositions.

License MIT + file LICENSE

URL <https://github.com/RoheLab/LRMF3>

BugReports <https://github.com/RoheLab/LRMF3/issues>

Depends Matrix, R (>= 3.1)

Imports glue

Suggests covr, testthat

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

Config/testthat/edition 3

NeedsCompilation no

Author Alex Hayes [aut, cre] (<<https://orcid.org/0000-0002-4985-5160>>)

Maintainer Alex Hayes <alexpghayes@gmail.com>

Repository CRAN

Date/Publication 2022-02-09 19:30:05 UTC

R topics documented:

as_fa_like	2
as_svd_like	2
dim_and_class	3
fa_like	3
ml100k	4
svd_like	4

Index	6
--------------	----------

as_fa_like	<i>Coerce an object to a factor analysis like factorization</i>
------------	---

Description

Coerce an object to a factor analysis like factorization

Usage

```
as_fa_like(x, ...)  
  
## S3 method for class 'list'  
as_fa_like(x, ...)
```

Arguments

x	Object to coerce
...	Ignored.

Value

Object as [svd_like\(\)](#) object.

as_svd_like	<i>Coerce an object to LRMF class</i>
-------------	---------------------------------------

Description

Coerce an object to LRMF class

Usage

```
as_svd_like(x, ...)  
  
## S3 method for class 'list'  
as_svd_like(x, ...)
```

Arguments

x	Object to coerce
...	Ignored.

Value

Object as [svd_like\(\)](#) object.

dim_and_class	<i>Description array size and type</i>
---------------	--

Description

Description array size and type

Usage

```
dim_and_class(x)
```

Arguments

x	Matrix or vector
---	------------------

Value

Description as character vector

fa_like	<i>Create a Factor Analysis-like low rank matrix factorization object</i>
---------	---

Description

A low rank matrix factorization of a matrix X is parameterized by $X \approx X \%*\% B \%*\% t(Y)$. The object is "factor analysis-like" because the middle matrix in the decomposition is arbitrary rather than diagonal.

Usage

```
fa_like(Z, B, Y, subclasses = NULL, ...)
```

Arguments

Z	A <i>matrix</i> of embeddings for each observation.
B	A mixing <i>matrix</i> describing how observation embeddings and topics interact. Does not have to be diagonal!
Y	A <i>matrix</i> describing the compositions of various topics or factors.
subclasses	A character vector of subclasses. Optional, defaults to NULL.
...	Optional additional items to pass to the constructor.

Examples

```
s <- svd(as.matrix(trees))
```

```
fa_like(s$u, diag(s$d), s$v)
```

m1100k

MovieLens 100K dataset

Description

Standard benchmarking dataset for recommendation systems. 100k movie ratings on 1682 movies by 943 users. Each user has rated at least 20 movies.

Usage

```
m1100k
```

Format

An object of class `dgCMatrix` with 943 rows and 1682 columns.

Details

Stored as a `Matrix::dgCMatrix` object, which is a sparse matrix. Each row corresponds to a user and each column to a movie.

References

F. Maxwell Harper and Joseph A. Konstan. 2015. The MovieLens Datasets: History and Context. *ACM Transactions on Interactive Intelligent Systems (TiiS)* 5, 4, Article 19 (December 2015), 19 pages. DOI=<http://dx.doi.org/10.1145/2827872>

<https://grouplens.org/datasets/movielens/100k/>

svd_like

Create a SVD-like low rank matrix factorization object

Description

A low rank matrix factorization of a matrix X is parameterized by $X \approx u \text{diag}(d) t(v)$. The object is "svd-like" because the middle matrix in the decomposition must be strictly diagonal.

Usage

```
svd_like(u, d, v, subclasses = NULL, ...)
```

Arguments

<code>u</code>	A <i>matrix</i> "left singular-ish" vectors.
<code>d</code>	A <i>vector</i> of "singular-ish" values.
<code>v</code>	A <i>matrix</i> of "right singular-ish" vectors.
<code>subclasses</code>	A character vector of subclasses. Optional, defaults to <code>NULL</code> .
<code>...</code>	Optional additional items to pass to the constructor.

Examples

```
s <- svd(as.matrix(trees))

# using the constructor directly
svd_like(s$u, s$d, s$v)

# coercing svd-like lists
as_svd_like(s)
```

Index

* datasets

ml100k, 4

as_fa_like, 2

as_svd_like, 2

dim_and_class, 3

fa_like, 3

ml100k, 4

svd_like, 4

svd_like(), 2