

# Package ‘PhySortR’

October 12, 2022

**Type** Package

**Title** A Fast, Flexible Tool for Sorting Phylogenetic Trees

**Version** 1.0.8

**Date** 2018-07-20

**Maintainer** Timothy Stephens <timothy.stephens1@uqconnect.edu.au>

**Description** Screens and sorts phylogenetic trees in both traditional and extended Newick format. Allows for the fast and flexible screening (within a tree) of Exclusive clades that comprise only the target taxa and/or Non-Exclusive clades that includes a defined portion of non-target taxa.

**Depends** R (>= 3.0.0)

**Imports** phytools, ape

**Repository** CRAN

**LazyData** true

**License** GPL (>= 3)

**RoxygenNote** 6.0.1

**NeedsCompilation** no

**Author** Timothy Stephens [aut, cre, trl] (R port),  
Debashish Bhattacharya [aut],  
Mark Ragan [aut],  
Cheong Xin Chan [aut, cph] (Original Perl implementation)

**Date/Publication** 2018-08-06 07:00:08 UTC

## R topics documented:

PhySortR-package . . . . .	2
convert.eNewick . . . . .	2
sortTrees . . . . .	3

<b>Index</b>	<b>6</b>
--------------	----------

PhySortR-package

*A Fast, Flexible Tool for Sorting Phylogenetic Trees*

---

**Description**

**PhySortR** provides a quick and highly flexible function for the screening (within a tree) of Exclusive clades that comprise only the target taxa and/or Non-Exclusive clades that includes a defined portion of non-target taxa. Support is also provided for both traditional and extended Newick formatted phylogenetic trees.

A full list of functions can be displayed by `library(help = PhySortR)`.

**Details**

Package: PhySortR  
Type: Package  
Version: 1.0.8  
Date: 2018-07-20  
License: GPL (>= 3)

**Author(s)**

Timothy G. Stephens, Debashish Bhattacharya, Mark A. Ragan, Cheong Xin Chan

Maintainer: Timothy G. Stephens <timothy.stephens1@uqconnect.edu.au>

**References**

Stephens TG, Bhattacharya D, Ragan MA, Chan CX. 2016. PhySortR: a fast, flexible tool for sorting phylogenetic trees in R. PeerJ, 4:e2038, DOI:10.7717/peerj.2038

**See Also**

[phytools ape](#)

---

convert.eNewick*Converts Extended Newick Format to Traditional Newick Format*

---

**Description**

Takes a phylogenetic tree in extended Newick format and converts it to traditional Newick format that can be directly manipulated by packages such as `ape` and `phytools`.

**Usage**

```
convert.eNewick(eNewick)
```

**Arguments**

eNewick            phylogenetic tree in extended Newick format.

**Value**

phylogenetic tree in traditional Newick format.

**Examples**

```
### Converts the phylogenetic tree into traditional Newick format.
tree <- "(A:0.1,(B:0.3,C:0.2):0.2[60]):0.4[100],(E:0.12,F:0.09):0.4[100]);"
new.tree <- convert.eNewick(tree)
new.tree
```

---

 sortTrees

*Sorts Phylogenetic Trees using Taxa Identifiers*


---

**Description**

Reads phylogenetic trees from a directory and sorts them based on the presence of Exclusive and Non-Exclusive clades containing a set of given target leaves at a desired support value. Can interpret trees in both Newick and extended Newick format.

**Usage**

```
sortTrees(target.groups, min.support = 0, min.prop.target = 0.7,
  in.dir = ".", out.dir = "Sorted_Trees", mode = "l",
  clades.sorted = "E,NE", extension = ".tre", clade.exclusivity = 0.9)
```

**Arguments**

target.groups    a set of one or more terms that represent the target leaves whose membership will be tested in each clade during sorting. Multiple terms are to be separated by a comma ("Taxon1,Taxon2"). This process is case sensitive and uses strict string-matching, so the taxa identifiers must be unique i.e. "plantae" and "Viridiplantae" might not be appropriate as the first is a subset of the second.

min.support      the minimum support (i.e. between 0-1 or 0-100) of a clade (Default = 0). Support values missing from phylogenetic trees are interpreted as zero.

min.prop.target    the minimum proportion (between 0.0-1.0) of target leaves to be present in a clade out of the total target leaves in the tree (Default = 0.7).

in.dir            directory containing the phylogenetic trees to be sorted (Default = current working directory).

out.dir	directory to be created within in.dir for the trees identified during sorting. If out.dir is omitted the default of Sorted_Trees/ will be used.
mode	option to "m" (move), "c" (copy) or "l" (list) trees identified during sorting. In "l" mode (default) a list of the sorted trees is returned, in the "m" and "c" modes a list is returned and the identified trees are moved/copied to the out.dir.
clades.sorted	option to control if the function will sort for Exclusive ("E") and/or Non-Exclusive ("NE") clades. Specify both options by comma separation "E,NE" (Default). Exclusive clades are also sorted into a sub-group of All Exclusive trees.
extension	the file extension of the tree files to be analyzed (Default = ".tre").
clade.exclusivity	the minimum proportion ( $0.0 \leq x < 1.0$ ) of target leaves to interrupting leaves allowed in each non-exclusive clade (Default = 0.9).

### Value

Will always return a list containing the names of the trees identified during sorting, irrespective of the mode argument.

### Examples

```
### Load data ###
extdata <- system.file("extdata", package="PhySortR")
file.copy(dir(extdata, full.names = TRUE), ".")
dir.create("Algae_Trees/")
file.copy(dir(extdata, full.names = TRUE), "Algae_Trees/")

### Examples ###
# (1) Sorting using 3 target terms, all other parameters default.
sortTrees(target.groups = "Rhodophyta,Viridiplantae")

# The function will search in the users current working directory for files
# with the extension ".tre" and check them (using default min.support,
# min.prop.target and clade.exclusivity) for Exclusive, All Exclusive or
# Non-Exclusive clades. A list will be returned with the names of the trees
# identified during sorting.

# (2) Sorting with a target directory and an out directory specified.
sortTrees(target.groups = "Rhodophyta,Viridiplantae",
  in.dir= "Algae_Trees/",
  out.dir="Sorted_Trees_RVG/",
  mode = "c")

# The function will search in "Algae_Trees/" for files with the extension
# ".tre" and check them (using default min.support, min.prop.target,
# clade.exclusivity) for Exclusive, All Exclusive or Non-Exclusive clades.
# The function will both (a) return a list of the trees identified during
# sorting and (b) copy the files into their respective subdirectories of
# "Algae_Trees/Sorted_Trees_RVG/Exclusive/",
```

```
# "Algae_Trees/Sorted_Trees_RVG/Exclusive/All_Exclusive/" and
# "Algae_Trees/Sorted_Trees_RVG/Non_Exclusive/".

# (3) Sorting with in/out directories, min.prop.target and min.support specified.
sortTrees(target.groups = "Rhodophyta,Viridiplantae",
  min.prop.target = 0.8,
  min.support = 90,
  in.dir= "Algae_Trees/",
  out.dir="Sorted_Trees_RVG_95/",
  mode = "c",
  clades.sorted = "NE",
  clade.exclusivity = 0.95)

# The function will search in "Algae_Trees/" for files with the
# extension ".tre" and check them for only Non-Exclusive clades.
# A clade will only be defined if it has support >= 90 and contains at least
# 80% of the total target leaves in the tree. A Non-Exclusive clade must also
# be composed of >= 95% target taxa (i.e. < 5% non-target taxa).
# The function will (a) return a list of the trees identified during
# sorting and (b) copy the trees identified during sorting to the out
# directory "Algae_Trees/Sorted_Trees_RVG/Non_Exclusive/".

### Clean up ###
unlink("Algae_Trees", recursive=TRUE)
unlink("Sorted_Trees.log")
unlink(dir(".", "*.tre$"))
```

# Index

\* **package**

PhySortR-package, [2](#)

ape, [2](#)

convert.eNewick, [2](#)

PhySortR-package, [2](#)

phytools, [2](#)

sortTrees, [3](#)