

Package ‘vismeteor’

September 8, 2025

Type Package
Title Analysis of Visual Meteor Data
Version 2.0.0
Author Janko Richter [aut, cre]
Maintainer Janko Richter <janko@richtej.de>
Description Provides a suite of analytical functionalities to process and analyze
visual meteor observations from the Visual Meteor Database
of the International Meteor Organization <<https://www.imo.net/>>.
License MIT + file LICENSE
URL <https://github.com/jankorichter/vismeteor>
BugReports <https://github.com/jankorichter/vismeteor/issues>
Encoding UTF-8
LazyData true
Depends R (>= 3.5.0)
Imports methods, stats, DBI
RoxygenNote 7.3.2
Suggests usethis (>= 2.1.1), testthat (>= 3.0.0), RSQLite (>= 2.2.1),
RPostgreSQL (>= 0.7), RMySQL (>= 0.10.1), knitr, rmarkdown
Config/testthat/edition 3
VignetteBuilder knitr
NeedsCompilation no
Repository CRAN
Date/Publication 2025-09-07 22:00:02 UTC

Contents

vismeteor-package	2
freq.quantile	2
load_vmdb	3

mideal	6
PER_2015_magn	9
PER_2015_rates	9
vmgeom	10
vmgeomVst	12
vmideal	14
vmidealVst	17
vmperception	18
vmtable	20
Index	22

vismeteor-package	<i>vismeteor: Analysis of Visual Meteor Data</i>
-------------------	--

Description

Provides a suite of analytical functionalities to process and analyze visual meteor observations from the Visual Meteor Database of the International Meteor Organization <https://www.imo.net/>.

Details

The data used in this package can created and provided by [imo-vmdb](#).

Author(s)

Maintainer: Janko Richter <janko@richtej.de>

See Also

- Useful links:
- <https://github.com/jankorichter/vismeteor>
 - Report bugs at <https://github.com/jankorichter/vismeteor/issues>

freq.quantile	<i>Quantiles with a minimum frequency</i>
---------------	---

Description

This function generates quantiles with a minimum frequency. These quantiles are formed from a vector freq of frequencies. Each quantile then has the minimum total frequency min.

Usage

freq.quantile(freq, min)

Arguments

freq integer; A vector of frequencies.
 min integer; Minimum total frequency per quantile.

Details

The frequencies freq are grouped in the order in which they are passed as a vector. The minimum min must be greater than 0.

Value

A factor of indices is returned. The index references the corresponding passed frequency freq.

Examples

```
freq <- c(1,2,3,4,5,6,7,8,9)
cumsum(freq)
(f <- freq.quantile(freq, 10))
tapply(freq, f, sum)
```

load_vmdb

Loading visual meteor observations from the data base

Description

Loads the data of visual meteor observations from a data base created with **imo-vmdb**.

Usage

```
load_vmdb_rates(
  dbcon,
  shower = NULL,
  period = NULL,
  sl = NULL,
  lim.magn = NULL,
  sun.alt.max = NULL,
  moon.alt.max = NULL,
  session.id = NULL,
  rate.id = NULL,
  withSessions = FALSE,
  withMagnitudes = FALSE
)

load_vmdb_magnitudes(
  dbcon,
  shower = NULL,
  period = NULL,
```

```

sl = NULL,
lim.magn = NULL,
session.id = NULL,
magn.id = NULL,
withSessions = FALSE,
withMagnitudes = TRUE
)

```

Arguments

dbcon	database connection.
shower	character; selects by meteor shower codes. NA loads sporadic meteors.
period	time; selects a time range by minimum/maximum.
sl	numeric; selects a range of solar longitudes by minimum/maximum.
lim.magn	numeric; selects a range of limiting magnitudes by minimum/maximum.
sun.alt.max	numeric; selects the maximum altitude of the sun.
moon.alt.max	numeric; selects the maximum altitude of the moon.
session.id	integer; selects by session ids.
rate.id	integer; selects rate observations by ids.
withSessions	logical; if TRUE, also load the corresponding session data.
withMagnitudes	logical; if TRUE, also load the corresponding magnitude observations.
magn.id	integer; selects magnitude observations by ids.

Details

sl, period and lim.magn expect a vector with successive minimum and maximum values. sun.alt.max and moon.alt.max are expected to be scalar values.

Value

Both functions return a list, with

observations	data frame, rate or magnitude observations,
sessions	data frame; session data of observations,
magnitudes	table; contingency table of meteor magnitude frequencies.

observations depends on the function call. load_vmdb_rates returns a data frame, with

rate.id	unique identifier of the rate observation,
shower.code	IAU code of the shower. It is NA in case of sporadic meteors.
period.start	start of observation,
period.end	end of observation,
sl.start	solarlong at start of observation,
sl.end	solarlong at start of observation,
session.id	reference to the session,

freq	count of observed meteors,
lim.magn	limiting magnitude,
t.eff	net observed time in hours,
f	correction factor of cloud cover,
time.sidereal	sidereal time,
sun.alt	altitude of the sun,
sun.az	azimuth of the sun,
moon.alt	altitude of the moon,
moon.az	azimuth of the moon,
moon.illum	illumination of the moon (0.0 .. 1.0),
field.alt	altitude of the field of view (optional),
field.az	azimuth of the field of view (optional),
radiant.alt	altitude of the radiant (optional). The zenith attraction is already applied.
radiant.az	azimuth of the radiant (optional),
magn.id	reference to the magnitude observations (optional).

load_vmdb_magnitudes returns a observations data frame, with

magn.id	unique identifier of the magnitude observation,
shower.code	IAU code of the shower. It is NA in case of sporadic meteors.
period.start	start of observation,
period.end	end of observation,
sl.start	solarlong at start of observation,
sl.end	solarlong at start of observation,
session.id	reference to the session,
freq	count of observed meteors,
magn.mean	mean of magnitudes,
lim.magn	limiting magnitude (optional).

The sessions data frame contains

session.id	unique identifier of the session,
longitude	location's longitude,
latitude	location's latitude,
elevation	height above mean sea level in km,
country	country name,
location.name	location name,
observer.id	observer id (optional),
observer.name	observer name (optional).

magnitudes is a contingency table of meteor magnitude frequencies. The row names refer to the id of magnitude observations. The column names refer to the magnitude.

Note

Angle values are expected and returned in degrees.

References

<https://pypi.org/project/imo-vmdb/>

Examples

```
## Not run:
# create a connection to the data base
con <- dbConnect(
  PostgreSQL(),
  dbname = "vmdb",
  host = "localhost",
  user = "vmdb"
)

# load rate observations including
# session data and magnitude observations
data <- load_vmdb_rates(
  con,
  shower = 'PER',
  sl = c(135.5, 145.5),
  period = c('2015-08-01', '2015-08-31'),
  lim.magn = c(5.3, 6.7),
  withMagnitudes = TRUE,
  withSessions = TRUE
)

# load magnitude observations including
# session data and magnitude observations
data <- load_vmdb_magnitudes(
  con,
  shower = 'PER',
  sl = c(135.5, 145.5),
  period = c('2015-08-01', '2015-08-31'),
  lim.magn = c(5.3, 6.7),
  withMagnitudes = TRUE,
  withSessions = TRUE
)

## End(Not run)
```

mideal

Ideal Distribution of Meteor Magnitudes

Description

Density, distribution function, quantile function and random generation for the ideal distribution of meteor magnitudes.

Usage

```
dmideal(m, psi = 0, log = FALSE)

pmideal(m, psi = 0, lower.tail = TRUE, log = FALSE)

qmideal(p, psi = 0, lower.tail = TRUE)

rmideal(n, psi = 0)
```

Arguments

<code>m</code>	numeric; meteor magnitude.
<code>psi</code>	numeric; the location parameter of a probability distribution. It is the only parameter of the distribution.
<code>log</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default) probabilities are $P[M \leq m]$, otherwise, $P[M > m]$.
<code>p</code>	numeric; probability.
<code>n</code>	numeric; count of meteor magnitudes.

Details

The density of the ideal distribution of meteor magnitudes is

$$\frac{dp}{dm} = \frac{3}{2} \log(r) \sqrt{\frac{r^{3\psi+2m}}{(r^\psi + r^m)^5}}$$

where m is the meteor magnitude, $r = 10^{0.4} \approx 2.51189 \dots$ is a constant and ψ is the only parameter of this magnitude distribution.

Value

`dmideal` gives the density, `pmideal` gives the distribution function, `qmideal` gives the quantile function and `rmideal` generates random deviates.

The length of the result is determined by `n` for `rmideal`, and is the maximum of the lengths of the numerical vector arguments for the other functions.

`qmideal` can return NaN value with a warning.

References

Richter, J. (2018) *About the mass and magnitude distributions of meteor showers*. WGN, Journal of the International Meteor Organization, vol. 46, no. 1, p. 34-38

Examples

```

old_par <- par(mfrow = c(2,2))
psi <- 5.0
plot(
  function(m) dmideal(m, psi, log = FALSE),
  -5, 10,
  main = paste0('Density of the Ideal Meteor Magnitude\nDistribution (psi = ', psi, ')'),
  col = "blue",
  xlab = 'm',
  ylab = 'dp/dm'
)
abline(v=psi, col="red")

plot(
  function(m) dmideal(m, psi, log = TRUE),
  -5, 10,
  main = paste0('Density of the Ideal Meteor Magnitude\nDistribution (psi = ', psi, ')'),
  col = "blue",
  xlab = 'm',
  ylab = 'log( dp/dm )'
)
abline(v=psi, col="red")

plot(
  function(m) pmideal(m, psi),
  -5, 10,
  main = paste0('Probability of the Ideal Meteor Magnitude\nDistribution (psi = ', psi, ')'),
  col = "blue",
  xlab = 'm',
  ylab = 'p'
)
abline(v=psi, col="red")

plot(
  function(p) qmideal(p, psi),
  0.01, 0.99,
  main = paste0('Quantile of the Ideal Meteor Magnitude\nDistribution (psi = ', psi, ')'),
  col = "blue",
  xlab = 'p',
  ylab = 'm'
)
abline(h=psi, col="red")

# generate random meteor magnitudes
m <- rmideal(1000, psi)

# log likelihood function
llr <- function(psi) {
  -sum(dmideal(m, psi, log=TRUE))
}

# maximum likelihood estimation (MLE) of psi

```



```

est <- optim(2, llr, method='Brent', lower=0, upper=8, hessian=TRUE)

# estimations
est$par # mean of psi
sqrt(1/est$hessian[1][1]) # standard deviation of psi

par(old_par)

```

PER_2015_magn

Visual magnitude observations of Perseids from 2015

Description

Visual magnitude observations of the Perseid shower from 2015.

Details

PER_2015_magn are magnitude observations loaded with [load_vmdb_magnitudes](#).

See Also

[load_vmdb](#)

PER_2015_rates

Visual rate observations of Perseids from 2015

Description

Visual rate and magnitude observations of the Perseid shower from 2015.

Details

PER_2015_rates are rate observations loaded with [load_vmdb_rates](#).

See Also

[load_vmdb](#)

Description

Density, distribution function, quantile function, and random generation for the geometric model of visual meteor magnitudes.

Usage

```
dvmgeom(m, lm, r, log = FALSE, perception.fun = NULL)
```

```
pvmgeom(m, lm, r, lower.tail = TRUE, log = FALSE, perception.fun = NULL)
```

```
qvmgeom(p, lm, r, lower.tail = TRUE, perception.fun = NULL)
```

```
rvmgeom(n, lm, r, perception.fun = NULL)
```

Arguments

<code>m</code>	numeric; the meteor magnitude.
<code>lm</code>	numeric; limiting magnitude.
<code>r</code>	numeric; the population index.
<code>log</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>perception.fun</code>	function; perception probability function (optional). Default is vmperception .
<code>lower.tail</code>	logical; if TRUE (default) probabilities are $P[M < m]$, otherwise, $P[M \geq m]$.
<code>p</code>	numeric; probability.
<code>n</code>	numeric; count of meteor magnitudes.

Details

In visual meteor observations, magnitudes are usually estimated as integer values. Hence, this distribution is discrete and its probability mass function is

$$P[X = x] \sim f(x) r^{-x},$$

where $x \geq -0.5$ denotes the difference between the limiting magnitude `lm` and the meteor magnitude `m`, and $f(x)$ is the perception probability function. Thus, the distribution is the product of the [perception probabilities](#) and the underlying [geometric distribution](#) of meteor magnitudes. Therefore, the parameter `p` of the geometric distribution is given by $p = 1 - 1/r$.

The parameter `lm` specifies the reference for the meteor magnitude `m`. `m` must be an integer meteor magnitude. The length of the vector `lm` must either equal the length of the vector `m`, or `lm` must be a scalar value. In the case of `rvmgeom`, the length of the vector `lm` must equal `n`, or `lm` must be a scalar value.

If a perception probability function `perception.fun` is provided, it must have the signature `function(x)` and return the perception probability of the difference `x` between the limiting magnitude and the meteor magnitude. If `x >= 15.0`, the function `perception.fun` should return a perception probability of `1.0`. If `log = TRUE` is specified, the logarithm of the perception probabilities must be returned. The argument `perception.fun` is resolved using [match.fun](#).

Value

- `dvmgeom`: density
- `pvmgeom`: distribution function
- `qvmgeom`: quantile function
- `rvmgeom`: random generation

The length of the result is determined by `n` for `rvmgeom`, and by the maximum of the lengths of the numeric vector arguments for the other functions.

Since the distribution is discrete, `qvmgeom` and `rvmgeom` always return integer values. `qvmgeom` may return `NaN` with a warning.

See Also

[vmperception stats::Geometric](#)

Examples

```
N <- 100
r <- 2.0
limmag <- 6.5
(m <- seq(6, -7))

# discrete density of `N` meteor magnitudes
(freq <- round(N * dvmgeom(m, limmag, r)))

# log likelihood function
lld <- function(r) {
  -sum(freq * dvmgeom(m, limmag, r, log=TRUE))
}

# maximum likelihood estimation (MLE) of r
est <- optim(2, lld, method='Brent', lower=1.1, upper=4)

# estimations
est$par # mean of r

# generate random meteor magnitudes
m <- rvmgeom(N, r, lm=limmag)

# log likelihood function
llr <- function(r) {
  -sum(dvmgeom(m, limmag, r, log=TRUE))
}
```

```

# maximum likelihood estimation (MLE) of r
est <- optim(2, llr, method='Brent', lower=1.1, upper=4, hessian=TRUE)

# estimations
est$par # mean of r
sqrt(1/est$hessian[1][1]) # standard deviation of r

m <- seq(6, -4, -1)
p <- vismeteor::dvmgeom(m, limmag, r)
barplot(
  p,
  names.arg = m,
  main = paste0('Density (r = ', r, ', limmag = ', limmag, ')'),
  col = "blue",
  xlab = 'm',
  ylab = 'p',
  border = "blue",
  space = 0.5
)
axis(side = 2, at = pretty(p))

```

vmgeomVst

Variance-Stabilizing Transformation for Geometric Visual Meteor Magnitudes

Description

Applies a variance-stabilizing transformation to visual meteor magnitudes under the geometric model.

Usage

```
vmgeomVstFromMagn(m, lm)
```

```
vmgeomVstToR(tm, log = FALSE, deriv.degree = 0L)
```

Arguments

m	integer; meteor magnitude.
lm	numeric; limiting magnitude.
tm	numeric; transformed magnitude.
log	logical; if TRUE, the logarithm of the population index r is returned.
deriv.degree	integer; the order of the derivative at tm to return instead of r or $\log(r)$. Must be 0, 1, or 2.

Details

Many linear models require the variance of visual meteor magnitudes to be homoscedastic. The function `vmgeomVstFromMagn` applies a transformation that produces homoscedastic distributions of visual meteor magnitudes if the underlying distribution follows a geometric model.

The geometric model of visual meteor magnitudes depends on the [population index](#) r and the limiting magnitude l_m , resulting in a two-parameter distribution. Without detection probabilities, the magnitude distribution is purely geometric, and for integer limiting magnitudes the variance depends only on the population index r . Since the limiting magnitude l_m is a fixed parameter and never estimated statistically, the magnitudes can be transformed such that, for example, the mean of the transformed magnitudes directly provides an estimate of r using the function `vmgeomVstToR`.

A key advantage of this transformation is that the limiting magnitude l_m is already incorporated into subsequent analyses. In this sense, the transformation acts as a normalization of meteor magnitudes and yields a variance close to 1.0.

This transformation is valid for $1.4 \leq r \leq 3.5$. The numerical form of the transformation is version-specific and may change substantially in future releases. Do not rely on equality of transformed values across package versions.

Value

- `vmgeomVstFromMagn`: numeric value, the transformed meteor magnitude.
- `vmgeomVstToR`: numeric value of the population index r , derived from the mean of `tm`.

The argument `deriv.degree` can be used to apply the delta method. If `log = TRUE`, the logarithm of r is returned.

See Also

[vmgeom](#)

Examples

```
N <- 100
r <- 2.0
limmag <- 6.3

# Simulate magnitudes
m <- rvmgeom(N, limmag, r)

# Variance-stabilizing transformation
tm <- vmgeomVstFromMagn(m, limmag)
tm.mean <- mean(tm)
tm.var <- var(tm)

# Estimator for r from the transformed mean
r.hat <- vmgeomVstToR(tm.mean)

# Derivative dr/d(tm) at tm.mean (needed for the delta method)
dr_dtm <- vmgeomVstToR(tm.mean, deriv.degree = 1L)

# Variance of the sample mean of tm
```

```

var_tm.mean <- tm.var / N

# Delta method: variance and standard error of r.hat
var_r.hat <- (dr_dtm^2) * var_tm.mean
se_r.hat  <- sqrt(var_r.hat)

# Results
print(r.hat)
print(se_r.hat)

```

vmideal

Ideal Distribution of Visual Meteor Magnitudes

Description

Density, distribution function, quantile function, and random generation for the ideal distribution of visual meteor magnitudes.

Usage

```

dvmideal(m, lm, psi, log = FALSE, perception.fun = NULL)

pvmideal(m, lm, psi, lower.tail = TRUE, log = FALSE, perception.fun = NULL)

qvmideal(p, lm, psi, lower.tail = TRUE, perception.fun = NULL)

rvmideal(n, lm, psi, perception.fun = NULL)

cvmideal(lm, psi, log = FALSE, perception.fun = NULL)

```

Arguments

m	integer; visual meteor magnitude.
lm	numeric; limiting magnitude.
psi	numeric; the location parameter of the probability distribution.
log	logical; if TRUE, probabilities are returned as $\log(p)$.
perception.fun	function; optional perception probability function. The default is vmperception .
lower.tail	logical; if TRUE (default), probabilities are $P[M < m]$; otherwise, $P[M \geq m]$.
p	numeric; probability.
n	numeric; count of meteor magnitudes.

Details

The density of the [ideal distribution of meteor magnitudes](#) is

$$f(m) = \frac{dp}{dm} = \frac{3}{2} \log(r) \sqrt{\frac{r^{3\psi+2m}}{(r^\psi + r^m)^5}}$$

where m is the meteor magnitude, $r = 10^{0.4} \approx 2.51189 \dots$ is a constant, and ψ is the only parameter of this magnitude distribution.

In visual meteor observations, magnitudes are usually estimated as integer values. Hence, this distribution is discrete and its probability mass function is given by

$$P[M = m] \sim g(m) \int_{m-0.5}^{m+0.5} f(m) dm,$$

where $g(m)$ denotes the perception probability. Thus, the distribution is the product of the [perception probabilities](#) and the underlying [ideal distribution](#) of meteor magnitudes.

If a perception probability function `perception.fun` is supplied, it must have the signature `function(M)` and return the perception probabilities of the difference M between the limiting magnitude and the meteor magnitude. If `m >= 15.0`, the `perception.fun` function should return a perception probability of `1.0`. If `log = TRUE` is given, the logarithm of the perception probabilities must be returned. The argument `perception.fun` is resolved using [match.fun](#).

Value

- `dvideal`: density
- `pvmideal`: distribution function
- `qvmideal`: quantile function
- `rvmideal`: random generation
- `cvmideal`: partial convolution of the ideal distribution of meteor magnitudes with the perception probabilities.

The length of the result is determined by `n` for `rvmideal`, and is the maximum of the lengths of the numeric vector arguments for the other functions.

Since the distribution is discrete, `qvmideal` and `rvmideal` always return integer values. `qvmideal` may return `NaN` with a warning.

References

Richter, J. (2018) *About the mass and magnitude distributions of meteor showers*. WGN, Journal of the International Meteor Organization, vol. 46, no. 1, p. 34-38

See Also

[mideal](#) [vmperception](#)

Examples

```

N <- 100
psi <- 5.0
limmag <- 6.5
(m <- seq(6, -4))

# discrete density of `N` meteor magnitudes
(freq <- round(N * dvmideal(m, limmag, psi)))

# log likelihood function
lld <- function(psi) {
  -sum(freq * dvmideal(m, limmag, psi, log=TRUE))
}

# maximum likelihood estimation (MLE) of psi
est <- optim(2, lld, method='Brent', lower=0, upper=8, hessian=TRUE)

# estimations
est$par # mean of psi

# generate random meteor magnitudes
m <- rvmideal(N, limmag, psi)

# log likelihood function
llr <- function(psi) {
  -sum(dvmideal(m, limmag, psi, log=TRUE))
}

# maximum likelihood estimation (MLE) of psi
est <- optim(2, llr, method='Brent', lower=0, upper=8, hessian=TRUE)

# estimations
est$par # mean of psi
sqrt(1/est$hessian[1][1]) # standard deviation of psi

m <- seq(6, -4, -1)
p <- vismeteor::dvmideal(m, limmag, psi)
barplot(
  p,
  names.arg = m,
  main = paste0('Density (psi = ', psi, ', limmag = ', limmag, ')'),
  col = "blue",
  xlab = 'm',
  ylab = 'p',
  border = "blue",
  space = 0.5
)
axis(side = 2, at = pretty(p))

plot(
  function(lm) vismeteor::cvmideal(lm, psi, log = TRUE),
  -5, 10,

```



```

    main = paste0(
      'Partial convolution of the ideal meteor magnitude distribution\n',
      'with the perception probabilities (psi = ', psi, ')\n'
    ),
    col = "blue",
    xlab = 'lm',
    ylab = 'log(rate)'
  )
)

```

vmidealVst	<i>Variance-stabilizing Transformation for the Ideal Distribution of Visual Meteor Magnitudes</i>
------------	---

Description

Applies a variance-stabilizing transformation to meteor magnitudes under the assumption of the ideal magnitude distribution.

Usage

```

vmidealVstFromMagn(m, lm)

vmidealVstToPsi(tm, lm, deriv.degree = 0L)

```

Arguments

<code>m</code>	integer; the meteor magnitude.
<code>lm</code>	numeric; limiting magnitude.
<code>tm</code>	numeric; transformed magnitude.
<code>deriv.degree</code>	integer; the degree of the derivative at <code>tm</code> to return instead of <code>r</code> or <code>log(r)</code> . Must be 0, 1 or 2.

Details

Many linear models require the variance of visual meteor magnitudes to be homoscedastic. The function `vmidealVstFromMagn` applies a transformation that produces homoscedastic distributions of visual meteor magnitudes if the underlying magnitudes follow the ideal magnitude distribution. In this sense, the transformation acts as a normalization of meteor magnitudes and yields a variance close to 1.0.

The ideal distribution of visual meteor magnitudes depends on the [parameter `psi`](#) and the limiting magnitude `lm`, resulting in a two-parameter distribution. Without detection probabilities, the magnitude distribution reduces to a pure [ideal magnitude distribution](#), which depends only on the parameter `psi`. Since the limiting magnitude `lm` is a fixed parameter and never estimated statistically, the magnitudes can be transformed such that, for example, the mean of the transformed magnitudes directly provides an estimate of `psi` using the function `vmidealVstToPsi`.

This transformation is valid for $-10 \leq \psi \leq 9$. The numerical form of the transformation is version-specific and may change substantially in future releases. Do not rely on equality of transformed values across package versions.

Value

- `vmidealVstFromMagn`: a numeric value, the transformed meteor magnitude.
- `vmidealVstToPsi`: a numeric value of the parameter `psi`, derived from the mean of `tm`. The argument `deriv.degree` can be used to apply the delta method.

See Also

[vmgeom](#)

Examples

```
N <- 100
psi <- 5.0
limmag <- 6.3

# Simulate magnitudes
m <- rvmideal(N, limmag, psi)

# Variance-stabilizing transformation
tm <- vmidealVstFromMagn(m, limmag)
tm.mean <- mean(tm)
tm.var <- var(tm)

# Estimator for psi from the transformed mean
psi.hat <- vmidealVstToPsi(tm.mean, limmag)

# Derivative d(psi)/d(tm) at tm.mean (needed for the delta method)
dpsi_dtm <- vmidealVstToPsi(tm.mean, limmag, deriv.degree = 1L)

# Variance of the sample mean of tm
var_tm.mean <- tm.var / N

# Delta method: variance and standard error of psi.hat
var_psi.hat <- (dpsi_dtm^2) * var_tm.mean
se_psi.hat <- sqrt(var_psi.hat)

# Results
print(psi.hat)
print(se_psi.hat)
```

vmperception

Perception Probabilities of Visual Meteor Magnitudes

Description

Provides the perception probability of visual meteor magnitudes.

Usage

```
vmperception(m)
```

Arguments

m numerical; difference between the limiting magnitude and the meteor magnitude.

Details

The perception probabilities of *Koschack R., Rendtel J., 1990b* are estimated with the formula

$$p(m) = \begin{cases} 1.0 - \exp(-z(m + 0.5)) & \text{if } m > -0.5, \\ 0.0 & \text{otherwise,} \end{cases}$$

where

$$z(x) = 0.0037x + 0.0019x^2 + 0.00271x^3 + 0.0009x^4$$

and m is the difference between the limiting magnitude and the meteor magnitude.

Value

This function returns the visual perception probabilities.

References

Koschack R., Rendtel J., 1990b *Determination of spatial number density and mass index from visual meteor observations (II)*. WGN 18, 119–140.

Examples

```
# Perception probability of visually estimated meteor of magnitude 3.0
# with a limiting magnitude of 5.6.
vmperception(5.6 - 3.0)

# plot
old_par <- par(mfrow = c(1,1))
plot(
  vmperception,
  -0.5, 8,
  main = paste(
    'perception probability of',
    'visual meteor magnitudes'
  ),
  col = "blue",
  xlab = 'm',
  ylab = 'p'
)

par(old_par)
```

vmtable

*Rounds a contingency table of meteor magnitude frequencies***Description**

The meteor magnitude contingency table of VMDB contains half meteor counts (e.g. 3.5). This function converts these frequencies to integer values.

Usage

```
vmtable(mt)
```

Arguments

`mt` table; A two-dimensional contingency table of meteor magnitude frequencies.

Details

The contingency table of meteor magnitudes `mt` must be two-dimensional. The row names refer to the magnitude observations. Column names must be integer meteor magnitude values. Also, the columns must be sorted in ascending or descending order of meteor magnitude.

A sum-preserving algorithm is used for rounding. It ensures that the total frequency of meteors per observation is preserved. The marginal frequencies of the magnitudes are also preserved with the restriction that the deviation is at most ± 0.5 . If the total sum of a meteor magnitude is integer, then the deviation is ± 0 .

The algorithm is asymptotic. This means that the more meteors the table contains, the more unbiased is the result of the rounding.

Value

A rounded contingency table of meteor magnitudes is returned.

Examples

```
# For example, create a contingency table of meteor magnitudes
mt <- as.table(matrix(
  c(
    0.0, 0.0, 2.5, 0.5, 0.0, 1.0,
    0.0, 1.5, 2.0, 0.5, 0.0, 0.0,
    1.0, 0.0, 0.0, 3.0, 2.5, 0.5
  ), nrow = 3, ncol = 6, byrow = TRUE
))
colnames(mt) <- seq(6)
rownames(mt) <- c('A', 'B', 'C')
mt
margin.table(mt, 1)
margin.table(mt, 2)
```

```
# contingency table with integer values
(mt.int <- vmtable(mt))
margin.table(mt.int, 1)
margin.table(mt.int, 2)
```

Index

- * **data**
 - PER_2015_magn, [9](#)
 - PER_2015_rates, [9](#)
- cvideal (vmideal), [14](#)
- dmideal (mideal), [6](#)
- dvmgeom (vmgeom), [10](#)
- dvideal (vmideal), [14](#)
- freq.quantile, [2](#)
- geometric distribution, [10](#)
- ideal distribution, [15](#)
- ideal distribution of meteor
 - magnitudes, [15](#)
- ideal magnitude distribution, [17](#)
- load_vmdb, [3](#), [9](#)
- load_vmdb_magnitudes, [9](#)
- load_vmdb_magnitudes (load_vmdb), [3](#)
- load_vmdb_rates, [9](#)
- load_vmdb_rates (load_vmdb), [3](#)
- match.fun, [11](#), [15](#)
- mideal, [6](#), [15](#)
- parameter psi, [17](#)
- PER_2015_magn, [9](#)
- PER_2015_rates, [9](#)
- perception probabilities, [10](#), [15](#)
- pmideal (mideal), [6](#)
- population index, [13](#)
- pvmgeom (vmgeom), [10](#)
- pvmideal (vmideal), [14](#)
- qmideal (mideal), [6](#)
- qvmgeom (vmgeom), [10](#)
- qvmideal (vmideal), [14](#)
- rmideal (mideal), [6](#)
- rvmgeom (vmgeom), [10](#)
- rvmideal (vmideal), [14](#)
- stats::Geometric, [11](#)
- vismeteor (vismeteor-package), [2](#)
- vismeteor-package, [2](#)
- vmgeom, [10](#), [13](#), [18](#)
- vmgeomVst, [12](#)
- vmgeomVstFromMagn (vmgeomVst), [12](#)
- vmgeomVstToR (vmgeomVst), [12](#)
- vmideal, [14](#)
- vmidealVst, [17](#)
- vmidealVstFromMagn (vmidealVst), [17](#)
- vmidealVstToPsi (vmidealVst), [17](#)
- vmperception, [10](#), [11](#), [14](#), [15](#), [18](#)
- vmtable, [20](#)