

# Package ‘airship’

July 22, 2025

**Title** Visualization of Simulated Datasets with Multiple Simulation Input Dimensions

**Version** 1.4.3

**Description** Plots simulation results of clinical trials. Its main feature is allowing users to simultaneously investigate the impact of several simulation input dimensions through dynamic filtering of the simulation results. A more detailed description of the app can be found in Meyer et al. <[DOI:10.1016/j.softx.2023.101347](https://doi.org/10.1016/j.softx.2023.101347)> or the vignettes on 'GitHub'.

**BugReports** <https://github.com/el-meyer/airship/issues>

**License** GPL-3

**Encoding** UTF-8

**RoxygenNote** 7.3.1

**Depends** R (>= 2.10), shiny, shinyBS

**Imports** DT, shinybusy, plotly, dplyr, tidyselect, tidyr, stringr, colourpicker, shinyWidgets, shinydashboard, scales, Cairo, ggplot2, rlang, magrittr, shinyjs, data.table, shinyalert, vctrs, mvtnorm

**LazyData** true

**Suggests** knitr, rmarkdown, ggpubr

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Elias Laurin Meyer [aut, cre] (ORCID: <<https://orcid.org/0000-0001-5398-6334>>),  
Constantin Kumaus [aut, ctb],  
Michal Majka [aut, ctb] (ORCID: <<https://orcid.org/0000-0002-7524-8014>>),  
Franz Koenig [aut, ctb] (ORCID: <<https://orcid.org/0000-0002-6893-3304>>)

**Maintainer** Elias Laurin Meyer <[elias@berryconsultants.net](mailto:elias@berryconsultants.net)>

**Repository** CRAN

**Date/Publication** 2024-12-05 18:40:10 UTC

## Contents

airship . . . . .	2
ExampleData1 . . . . .	3
ExampleData2 . . . . .	4

<b>Index</b>	<b>5</b>
--------------	----------

---

airship	<i>Runs the Shiny app "AIRSHIP".</i>
---------	--------------------------------------

---

### Description

Runs the Shiny app "AIRSHIP".

### Usage

```
airship(
  dfData = NULL,
  cLastInputVar = NULL,
  cReplicationVar = NULL,
  bIsFacts = FALSE
)
```

### Arguments

dfData	Dataset that should be plotted by Airship; can be NULL if upload should be done within the app.
cLastInputVar	Optional and only useful in combination with dfData. Character name of last input variable.
cReplicationVar	Optional and only useful in combination with dfData. Character name of simulation replication variable.
bIsFacts	Boolean variable; is the supplied dfData a FACTS aggregated simulation file.

### Value

No return value

### Examples

```
if(interactive()){
  airship()
}

# See Vignette.
```

---

`ExampleData1`*Example Data 1*

---

**Description**

An artificially simulated dataset containing bivariate normal outcomes. Outcomes depend on four input variables in a very simple manner. For each set of input variables, 1000 replications are simulated.

**Usage**`ExampleData1`**Format**

An object of class `data.frame` with 81000 rows and 7 columns.

**Examples**

```
input1 <- c("A", "B", "C")
input2 <- c(1, 2, 3)
input3 <- c("Z", "Y", "X")
input4 <- c(11, 12, 13)
replications <- 1:1000

scenarios <-
  expand.grid(
    replications = replications,
    input1 = input1,
    input2 = input2,
    input3 = input3,
    input4 = input4
  )

for (i in 1:nrow(scenarios)) {

  var <- ifelse(scenarios$input1[i] == "A", 1, 10)
  cor <- ifelse(scenarios$input3[i] == "Z", 0.7, 0.1)

  out <- mvtnorm::rmvnorm(
    1,
    mean = c(scenarios$input2[i], scenarios$input4[i]),
    sigma = matrix(c(var, cor, cor, var), nrow = 2)
  )

  scenarios$output1[i] <- out[1]
  scenarios$output2[i] <- out[2]
}
```

```
ExampleData1 <- scenarios
```

---

ExampleData2	<i>Example Data 2</i>
--------------	-----------------------

---

**Description**

Simulated dataset from Meyer et al. (2022) <https://doi.org/10.1002/pst.2194>.

**Usage**

```
ExampleData2
```

**Format**

An object of class `data.frame` with 10080 rows and 18 columns.

**Source**

<https://github.com/el-meyer/airship/blob/master/data/ExampleDataNASH.csv>

# Index

## \* datasets

ExampleData1, 3

ExampleData2, 4

airship, 2

ExampleData1, 3

ExampleData2, 4