

Package ‘valdr’

September 1, 2025

Title Access and Analyse 'VALD' Data via Our External 'APIs'

Version 2.0.0

Description Provides helper functions and wrappers to simplify authentication, data retrieval, and result processing from the 'VALD' 'APIs'.

Designed to streamline integration for analysts and researchers working with 'VALD's external 'APIs'.

For further documentation on integrating with 'VALD' 'APIs', see:

<<https://support.vald.com/hc/en-au/articles/23415335574553-How-to-integrate-with-VALD-APIs>>.

For a step-by-step guide to using this package, see:

<<https://support.vald.com/hc/en-au/articles/48730811824281-A-guide-to-using-the-valdr-R-package>>.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Imports httr, base64enc, keyring, jsonlite

NeedsCompilation no

Author Kieran Harrison [aut, cre],
VALD Support [ctb],
VALD [cph] (Copyright holder)

Maintainer Kieran Harrison <k.harrison@vald.com>

Repository CRAN

Date/Publication 2025-09-01 03:10:02 UTC

Contents

.retry_key_get	2
get_config	3
get_forcedecks_data	3
get_forcedecks_result_definitions_only	4
get_forcedecks_tests_only	4
get_forcedecks_tests_trials	5

get_forcedecks_trials_only	6
get_forceframe_data	6
get_forceframe_tests_only	7
get_forceframe_test_by_id	8
get_nordbord_data	9
get_nordbord_tests_only	9
get_nordbord_test_by_id	10
get_profiles_only	11
get_start_date	11
set_credentials	12
set_start_date	12
Index	13

.retry_key_get	<i>Internal helper function to retry reading a key from the system keyring. This handles potential intermittent delays after writing to the keyring.</i>
----------------	--

Description

Internal helper function to retry reading a key from the system keyring. This handles potential intermittent delays after writing to the keyring.

Usage

```
.retry_key_get(service, username, retries = 5, delay = 0.5)
```

Arguments

- service Character. Keyring service name (e.g., "valdr_credentials").
- username Character. Keyring username (e.g., "client_id").
- retries Integer. Number of retry attempts before giving up (default 5).
- delay Numeric. Delay in seconds between retry attempts (default 0.5).

Value

Character scalar. The retrieved credential value. Will throw an error if unable to retrieve a valid, non-blank value after all retries.

get_config	<i>Retrieve stored VALD configuration</i>
------------	---

Description

Returns the configuration list previously set by `set_credentials()`. If credentials have not been set, this function will raise an error.

Usage

```
get_config(safe = TRUE, quiet = FALSE)
```

Arguments

safe	Logical; if TRUE (default), sensitive values are redacted in printed output (only when not quiet).
quiet	Logical; if TRUE, suppresses printed output (default FALSE).

Value

A named list containing the stored VALD configuration values for the current user. Sensitive values are redacted when printed with `safe = TRUE`. Returned invisibly.

get_forcedecks_data	<i>Run full initial data fetch from the VALD ForceDecks API and External Profiles API</i>
---------------------	---

Description

This function is intended for first-time use or a full refresh of all datasets. It retrieves profiles, result definitions, tests (from a specified start date), and trials.

Usage

```
get_forcedecks_data(start_date = NULL)
```

Arguments

start_date	In ISO 8601 UTC format (e.g., "2025-06-25T00:00:00Z") indicating the start of the test retrieval window.
------------	--

Value

A named list with data frames: `profiles`, `result_definitions`, `tests`, and `trials`. Each element contains the respective dataset fetched from the ForceDecks API.

Examples

```
## Not run:  
# Fetch all data (profiles, results, tests, trials)  
data <- get_forcedecks_data()  
View(data$profiles)  
  
## End(Not run)
```

```
get_forcedecks_result_definitions_only  
  Get only ForceDecks result definitions
```

Description

Wrapper around `get_forcedecks_result_definitions()` to refresh result definitions. Typically called infrequently unless definitions are known to have changed.

Usage

```
get_forcedecks_result_definitions_only()
```

Value

A data frame where each row corresponds to a ForceDecks result definition retrieved from the API. Returned invisibly.

Examples

```
## Not run:  
# Fetch result definitions  
results <- get_forcedecks_result_definitions_only()  
View(results)  
  
## End(Not run)
```

```
get_forcedecks_tests_only  
  Get only ForceDecks test data
```

Description

Wrapper around `get_forcedecks_tests()` if the user only wants test-level data without trials.

Usage

```
get_forcedecks_tests_only(start_date = NULL)
```

Arguments

start_date In ISO 8601 UTC format (e.g., "2025-06-25T00:00:00Z") indicating the start of the test retrieval window.

Value

A data frame containing ForceDecks test-level data.

Examples

```
## Not run:
# Fetch only tests
tests <- get_forcedecks_tests_only()
View(tests)

## End(Not run)
```

```
get_forcedecks_tests_trials
```

Run a standard session to get new ForceDecks tests and trials only

Description

Use this when profiles and result definitions have already been downloaded previously.

Usage

```
get_forcedecks_tests_trials(start_date = NULL)
```

Arguments

start_date In ISO 8601 UTC format (e.g., "2025-06-25T00:00:00Z") indicating the start of the test retrieval window.

Value

A named list with two data frames: `tests` and `trials`. These contain newly retrieved ForceDecks tests and their associated trial results.

Examples

```
## Not run:
# Fetch tests and trials only
session <- get_forcedecks_tests_trials()
View(session$tests)
View(session$trials)

## End(Not run)
```

`get_forcedecks_trials_only`*Get trials for an existing test data frame*

Description

Useful for re-running or extending analysis without re-downloading tests.

Usage

```
get_forcedecks_trials_only(tests_df)
```

Arguments

`tests_df` A data frame of tests (from `get_forcedecks_tests()` or a previous session)

Value

A data frame containing trial-level results corresponding to the input tests.

Examples

```
## Not run:  
# Fetch trials based on existing tests  
tests <- get_forcedecks_tests_only()  
trials <- get_forcedecks_trials_only(tests)  
View(trials)  
  
## End(Not run)
```

`get_forceframe_data` *Get ForceFrame test data*

Description

Wrapper around `get_forceframe_tests()` that also calls `get_profiles()` to ensure profile data is available before retrieving ForceFrame test data. Intended for use when you want to fetch Profiles information as well as ForceFrame tests from the API.

Usage

```
get_forceframe_data(start_date = NULL, profile_id = NULL)
```

Arguments

- start_date** (Optional) A UTC ISO 8601 datetime string (e.g. "2025-06-25T00:00:00Z") used to filter results by modification time. Input as a string.
- profile_id** (Optional) A specific profile ID to filter results for a single athlete. Input as a string.

Value

A data frame containing Profiles information and a data frame containing ForceFrame test data.

Examples

```
## Not run:  
# Fetch all recent ForceFrame tests along with Profiles information  
tests <- get_forceframe_data()  
View(tests)  
  
# Fetch ForceFrame tests for a specific profile  
get_forceframe_data(profile_id = "abc123")  
  
## End(Not run)
```

```
get_forceframe_tests_only  
  Get only ForceFrame test data
```

Description

Wrapper around `get_forceframe_tests()` to retrieve ForceFrame test data. Intended for use when you want to fetch ForceFrame tests.

Usage

```
get_forceframe_tests_only(start_date = NULL, profile_id = NULL)
```

Arguments

- start_date** (Optional) A UTC ISO 8601 datetime string (e.g. "2025-06-25T00:00:00Z") used to filter results by modification time. Input as a string.
- profile_id** (Optional) A specific profile ID to filter results for a single athlete. Input as a string.

Value

A data frame where each row corresponds to a ForceFrame test retrieved from the API. Returned invisibly.

Examples

```
## Not run:  
# Fetch all recent ForceFrame tests  
tests <- get_forceframe_tests_only()  
View(tests)  
  
# Fetch ForceFrame tests for a specific profile  
get_forceframe_tests_only(profile_id = "abcd1234-ab12-cd34-ef56-abcdef123456")  
  
## End(Not run)
```

get_forceframe_test_by_id

Get a single ForceFrame test by ID

Description

Wrapper around `get_forceframe_tests_by_id()` to retrieve a specific ForceFrame test. Intended for use when you want to fetch a single ForceFrame test record.

Usage

```
get_forceframe_test_by_id(test_id)
```

Arguments

`test_id` (Required) The unique test ID for the ForceFrame test you want to retrieve.

Value

A data frame with one row corresponding to the requested ForceFrame test. Returned invisibly.

Examples

```
## Not run:  
# Fetch a ForceFrame test by ID  
test <- get_forceframe_test_by_id("abcd1234-ab12-cd34-ef56-abcdef123456")  
View(test)  
  
## End(Not run)
```

get_nordbord_data	<i>Get NordBord test data</i>
-------------------	-------------------------------

Description

Wrapper around `get_nordbord_tests()` that also calls `get_profiles()` to ensure profile data is available before retrieving NordBord test data. Intended for use when you want to fetch Profiles information as well as NordBord tests from the API.

Usage

```
get_nordbord_data(start_date = NULL, profile_id = NULL)
```

Arguments

start_date	(Optional) A UTC ISO 8601 datetime string (e.g. "2025-06-25T00:00:00Z") used to filter results by modification time. Input as a string.
profile_id	(Optional) A specific profile ID to filter results for a single athlete. Input as a string.

Value

A data frame containing Profiles information and a data frame containing NordBord test data.

Examples

```
## Not run:
# Fetch all recent NordBord tests along with Profiles information
tests <- get_nordbord_data()
View(tests)

# Fetch NordBord tests for a specific profile
get_nordbord_data(profile_id = "abcd1234-ab12-cd34-ef56-abcdef123456")

## End(Not run)
```

get_nordbord_tests_only	<i>Get only NordBord test data</i>
-------------------------	------------------------------------

Description

Wrapper around `get_nordbord_tests()` to retrieve NordBord test data. Intended for use when you want to fetch NordBord tests.

Usage

```
get_nordbord_tests_only(start_date = NULL, profile_id = NULL)
```

Arguments

start_date (Optional) A UTC ISO 8601 datetime string (e.g. "2025-06-25T00:00:00Z") used to filter results by modification time. Input as a string.

profile_id (Optional) A specific profile ID to filter results for a single athlete. Input as a string.

Value

A data frame where each row corresponds to a NordBord test retrieved from the API. Returned invisibly.

Examples

```
## Not run:
# Fetch all recent NordBord tests
tests <- get_nordbord_tests_only()
View(tests)

# Fetch NordBord tests for a specific profile
get_nordbord_tests_only(profile_id = "abcd1234-ab12-cd34-ef56-abcdef123456")

## End(Not run)
```

```
get_nordbord_test_by_id
```

Get a single NordBord test by ID

Description

Wrapper around `get_nordbord_tests_by_id()` to retrieve a specific NordBord test. Intended for use when you want to fetch a single NordBord test record.

Usage

```
get_nordbord_test_by_id(test_id)
```

Arguments

test_id (Required) The unique test ID for the NordBord test you want to retrieve.

Value

A data frame with one row corresponding to the requested NordBord test. Returned invisibly.

Examples

```
## Not run:
# Fetch a NordBord test by ID
test <- get_nordbord_test_by_id("abcd1234-ab12-cd34-ef56-abcdef123456")
View(test)

## End(Not run)
```

get_profiles_only	<i>Get only VALD profiles</i>
-------------------	-------------------------------

Description

Wrapper around get_profiles() to retrieve VALD profiles. Useful if profile data needs to be refreshed independently.

Usage

```
get_profiles_only()
```

Value

A data frame containing VALD profiles information for the stored tenant_id.

Examples

```
## Not run:
# Fetch profiles
profiles <- get_profiles_only()
View(profiles)

## End(Not run)
```

get_start_date	<i>Retrieve the start date from config</i>
----------------	--

Description

Returns the saved start date string from the config file.

Usage

```
get_start_date()
```

Value

A character scalar containing the start date string in ISO 8601 format previously saved to configuration.

set_credentials	<i>Set and Save VALD API Credentials</i>
-----------------	--

Description

Securely stores VALD API credentials in the system keyring and saves non-sensitive configuration to a JSON config file in the user’s home directory for reuse across sessions.

Usage

set_credentials(client_id, client_secret, tenant_id, region)

Arguments

- client_id Your VALD API Client ID (stored securely in keyring)
- client_secret Your VALD API Client Secret (stored securely in keyring)
- tenant_id Your VALD Tenant ID
- region The VALD data region code (e.g., "aue", "use", "euw")

Details

Sensitive values (client ID and secret) are never written to disk and are retrieved securely from the keyring when needed.

Value

Invisibly returns TRUE if credentials and configuration were saved successfully.

set_start_date	<i>Set and persist the start date</i>
----------------	---------------------------------------

Description

Saves the provided ISO 8601 start date to the config file.

Usage

set_start_date(start_date)

Arguments

- start_date Date in ISO 8601 UTC format, e.g., "2025-06-25T00:00:00Z"

Value

A logical scalar (TRUE), returned invisibly, indicating that the start date was saved and persisted successfully.

Index

.retry_key_get, [2](#)

get_config, [3](#)
get_forcedecks_data, [3](#)
get_forcedecks_result_definitions_only,
[4](#)
get_forcedecks_tests_only, [4](#)
get_forcedecks_tests_trials, [5](#)
get_forcedecks_trials_only, [6](#)
get_forceframe_data, [6](#)
get_forceframe_test_by_id, [8](#)
get_forceframe_tests_only, [7](#)
get_nordbord_data, [9](#)
get_nordbord_test_by_id, [10](#)
get_nordbord_tests_only, [9](#)
get_profiles_only, [11](#)
get_start_date, [11](#)

set_credentials, [12](#)
set_start_date, [12](#)